

# MATERIAL SAFETY DATA SHEET

**This product is classified as a Hazardous Substance according to criteria of NOHSC Australia**  
 Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code for transport by Rail and Air

## 1. IDENTIFICATION OF THE MATERIAL

Product Name: Other Names; Product Code: Supplier:	<b>SPRAY BOOTH COATING</b> Cam Booth Coating CSTRIPC Automotive Colour and equipment ABN 12 003 484 428 66 Marigold Street Revesby NSW 2212	Phone Fax: Internet: Email	+612 9771 1600 +612 9792 2403 <a href="http://www.ace-australia.com.au">www.ace-australia.com.au</a> <a href="mailto:sales@ace-australia.com.au">sales@ace-australia.com.au</a>
---	---	-------------------------------------	--

**Distributor in New Zealand**  
 R A Johnstone & Co Ltd  
 739 Great South Road, Otahuhu  
 Auckland. New Zealand  
 Ph :+64 9 261 0333  
 Fax:+64 9 261 0330  
[www.raj.co.nz](http://www.raj.co.nz)

Major Uses and Methods of Application: Coating for spray booths to protect spray build up on walls. Applied by brush or spray, water wash off.

Emergency telephone in New Zealand National Poison Center(24 hours):0800 POISON [764 766]

## 2. COMPOSITION

	CAS No.	PROPORTION
Ethanol	64-17-5	30 – 60 % w/w
Water	7732-18-5	30 – 60% w/w
Poly Vinyl Alcohol resin		10 - < 30% w/w

## 3. HAZARDS IDENTIFICATION

Risk Phrases: Highly Flammable



## 4. FIRST AID MEASURES

For advice, contact a Poisons information Centre (Phone Australia 1131 126, New Zealand 0 800 764766)

Swallowed:	Rinse mouth with water. If swallowed DO NOT INDUCE vomiting. Give a glass of water. Seek medical attention
Eye:	Flush with flowing water for at least 15 minutes, and if symptoms persist, seek medical attention.
Skin:	Remove contaminated clothing, wash skin thoroughly with soap and water. Wash contaminated clothing before reuse
Inhalation:	Remove source of contamination or move person to fresh air. Give artificial respiration if breathing has stopped. Seek medical attention
Advice to Doctor:	Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

If involved in a fire use foam, CO<sub>2</sub>, water fog or spray.

## 6. ACCIDENTAL RELEASE MEASURES

Spills: Spilled liquid may make floors and surfaces slippery. Contain spill and recover spilled liquid for safe disposal. Remainder can be soaked into an inert absorbent (vermiculite, sand, etc.) and residual washed off.

## 7. HANDLING AND STORAGE

Handling:      WARNING: When opening container place a rag over cap and remove slowly to release internal pressure in the container  
Avoid skin and eye contact and breathing in vapour. Ensure all potential sources of ignition are eliminated in and near the work area. DO NOT SMOKE

Storage: Store away from heat and open flame

## 8. EXPOSURE AND PERSONAL PROTECTION

(Not established, recommended value) 400 ppm TWA)

Personal Protection:

Eye protection: Safety glasses, goggles or face shield as required

Hand Protection: PVC, neoprene or nitrile rubber gloves

Footwear: Rubber boots

Respiratory Protection: No special ventilation required

Safety showers with eyewash should be provided in all areas where product is handled.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear viscous liquid, alcoholic odour

Boiling Range: 78 - 100°C

Specific Gravity: 0.93 @20°C

Flash Point ASTM D 93: 13°C

pH: Approx 7

Solubility in water: soluble

Volatiles by volume: > 70%

## 10. STABILITY AND REACTIVITY

Stable under ordinary conditions of use and storage. Carbon dioxide and carbon monoxide may form when heated to decomposition.

## 11. TOXICOLOGICAL INFORMATION

Swallowed: Not harmful. Irritant to mouth, throat and digestive tract. Vomiting, dizziness, disorientation and CNS depression

Eye: Moderate irritant  
Skin: Prolonged and repeated contact may dry out the skin.  
Inhalation: Euphoria and dizziness. Irritation to nose and throat.

#### 12. ECOLOGICAL INFORMATION

Keep out of sewers, storm drains, surface waters and soil

#### 3.DISPOSAL

For small spills or drips, wipe up and dispose in approved waste container. For large spills, contain and pump into waste containers for disposal by an approved method recover spilled liquid for safe disposal. Remainder can be soaked into an inert absorbent (vermiculite, sand, etc.) and residual washed off. Dispose absorbed and unrecoverable material to an approved site. Consult local authority.

#### 14. TRANSPORT INFORMATION

U.N. Number: 1170 Hazchem Code: 2[Y] E  
D. G Class: 3 Packaging Group: III



#### 15. REGULATORY INFORMATION

The HSNO Approval Number for this Group Standard is HSR002662 Surface Coatings & Colourants (Flammable)

Risk Phrase: R11 Highly Flammable

Safety Phrase: S16 Keep away from sources of ignition

#### 16. OTHER INFORMATION

Contact: Technical Manager  
Telephone (02) 9771 1600

---

The information and recommendations in this publication are to the best of our knowledge accurate at the time of publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or process. Nothing herein is to be construed as warranty, expressed or implied. In all cases, it is the responsibility of the user to determine the applicability of such information or the suitability of any products for their own particular use

END OF MSDS