

1. Identification of the substance/preparation and of the company

Trade name	Distributor in New Zealand
Uniflex MS schwarz/grau/beige	R A Johnstone & Co Ltd
Use of the substance / preparation	739 Great South Road, Otahuhu
Sealant	PO Box 97 948 SAMC. Manukau 2240
Manufacturer / marketer identification	Auckland. New Zealand
VOSSCHEMIE GmbH	Ph :+64 9 261 0333
Esinger Steinweg 50	Fax:+64 9 261 0330
D-25436 Uetersen	www.raj.co.nz
Tel. +49-4122/717-0 Fax. +49-4122/717158	Emergency telephone in New Zealand
Information provided by:	National Poison Center(24 hours):
Laboratory / Telephone: +49-4122-717-0	0800 POISON [764 766]
Emergency information:	
Giftinformationszentrum(GIZ)-Nord, Göttingen	
Telephone Numbers: +49-551-19240, +49-551-383180	

2. Composition/information on ingredients**Chemical characterization**

Description
Sealing compound based on copolymer

Dangerous components

CAS No.	EC No	content	unit	danger	symbol	R phrases
90622-57-4	292-459-0	<	10 %	Xn		R53, R65, R66
Isoparaffin mixture						

Full text of R-Phrases: see under section 16.

**3. Hazards identification**

+ Contains [3-(2-Aminoethylamino)propyl]trimethoxysilane. May produce an allergic reaction.

The HSNO Approval Number for this Group Standard is HSR002624.

4. First aid measures**First aid measures / general indications**

Pay attention to self-protection.
Remove contaminated clothes without delay.

First Aid measures / inhalation

Provide for fresh air, if complaints occur, consult a doctor immediately.
In case of unconsciousness place and transport casualty in stable position (lying sideways).

First Aid measures / skin contact

Remove mechanically and wash off with plenty of soap and water.

First Aid measures / eye contact

Rinse immediately with plenty of water with eyelid open (for at least 15 minutes), then send for a doctor immediately.

First Aid measures / ingestion

Do not induce vomiting. Seek immediately for medical attention.

Use self contained air breathing equipment or filter respirator
(for short time use only)
Recommended: filter type A, colour brown.

Hand protection
Protective gloves recommended.
Use skin protective barrier cream

Eye protection
Wear safety glasses in case risk to eye contact exists.

Hygiene measures
Apply a suitable skin protective agent before work.
Do not eat, drink or smoke during work.
Wash hands before pauses and when ending work.
Remove contaminated clothes immediately.
Store working clothes separately.

9. Physical and chemical properties

Appearance

Form : pasty
Colour : coloured
Odour : solvent-like

Security-relevant data

Flash point: °C
Method : not applicable

Ignition temperature : > 200 °C
Method :

Lower explosion limit: 0,4 % vol
Method :

Upper explosion limit: 7 % vol
Method :

Vapour pressure: 20°C < 10 mbar
Method :

Density at: 20°C 1,5 g/cm³
Method :

Solubility in water: insoluble

Solvent content: 9,7 %

10. Stability and reactivity

Dangerous reactions

exothermic reaction with acids and strong reducing agents

Hazardous decomposition products

In case of fire formation of nitrous gases possible.
Contact with water liberates methanol.

Thermal decomposition

Not to be considered if duly stored and manipulated.

11. Toxicological information

Prolonged or repeated skin contact can cause skin irritation.

12. Ecological information

Do not allow to enter the ground, natural waters or the drain.

13. Advice on disposal

Disposal / product
In accordance with local administrative provisions,
take to an appropriate incineration installation,

Waste code no. / name of waste (only for Germany)

08 04 09 Klebstoff- und Dichtmassenabfälle, die organische
Lösemittel oder andere gefährliche Stoffe enthalten

The waste codes quoted are only recommendations. Other waste
codes may also be possible with regard to different regional
regulations.

14. Transport information

Non-hazardous transport goods within the meaning of the hazardous
goods regulations.

15. Regulatory information

Labelling [The HSNO Approval Number for this Group Standard is HSR002624.](#)

S phrases

S 02

Keep out of reach of children

S 46

If swallowed, seek medical advice immediately and show
this container or label.

Special labelling for certain preparations

Contains [3-(2-Aminoethylamino)propyl]trimethoxysilane. May
produce an allergic reaction.

Safety data sheet available for professional user on request.

National regulations (D)

The legal regulations for limited employment, e.g. the law for
the protection of youth work and the decree for the legal
protection of motherhood, have to be observed.

TA-Luft (Technical guidance air): Class III 9,7%

Class of danger to water (WGK):

substances slightly hazardous to water (own assessment)

Consult the technical leaflets by BG-Chemie (Employment Accident
Insurance Fund for the Chemical Industry)

M 017 Lösemittel

16. Other information

Relevant R phrases

R 53

May cause long-term adverse effects in the aquatic
environment

R 65

Harmful: may cause lung damage if swallowed

R 66

Repeated exposure may cause skin dryness or cracking

* + Data changed compared with the previous version.

Sections where no data are entered indicate that no data are
known, or no experience is available. This does not justify the
assumption that no danger can arise from the relevant point under
consideration.

The information given is based on the current state of our
knowledge and experience. The safety data sheet describes
products with regard to safety requirements. The data do not
represent a guarantee of properties.

This product may only be used according to its foreseen aim.