

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 07.01.2009

V - 1

Revision: 07.01.2009

1 Identification of the substance/preparation and of the company/undertaking

- **Product details** **Distributor in New Zealand**
- **Trade name:** **CARSYSTEM KUNSTSTOFF-HAFTVERMITTLER** R A Johnstone & Co Ltd
- **Application of the substance / the preparation** Priming 739 Great South Road, Otahuhu
- **Manufacturer/Supplier:** PO Box 97 948 SAMC. Manukau 2240
 Vosschemie GmbH Auckland. New Zealand
 Esinger Steinweg 50 Ph :+64 9 261 0333
 D-25436 Uetersen Fax:+64 9 261 0330
 Phone: +49 4122 717 0 Fax: +49 4122 717158 info@vosschemie.de www.raj.co.nz
- **Further information obtainable from:** **Emergency telephone in New Zealand**
 Abteilung Labor / +49-4122-717-0 **National Poison Center(24 hours):**
 s.schaller@vosschemie.de **0800 POISON [764 766]**
- **Information in case of emergency:** **0800 POISON [764 766]**
 Giftinformationszentrum (GIZ)-Nord, Goettingen, Deutschland
 +49-551-19240, +49-551-383180

2 Hazards identification

· **Hazard description:**



Xi Irritant
F+ Extremely flammable



· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Contact with skin and inhalation of aerosols/ vapours of the preparation should be avoided.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Warning! Pressurized container.

Has a narcotizing effect.

The HSNO Approval Number for this Group Standard is HSR002515.

R 12 Extremely flammable.

R 36 Irritating to eyes.

R 66 Repeated exposure may cause skin dryness or cracking.

R 67 Vapours may cause drowsiness and dizziness.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

100.0 % by mass of the contents are flammable

Keep out of the reach of children

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

3 Composition/information on ingredients

· **Chemical characterization**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 141-78-6	ethyl acetate	25-50%
EINECS: 205-500-4	Xi, F; R 11-36-66-67	
CAS: 106-97-8	butane	10-25%
EINECS: 203-448-7	F+; R 12	

(Contd. on page 2)





Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 07.01.2009

V - 1

Revision: 07.01.2009

Trade name: CARSYSTEM KUNSTSTOFF-HAFTVERMITTLER

		(Contd. of page 1)
CAS: 74-98-6 EINECS: 200-827-9	propane  F+; R 12	10-25%
CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate R 10-66-67	10-25%
CAS: 108-88-3 EINECS: 203-625-9	toluene Repr. Cat. 3;  Xn,  Xi,  F; R 11-38-48/20-63-65-67	2.5-<5%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- **General information:** Take affected persons out into the fresh air.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.

5 Fire-fighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:**
Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.

6 Accidental release measures

- **Person-related safety precautions:**
Keep away from ignition sources.
Ensure adequate ventilation
Use respiratory protective device against the effects of fumes/dust/aerosol.
Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Ensure adequate ventilation.
Dispose of the material collected according to regulations.
Do not flush with water or aqueous cleansing agents
- **Additional information:** See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Keep away from heat and direct sunlight.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
Avoid contact with the eyes and skin.
Open and handle receptacle with care.

(Contd. on page 3)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 07.01.2009

V - 1

Revision: 07.01.2009

Trade name: CARSYSTEM KUNSTSTOFF-HAFTVERMITTLER

(Contd. of page 2)

- **Information about fire - and explosion protection:**
Fumes can combine with air to form an explosive mixture.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
Keep container tightly sealed.
Do not seal receptacle gas tight.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

141-78-6 ethyl acetate

WEL (Great Britain)	Short-term value: 400 ppm Long-term value: 200 ppm
---------------------	---

106-97-8 butane

WEL (Great Britain)	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
---------------------	---

123-86-4 n-butyl acetate

WEL (Great Britain)	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
---------------------	---

108-88-3 toluene

WEL (Great Britain)	Short-term value: 384 mg/m ³ , 100 ppm Long-term value: 191 mg/m ³ , 50 ppm Sk
---------------------	--

- **Additional information:** The lists valid during the making were used as basis.

- **Personal protective equipment:**
- **General protective and hygienic measures:**
Do not eat, drink, smoke or sniff while working.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Respiratory protection:** Not required.
- **Protection of hands:**



Protective gloves

Solvent resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 4)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 07.01.2009

V - 1

Revision: 07.01.2009

Trade name: CARSYSTEM KUNSTSTOFF-HAFTVERMITTLER

(Contd. of page 3)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:**

Natural rubber, NR

- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

9 Physical and chemical properties

- **General Information**

Form:	Aerosol
Colour:	Colourless
Odour:	Characteristic

- **Change in condition**

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: Not applicable, as aerosol.

- **Flash point:** Not applicable, as aerosol.

- **Self-igniting:** Product is not selfigniting.

- **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

- **Explosion limits:**

Lower:	1.2 Vol %
Upper:	11.5 Vol %

- **Vapour pressure at 20°C:** 8300 hPa

- **Density at 20°C:** 0.77 g/cm³

- **Solubility in / Miscibility with**

water: Not miscible or difficult to mix.
VOC (EC) 2004/42/IIB (e) (840) <830

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.

(Contd. on page 5)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 07.01.2009

V - 1

Revision: 07.01.2009

Trade name: CARSYSTEM KUNSTSTOFF-HAFTVERMITTLER

(Contd. of page 4)

· **Dangerous decomposition products:** No dangerous decomposition products known.**11 Toxicological information**· **Acute toxicity:**· **LD/LC50 values relevant for classification:****141-78-6 ethyl acetate**

Oral LD50 5620 mg/kg (rabbit)

Inhalative LC50/4 h 1600 mg/l (rat)

108-88-3 toluene

Oral LD50 5000 mg/kg (rat)

Dermal LD50 12124 mg/kg (rabbit)

Inhalative LC50/4 h 31 mg/l (rat)

· **Primary irritant effect:**· **on the skin:** No irritant effect.· **on the eye:** Irritating effect.· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

· **Sensitisation** No sensitizing effects known.**12 Ecological information**· **Ecotoxicological effects:**· **Aquatic toxicity:****108-88-3 toluene**

EC 50/ 96h 10 - 100 mg/l (daphnia)

· **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations· **Product:**· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 01 11 waste paint and varnish containing organic solvents or other dangerous substances

15 01 04 metallic packaging

· **Uncleaned packaging:**· **Recommendation:** Non contaminated packagings may be recycled.

GB

(Contd. on page 6)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 07.01.2009

V - 1

Revision: 07.01.2009

Trade name: CARSYSTEM KUNSTSTOFF-HAFTVERMITTLER

(Contd. of page 5)

14 Transport information

· Land transport ADR/RID (cross-border)



- ADR/RID class: 2 5F Gases.
- Danger code (Kemler): 23
- UN-Number: 1950
- Packaging group: -
- Hazard label: 2.1
- Description of goods: 1950 AEROSOLS

· Maritime transport IMDG:



- IMDG Class: 2.1
- UN Number: 1950
- Label: 2.1
- Packaging group: -
- EMS Number: F-D,S-U
- Marine pollutant: No
- Proper shipping name: AEROSOLS

· Air transport ICAO-TI and IATA-DGR:



- ICAO/IATA Class: 2.1
- UN/ID Number: 1950
- Label: 2.1
- Packaging group: -
- Proper shipping name: AEROSOLS, flammable

15 Regulatory information

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:



Xi Irritant
F+ Extremely flammable

The HSNO Approval Number for this Group Standard is HSR002515.

· Risk phrases:

In use, may form flammable/explosive vapour-air mixture.
12 Extremely flammable.

(Contd. on page 7)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 07.01.2009

V - 1

Revision: 07.01.2009

Trade name: CARSYSTEM KUNSTSTOFF-HAFTVERMITTLER

(Contd. of page 6)

36 Irritating to eyes.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

Safety phrases:

2 Keep out of the reach of children.

9 Keep container in a well-ventilated place.

16 Keep away from sources of ignition - No smoking.

23 Do not breathe aerosol.

25 Avoid contact with eyes.

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

33 Take precautionary measures against static discharges.

43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.

46 If swallowed, seek medical advice immediately and show this container or label.

51 Use only in well-ventilated areas.

60 This material and its container must be disposed of as hazardous waste.

64 If swallowed, rinse mouth with water (only if the person is conscious).

Special labelling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

100.0 % by mass of the contents are flammable

Keep out of the reach of children

National regulations:

Information about limitation of use: Employment restrictions concerning juveniles must be observed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant R-phrases

10 Flammable.

11 Highly flammable.

12 Extremely flammable.

36 Irritating to eyes.

38 Irritating to skin.

48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

63 Possible risk of harm to the unborn child.

65 Harmful: may cause lung damage if swallowed.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

Department issuing MSDS: Abteilung Labor

Contact: Frau S. Schaller