



01/2009

## :: Elastic weiss

polyester fine putty white

### CHARACTERISTICS

Elastic weiss is a 2K-polyester filler developed specially for the body painter and fulfilling the highest demands of quality

- High standard of quality
- The optimum working material for the body painter.
- For use on steel surfaces only
- Not for use on zinc and aluminium surfaces

### APPLICATION

Because of its qualities of filling pores in the area of filling and base putty area, this fine putty can also be used to repair small scratches and paint defects.

### PRODUCT DATA

- Delivery viscosity at 20°C: as a paste
- VOC content 2004/42/IIIB (b) (250) <250g/l
- Shade: white

### HANDLING

The base must be clean, dry and grease-free.

#### DOSING

Addition of 2-3 % by weight hardener paste

Overdosing of the hardener paste is to be avoided. Bleeding-through and colour changes

in the finishing coat might be the result.

Pot life:

At +20°C room temperature, 3-4 minutes.



01/2009

**REACTION TEMPERATURE**

At least +5°C.

**APPLICATION:**

Spread on with a spatula

Air drying at +20°C room temperature, 15 - 20 minutes

**SANDABILITY:**

Following drying times given.

**As filling putty**

First sanding – dry with P80 - P120

Re-sanding - dry with P120 - 240

**As fine putty**

First sanding - dry with P120 - P180

Re-sanding - dry with P180 - P240

**REWORKING:**

The fine putty can be gone over with CS Spray.

**STORAGE:**

Ca. 6 - 8 months at 18 - 20° C in closed original container

**SAFETY ISSUES**

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged



01/2009

with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Security Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE