



1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Name of product

CA-Activator Spray (GB) Code-Nr. 12500-2

Manufacturer/distributor

WEICON GmbH & Co. KG
Königsberger Straße 255, DE-48157 Münster
Postbox 84 60, DE-48045 Münster
Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322-244
E-Mail : info@weicon.de
Internet : www.weicon.de

Distributor in New Zealand

R A Johnstone & Co Ltd
739 Great South Road, Otahuhu
PO Box 97 948 SAMC. Manukau 2240
Auckland. New Zealand
Ph : +64 9 261 0333
Fax: + 64 9 261 0330
www.raj.co.nz

Advice

Abteilung Angebote, Verkauf, Export
Phone ++49(0)251 / 9322 - 0

Emergency advice

Informationszentrale gegen Vergiftungen - Bonn
Phone ++49(0)228-19 240

Emergency telephone in New Zealand (24 hours)
National Poison Center: 0800 POISON [764 766]

Recommended intended purpose(s)

to accelerate the curing of cyanacrylat adhesives.

2. HAZARDS IDENTIFICATION

Classification

F+; R12
Xi; R38
N; R51/53



R-phrases

12 Extremely flammable.
38 Irritating to skin.
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
67 Vapours may cause drowsiness and dizziness.

Special hazards information for humans and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical characterization

Mixture of active ingredients with propellant

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification
64742-49-0	265-151-9	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha	50 - 100	F11; Xn R65; Xi R38; N R51/53; R65; R67
61641-74-5		propane/butane-mixture	20 - 50	F+, R12



4. FIRST AID MEASURES

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.
Ensure of fresh air.

In case of skin contact

In case of contact with skin wash off with water.

In case of eye contact

In case of contact with eyes rinse thoroughly with water.

In case of ingestion

Do not induce vomiting.
Medical treatment.

Physician's information / possible symptoms

The following symptoms may occur:

Unconsciousness
Delirious state
Anaesthetic state
Headache
Confusion
Dizziness

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Foam
Dry powder
Carbon dioxide

Extinguishing media which must not be used for safety reasons

water

Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

Fire gas of organic material has to be classed invariably as respiratory poison.

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.
Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Additional information

Cool endangered containers with water spray jet.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Use personal protective clothing.
Keep away sources of ignition.

Environmental precautions

Do not discharge into the drains or bodies of water..
Do not discharge into the subsoil/soil.

Methods for cleaning up

Take up with absorbent material.
After taking up the material dispose according to regulation.



7. HANDLING AND STORAGE

Advice on safe handling

Do not spray into the eyes.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Advice on protection against fire and explosion

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn even after use.

The product is combustible.

Vapours can form an explosive mixture with air.

Avoid effect of heat.

Requirements for storage rooms and vessels

Keep in closed original container.

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

Further information on storage conditions

Protect from heat and direct solar radiation.

Keep container in a well-ventilated place

Storage temperature may not exceed 50°C (=122°F).

Keep in a cool place.

Recommended storage temperature: room temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m ³]	[ml/m ³]	Spitzenb.	Remark
106-97-8	Butane	8 hours	1450	600		EH40/2005
		Short-term	1810	750		
14807-96-6	Talc respirable dust	8 hours	1			EH40/2005

Respiratory protection

Environment-independent breathing apparatus.

If ventilation insufficient, wear respiratory protection.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Nitrile rubber; 0,1mm; 480min;60min.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Eye protection

safety goggles

Skin protection

protective clothing

General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink, smoke or take drugs.

Wash hands before breaks and after work.



12. ECOLOGICAL INFORMATION

General regulation

Do not allow uncontrolled leakage of product into the environment.
Product is not allowed to be discharged into aquatic environment.

13. DISPOSAL CONSIDERATIONS

Waste code No.

07 01 04*
16 05 04*
20 01 99

Name of waste

other organic solvents, washing liquids and mother liquors
gases in pressure containers (including halons) containing dangerous substances
other fractions not otherwise specified

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 91/689/EEC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

Recommended cleansing agent

Alcohol

General information

For proper waste disposal a complete emptying of the tin is necessary.

14. TRANSPORT INFORMATION

Land and inland navigation transport ADR/RID

UN 1950 AEROSOLS, 2.1
transport in "limited quantities" according to 3.4 ADR LQ2 is possible

Marine transport IMDG

UN 1950 AEROSOLS, 2.1

Air transport ICAO/IATA-DGR

UN 1950 Aerosols, flammable, 2.1



15. REGULATORY INFORMATION

Remarks for classification

The product is classified and labelled in accordance with EC directives/German regulations on dangerous substances.

Classification

F+ Extremely flammable
Xi Irritant
N Dangerous for the environment

The HSNO Approval Number for this Group Standard is HSR002515.

R-phrases

12 Extremely flammable.
38 Irritating to skin.
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
67 Vapours may cause drowsiness and dizziness.

S-phrases

16 Keep away from sources of ignition - No smoking.
2 Keep out of the reach of children.
23.4 Do not breathe spray.
24 Avoid contact with skin.



51 Use only in well-ventilated areas.

Hazardous ingredients for labeling

Naphtha (petroleum), hydrotreated light, aromatic amine

Special labelling for certain preparations

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Without sufficient ventilation the formation of explosive vapour/air mixtures cannot be excluded. Keep away from ignition sources - Do not smoke. Keep out of children's reach.

VOC standard

VOC value 0,094 g/L

16. OTHER INFORMATION

Recommendend uses and restrictions

National and local regulations concerning chemicals shall be observed.

Further information

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Wording of the R-phrases specified in chapter 3 (not the classification of the formulation!)

R 11 Highly flammable.

R 12 Extremely flammable.

R 38 Irritating to skin.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 65 Harmful: may cause lung damage if swallowed.

R 67 Vapours may cause drowsiness and dizziness.