



1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Name of product

TFT/LCD Screen-Cleaner (GB) ; Code-Nr. 11208

Manufacturer/distributor

WEICON GmbH & Co. KG
Königsberger Straße 255, DE-48157 Münster
Postbox 84 60, DE-48045 Münster
Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322-244
E-Mail : info@weicon.de
Internet : www.weicon.de

Distributor in New Zealand

R A Johnstone & Co Ltd
739 Great South Road, Otahuhu
PO Box 97 948 SAMC. Manukau 2240
Auckland. New Zealand
Ph :+64 9 261 0333
Fax: + 64 9 261 0330
www.raj.co.nz

Advice

Abteilung Angebote, Verkauf, Export
Phone ++49(0)251 / 9322 - 0

Emergency advice

Informationszentrale gegen Vergiftungen - Bonn
Phone ++49(0)228-19 240

Emergency telephone in New Zealand (24 hours)
National Poison Center: 0800 POISON [764 766]

Recommended intended purpose(s)

Technical Aerosols

2. HAZARDS IDENTIFICATION

Classification

F+; R12

R-phrases

12 Extremely flammable.



Special hazards information for humans and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification
74-98-6	200-827-9	propane	10 - 20	F+ R12
106-97-8	203-448-7	butane	20 - 40	F+ R12
34590-94-8	252-104-2	(2-methoxymethylethoxy)-propanol	< 1,5	Xi R36/38

4. FIRST AID MEASURES

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Ensure of fresh air.

In case of inhalation remove the casualty into fresh air and seek medical advice.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with water.

In case of eye contact

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.



In case of ingestion

If swallowed seek medical advice immediately and show the doctor packing or label.

Physician's information / possible symptoms

The following symptoms may occur:

Unconsciousness
Delirious state
Anaesthetic state
Headache
Confusion
Dizziness

5. FIRE-FIGHTING MEASURES**Suitable extinguishing media**

Alcohol-resistant foam
Dry powder
Carbon dioxide

Extinguishing media which must not be used for safety reasons

Full water jet

Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

Danger of bursting

Fire gas of organic material has to be classed invariably as respiratory poison.

In the event of fire the following can be released:

Nitrogen oxides (NO_x)

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Additional information

Cool endangered containers with water spray jet.

Collect contaminated firefighting water separately, must not be discharged into the drains.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions**

Ensure adequate ventilation.

Keep away sources of ignition.

Environmental precautions

Do not discharge into the drains or bodies of water..

Methods for cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

7. HANDLING AND STORAGE**Advice on safe handling**

Ventilate closed rooms at ground level.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Do not spray on a naked flame or any incandescent material.

Pressurized container.

Do not pierce or burn even after use.



The product is combustible.
Avoid effect of heat.

Requirements for storage rooms and vessels

Keep in closed original container.
Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

Further information on storage conditions

Protect from direct solar radiation.
Keep container in a well-ventilated place
Storage temperature may not exceed 50°C (=122°F).
Keep in a cool place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Additional advice on system design

Sufficient ventilation and exhaustion.

Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m ³]	[ml/m ³]	Spitzenb.	Remark
106-97-8	Butane	8 hours	1450	600		EH40/2005
		Short-term	1810	750		
34590-94-8	(2-Methoxymethylethoxy) propanol	8 hours	308	50		EH40/2005

Respiratory protection

If ventilation insufficient, wear respiratory protection.
Short term: filter apparatus, Filter A/P2

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.
Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.
Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min; 60 min.

Eye protection

safety goggles

Skin protection

light protective clothing

General protective measures

Do not inhale aerosols
Avoid contact with the eyes.

Hygiene measures

At work do not eat, drink, smoke or take drugs.
Wash hands before breaks and after work.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form
aerosol

Colour
whitish

Odour
characteristic

Important health, safety and environmental information

Value	Temperature	at	Method	Remark
pH value in delivery state	not determined			



	Value	Temperature	at	Method	Remark
boiling point	-44 °C				
Flash point	< 0 °C				
Ignition temperature	365 °C				
Lower explosion limit	1,5 Vol-%				
Upper explosion limit	15 Vol-%				
Vapour pressure	8300 hPa	20 °C			Doseninnendruck
Density	not determined				
Solubility in water					immiscible
Viscosity 1 dynamic	not determined				

Explosive properties

The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .

10. STABILITY AND REACTIVITY

Conditions to avoid

Keep away from heat.

Formation of explosive gas/air mixtures.

Uncleaned empty vessels may contain product gases which can form explosive mixtures with air.

Hazardous decomposition products

carbon monoxide and carbon dioxide

Thermal decomposition

Remark No decomposition if used as directed.

11. TOXICOLOGICAL INFORMATION

Acute toxicity/Irritability/Sensitization

	Value/Validation	Species	Method	Remark
Irritability skin	non-irritant			
Irritability eye	non-irritant			
Skin sensitization	non-sensitizing			

Experiences made from practice

Inhalation causes narcotic effect/intoxication.

Additional information

Labelling in compliance with the assessment procedure specified in the EC guidelines 1999/45/EG



12. ECOLOGICAL INFORMATION

General regulation

Do not allow uncontrolled leakage of product into the environment.
Product is not allowed to be discharged into aquatic environment.

13. DISPOSAL CONSIDERATIONS

Waste code No.

15 01 04

16 05 04*

Name of waste

metallic packaging

gases in pressure containers (including halons) containing dangerous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 91/689/EEC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

General information

For proper waste disposal a complete emptying of the tin is necessary.

14. TRANSPORT INFORMATION

Land and inland navigation transport ADR/RID

UN 1950 AEROSOLS, 2.1

transport in "limited quantities" according to 3.4 ADR LQ2 is possible

Marine transport IMDG

UN 1950 AEROSOLS, 2.1

Air transport ICAO/IATA-DGR

UN 1950 Aerosols, flammable, 2.1



15. REGULATORY INFORMATION

Remarks for classification

The product is classified and labelled in accordance with EC directives.

Classification

F+ Extremely flammable

The HSNO Approval Number for this Group Standard is [HSR002515](#).

R-phrases

12 Extremely flammable.

S-phrases

16 Keep away from sources of ignition - No smoking.

24/25 Avoid contact with skin and eyes.

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

3/7 Keep container tightly closed in a cool place.

60 This material and its container must be disposed of as hazardous waste

9 Keep container in a well-ventilated place.

Special labelling for certain preparations

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Without sufficient ventilation the formation of explosive vapour/air mixtures cannot be excluded. Keep away from ignition sources - Do not smoke. Keep out of children's reach.



VOC standard
VOC value 0,058 g/L

16. OTHER INFORMATION

Recommend uses and restrictions

National and local regulations concerning chemicals shall be observed.

Further information

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Wording of the R-phrases specified in chapter 3 (not the classification of the formulation!)

R 12 Extremely flammable.

R 36/38 Irritating to eyes and skin.

Converted to New Zealand Standard by Sam Gunaratna B Sc, Post-Grad Dip in Science (University of Auckland)
Ph: 021 02776004; email: olu@ihug.co.nz *September 2008*