

MATERIAL SAFETY DATA SHEET

Date Printed: 07/28/2008

Product Code(s): 5164

1. CHEMICAL PRODUCT AND COMPANY INFORMATION

Product Name: Butter Wax

Product Code(s): 5164

Manufacturer/Supplier:

TRANSTAR AUTOBODY TECHNOLOGIES
2040 Heiserman Dr.
Brighton, MI, 48114, USA

24 Hour Emergency Phone(s):
800-424-9300 (CHEMTREC),
613-996-6666 (CANUTEC)

Business Phone: 810-220-3000

Product Use: Wax/Glaze/Compound

MSDS Prepared By: Transtar Autobody Technologies

Distributor in New Zealand

R A Johnstone & Co Ltd
739 Great South Road, Otahuhu
PO Box 97 948 SAMC. Manukau 2240
Auckland. New Zealand
Ph :+64 9 261 0333
Fax: + 64 9 261 0330
www.raj.co.nz

Emergency telephone in New Zealand (24 hours)
National Poison Center: 0800 POISON [764 766]

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% by Weight
Aliphatic Hydrocarbons	64742-47-8	15- 25%
Aliphatic Petroleum Distillates	64742-96-7	15- 25%
Kaolin Clay	1332-58-7	0 - 5%
Aliphatic Hydrocarbons (Stoddard Type)	8052-41-3	0 - 5%
Amine	110-91-8	0 - 5%

See Section 15. Regulatory Information for code descriptions
Weight percent (%) of 0.0 means chemical is in trace amounts.

3. HAZARDS IDENTIFICATION



CAUTION! COMBUSTIBLE IRRITANT.

HMIS Hazard Ratings: Health =1 , Flammability =1, Chemical Reactivity =0

Note: HMIS ratings involve data and interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this MSDS must be considered.

Potential Health Effects

Eyes: Slight to moderate irritation to the eyes.

Skin: Slight irritation to the skin. Can be absorbed through the skin. Prolonged contact with this product can cause reddening, swelling, rash scalling or blistering.

Inhalation: Minimal to slight irritation to the respiratory system.

Ingestion: Slight irritation to the digestive tract.

The HSN0 Approval Number for this Group Standard is HSR002670.

4. FIRST AID MEASURES

Seek professional medical attention for all over-exposures and/or persistent problems.

Eyes Contact: Flush eyes with clean water for a minimum of 15 minutes. Seek medical attention.

Skin Contact: Wash exposed area thoroughly with soap and water.

Inhalation: Remove person from area to fresh air. If breathing difficulty persists, seek medical attention.

Ingestion: DO NOT INDUCE VOMITTING. Seek immediate medical attention.

5. FIRE FIGHTING MEASURES

Flammable Properties

Flash Point: >200 Deg F, (93 Deg C) Method: Setaflash
Upper Explosive Limit (UEL): 13.3
Lower Explosive Limit (LEL): 0.6
Autoignition Temperature: No data

Extinguishing Media: Foam, Alcohol Foam, CO₂, Dry Chemical, Water Fog, Other.

Special Firefighting Procedures: Full fire fighter equipment including SCBA should be worn to avoid skin contact and inhalation of concentrated vapors. Minimize skin exposure. Highly toxic fumes may be generated by thermal decomposition.

Hazardous Combustion Products: Carbon monoxide, carbon dioxide, oxides of nitrogen.

Unusual Fire and Explosion Hazards: Vapors can travel to a source of ignition and flash back. Closed containers may explode when exposed to extreme heat or burst when contaminated with water (CO₂ gas evolved). Hazards apply to empty containers. Combustion generates toxic fumes.

6. ACCIDENTAL RELEASE MEASURES

For large spills or transportation accidents involving release of this

product, contact the Emergency Response Center: 800-424-9300.

Allow material to solidify and scrape up. Dispose of in accordance with all applicable federal, state and local regulations. Do not allow material to enter public sewers or water systems. Dike spill before cleaning up.

7. HANDLING AND STORAGE

Use in cool, well-ventilated areas. Keep containers closed when not in use. Keep away from incompatibles. Keep away from excessive heat and open flames. Follow all MSDS/label precautions even after container is emptied because they may retain product residues. Store in a cool area away from heat and flames. Do not reuse container when empty.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name/Exposure Limits	CAS Number
Aliphatic Hydrocarbons	64742-47-8
Aliphatic Petroleum Distillates	64742-96-7
Kaolin Clay	1332-58-7
OSHA PEL: 5 mg/m ³ , ACGIH TLV: 2 mg/m ³	
Aliphatic Hydrocarbons (Stoddard Type)	8052-41-3
OSHA PEL: 500 ppm, ACGIH TLV: 100 ppm, NIOSH: 350 mg/M ³	
IDLH: 20,000 mg/M ³	
Amine	110-91-8
OSHA PEL: 20 ppm, ACGIH TLV: 20 ppm, OTHER: NA	

Engineering Controls: Utilize engineering controls, such as ventilation and exhaust fans, to reduce occupational exposure limits (OSHA PEL & ACGIH TLV) listed above. Use with adequate ventilation. If normal ventilation is not adequate use exhaust fan.

Respiratory Protection: Utilize engineering controls to reduce emission levels below the time weighted exposure limits (ACGIH TLV & OSHA PEL). Wear an approved respirator if exposure limits are above the exposure limits listed above.

Eye Protection: Use safety glasses or splash goggles.

Skin Protection: Use chemical resistant gloves.

Safe Work Practices: Eye washes and safety showers in the workplace are recommended. Avoid contact with skin and eyes. Avoid breathing vapors. Wash hands thoroughly after using and before eating, drinking or smoking. Employee education and training in the safe use and handling of this product is required under the OSHA Hazard Communication Standard 29CFR1200. Smoking in area where this material is used should be strictly prohibited. Always use protective clothing and equipment. Remove all contaminated clothing and wash thoroughly when finished working. Keep food and drink away from material and from area where material is being used.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form: Homogeneous mixture
Physical State: Paste
Color: Yellow

Odor: Banana
Odor Threshold: No Data
Specific Gravity (water=1) 0.94
Vapor Pressure: No data
Vapor Density: Heavier than air
Material VOC: 3.17 lb/gl 379 g/l
Coating VOC: 5.16 lb/gl 618 g/l
Evaporation Rate: Slower than Butyl Acetate
Boiling Point: 263 deg F
Melting Point: No data
Freezing Point: No data
Viscosity at Ambient Temperature: No data
Solubility in Water: Partial

Octanol/Water Partition Coefficient: No data
pH: No data

10. STABILITY AND REACTIVITY

Stability: Stable

Incompatibility: Strong acids, strong bases and strong oxidizing agents.

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Effects of Exposure:

ACUTE:

INHALATION - Odor may be offensive

EYE CONTACT - Mild irritation with redness and tearing.

SKIN CONTACT - Mild irritation with redness, itching, swelling possible.

INGESTION - May cause mild gastrointestinal irritation, vomiting, nausea, & diarrhea

CHRONIC:

No chronic health effects known.

Acute Toxicity Data: No data.

Carcinogenicity: NTP -No, IARC -No, OSHA -No

This product has not been tested for carcinogenic effects. Some chemicals in this product may be identified by NTP, IARC and/or OSHA as carcinogenic, indicated above as "Yes". No further information available.

Teratology: No data.

Reproduction: No data.

Mutagenicity: No data.

12. ECOLOGICAL INFORMATION

No data.

13. DISPOSAL CONSIDERATIONS

This product when disposed represents a non-hazardous waste, as identified in 40CFR261. It is the responsibility of each waste generator to identify the proper classification of their waste streams.

14. TRANSPORT INFORMATION

The following transportation information is provided based on Transtar Autobody Technologies interpretation of shipping regulations. Each shipper is responsible for identifying, naming, marking and labeling prior to offering for transport.

USA (DOT) Status: Not regulated

Water (IMDG) Status: Not regulated

Air (ICAO,IATA) Status: Not regulated

Canada (TDG) Status: Not regulated

15. REGULATORY INFORMATION

The information listed in this section is not all inclusive of all regulations for this product or the chemical components of this product.

US Federal Regulations

TSCA Status: All known major components of this product are listed on the TSCA Inventory and/or are otherwise in compliance with TSCA.

SARA 302 (EHS) Status: No EHS chemicals present.

SARA 311/312 Status: Immediate Health Hazard, Fire Hazard

SARA 313 Status: *** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***

OSHA Status: This material meets the requirement of hazardous material and is subject to 29CFR1910.1200.

USA State Information

California Proposition 65: This product does not contain chemical(s) known to the State of California to cause cancer or birth defects or other reproductive harm.

Pennsylvania RtK Status: This material contains chemical(s) subject to notification under Pennsylvania Right to Know.

New Jersey RtK Status: This material contains chemical(s) subject to notification under New Jersey Right to Know.

Massachusetts RtK Status: This material contains chemical(s) subject to notification under Massachusetts Right to Know.

Rhode Island RtK Status: This material contains chemical(s) subject to notification under Rhode Island Right to Know.

International Regulations

Canada

DSL Status: All known major components of this product are listed on the DSL Inventory and/or are otherwise in compliance with the DSL

NDSL Status: Contains no chemicals on the NDSL

WHMIS: D2B

New Zealand

The HSNO Approval Number for this Group Standard is HSR002670.

EINECS Status: All components of this material are listed on the EINECS Inventory.

16. OTHER INFORMATION

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by Transtar Autobody Technologies to be accurate. As with all chemicals, KEEP AWAY FROM CHILDREN AND ANIMALS. FOR PROFESSIONAL USE ONLY. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

<p>Converted to New Zealand Standard by Sam Gunaratna B Sc, Post-Grad Dip in Science (University of Auckland) Ph: 021 02776004; email: olu@ihug.co.nz September 2008</p>
