



---

# PRODUCT DATA

---

1273

## *Euroflex Bumper/Trim Coat*

### **DESCRIPTION:**

Euroflex Bumper/Trim Coat is a tough, flexible polymer coating designed to restore bumpers and flexible or rigid trim to their original OEM condition, and offer a satin black, semi-gloss finish to match the "European" appearance on many late-model vehicles. Euroflex Bumper/Trim Coat has excellent adhesion to urethane, rubber and metal. It is fast drying, provides excellent adhesion and requires no priming.

### **TECHNICAL DATA:**

SOLVENTS: Toluene, Methyl Ethyl Ketone, Acetone, 2-Butoxy Ethanol  
V.O.C. CONTENT: 5.82#/gal (698g/l) and 61.86% by weight

### **APPLICATION:**

Shake well before using. Clean area to be coated with G.P. solvent or equivalent. For best results, use when can is between 70° and 90° F. Hold can 9 - 12" from surface and spray with steady, even strokes. Several thin coats are better than one thick coat. After use, invert can and spray to clean nozzle. Allow final coat to dry two hours before handling parts. Full adhesion and curing takes 24 hours. Replace metal trim and panels carefully to avoid damaging the freshly painted surfaces.

### **DEMO:**

Spray product on a piece of scrap flexible part or sheet metal. Show how quickly it covers and how well it hides. Ask prospect to try it. Also point out rapid flash time, and satin black finish.

### **COMPETITION:**

Premier Euro-black  
Rubber Seal Euro-black

### **SALES POINTS:**

- Unique polymer formula that is flexible and non-cracking
- Convenient aerosol container - no messy cleanup
- Primerless fewer application steps
- Semi-gloss, satin finish that matches factory blacked-out trim

---

*(Refer to Material Safety Data Sheet for proper handling of products listed in this bulletin.)*

### **PACKAGE SIZES:**

#1273 Euroflex Bumper/Trim Coat, 16 oz. Aerosol, 12/case

*DISCLAIMER: The technical information and suggestions for use have been compiled for your guidance and usage. Such information is based on Transtar Autobody Technologies experience and research and is believed to be reliable. As Transtar has no control over conditions in which the product is used, stored, or otherwise handled, the above information does not constitute a warranty. Buyers must assume responsibility for the suitability of the product for their purposes.*

