We create chemistry

Safety data sheet

1. Substance/preparation and manufacturer/supplier identification

Product name:
85-01 Thinner Fast

Use: Thinner

Manufacturer/supplier:
BASF New Zealand Ltd.
5E City Works Depot
77 Cook Street
Auckland Central, Auckland 1010
NEW ZEALAND
Telephone: +64 9 255-4300
Telefax number: +64 9 255-4307

Emergency information:
National Poisons Centre: 0800 764 766
BASF Emergency Advice Number: 0800 944 955 (24 hour advice in an emergency only)
BASF Emergency Advice Number: +61 3 8855 6666 (If calling from outside New Zealand)

2. Hazard identification

Classification of the substance and mixture:
Skin corrosion/irritation: Cat.2
Serious eye damage/eye irritation: Cat.2A
Aspiration hazard: Cat.1
Specific target organ toxicity — single exposure: Cat.3 (irritating to respiratory system)
Specific target organ toxicity — single exposure: Cat.3 (May cause drowsiness and dizziness.)
Specific target organ toxicity — repeated exposure: Cat.2
Hazardous to the aquatic environment - acute: Cat.2
Hazardous to the aquatic environment - chronic: Cat.3
Flammable liquids: Cat.3

Label elements and precautionary statement:

Pictogram:



Signal Word:
Danger

Hazard Statement:

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H401	Toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing and eye protection or face protection.
P264	Wash contaminated body parts thoroughly after handling.
P242	Use non-sparking tools.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P243	Take action to prevent static discharges.
P233	Keep container tightly closed.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground and bond container and receiving equipment.
P260	Do not breathe dust or mist.
P273	Avoid release to the environment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or physician if you feel unwell.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P370 + P378	In case of fire: Use water spray for extinction.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or physician.
P332 + P313	If skin irritation occurs: Get medical attention.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P337 + P313	If eye irritation persists: Get medical attention.
P314	Get medical advice/attention if you feel unwell.
P331	Do NOT induce vomiting.

Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.

Other hazards which do not result in classification:
If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

3. Composition/information on ingredients

Chemical nature

Substance nature: mixture

organic solvent

Hazardous ingredients

n-Butyl acetate

Content (W/W): >= 30 % - < 50 %	Flam. Liq.: Cat. 3
CAS Number: 123-86-4	STOT SE: Cat. 3 (drowsiness and dizziness)
	Aquatic Acute: Cat. 3

xylene

Content (W/W): >= 25 % - < 30 %	Asp. Tox.: Cat. 1
CAS Number: 1330-20-7	Flam. Liq.: Cat. 3
	Acute Tox.: Cat. 5 (Inhalation - vapour)
	Acute Tox.: Cat. 5 (oral)
	Skin Corr./Irrit.: Cat. 2
	Eye Dam./Irrit.: Cat. 2B
	STOT SE: Cat. 3 (irr. to respiratory syst.)
	STOT RE (Central nervous system, Liver, Kidney): Cat. 2
	Aquatic Acute: Cat. 2
	Aquatic Chronic: Cat. 3

ethyl acetate

Content (W/W): >= 20 % - < 25 %	Flam. Liq.: Cat. 2
CAS Number: 141-78-6	Eye Dam./Irrit.: Cat. 2A
	STOT SE: Cat. 3 (drowsiness and dizziness)

1-methoxy-2-propylacetate

Content (W/W): >= 5 % - < 7 %	Flam. Liq.: Cat. 3
CAS Number: 108-65-6	STOT SE: Cat. 3 (drowsiness and dizziness)

ethylbenzene

Content (W/W): >= 3 % - < 5 %	Asp. Tox.: Cat. 1
CAS Number: 100-41-4	Flam. Liq.: Cat. 2
	Acute Tox.: Cat. 4 (Inhalation - vapour)
	Acute Tox.: Cat. 5 (oral)
	STOT RE (Auditory organ): Cat. 2
	Aquatic Acute: Cat. 2
	Aquatic Chronic: Cat. 3

4. First-Aid Measures

General advice:
First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove affected person from danger area. Keep warm, calm and covered up. Immediately remove contaminated clothing. Never give anything by mouth to an unconscious person. In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product. Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.

If inhaled:
Immediate medical attention required. Remove the affected individual into fresh air and keep the person calm. If breathing is irregular or stopped, administer artificial respiration.

On skin contact:
If symptoms persist, seek medical advice. Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

On contact with eyes:
Remove contact lenses, if present. Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Immediate medical attention required.

On ingestion:
Summon medical aid without delay. Do not induce vomiting due to aspiration hazard. Keep at rest. Rinse mouth immediately with water.

Note to physician:
Symptoms: Eye irritation, aspiration pneumonia, dazed state, irritation of respiratory tract, skin irritation, dizziness, Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.
Hazards: If swallowed, in the event of vomiting, risk of product entering the lungs. When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.
Treatment: Symptomatic treatment (decontamination, vital functions).
Antidote: No known specific antidote.

5. Fire-Fighting Measures

Suitable extinguishing media:
carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:
water jet

Specific hazards:
Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

Special protective equipment:
Appropriate breathing apparatus may be required.

Further information:
Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

6. Accidental Release Measures

Personal precautions:
Avoid breathing vapours.For non-emergency personnel:Use personal protective clothing.Ensure adequate ventilation.Keep away from sources of ignition.For emergency responders:Advice on product handling can be found in sections 7 and 8 of this safety data sheet.Information regarding personal protective measures, see section 8.

Environmental precautions:
Do not allow to enter drains or waterways.If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency.Do not discharge into the subsoil/soil.

Methods for cleaning up or taking up:
Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents. Ensure adequate ventilation.

7. Handling and Storage

Handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:
Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is

recommended that operators should wear antistatic clothing and footwear. Solvent vapours are heavier than air and spread along floors. Vapour forms explosive mixtures with air. The relevant fire protection measures should be noted. Use explosion-proof equipment.

Storage

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

Suitable materials for containers: Stainless steel 1.4301 (V2), Carbon steel (Iron), tinned carbon steel (Tinplate)
Further information on storage conditions: Keep container dry. Keep away from heat. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Store protected against freezing.

8. Exposure controls and personal protection

Components with occupational exposure limits

ethylbenzene, 100-41-4;
TWA value 20 ppm (ACGIHTLV)
TWA value 88 mg/m3 ; 20 ppm (OEL (NZ))
STEL value 176 mg/m3 ; 40 ppm (OEL (NZ))
Skin Designation (OEL (NZ))
Skin absorption can be significant.

n-Butyl acetate, 123-86-4;
STEL value 150 ppm (ACGIHTLV)
TWA value 50 ppm (ACGIHTLV)
TWA value 713 mg/m3 ; 150 ppm (OEL (NZ))
STEL value 950 mg/m3 ; 200 ppm (OEL (NZ))

ethyl acetate, 141-78-6;
TWA value 400 ppm (ACGIHTLV)
TWA value 720 mg/m3 ; 200 ppm (OEL (NZ))

xylene, 1330-20-7;
TWA value 20 ppm (ACGIHTLV)
TWA value 217 mg/m3 ; 50 ppm (OEL (NZ))

Personal protective equipment

Respiratory protection:
Suitable respiratory protection: e.g. half-mask with A1P2 class combination filter When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators. Use A1P2 breathing-protection half mask in case of contact with aerosols.

Hand protection:
Further information on penetration time is available from the manufacturer of the glove.
Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.
The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).
Follow manufacturer's advice on use, storage, maintenance and replacement of gloves.
The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).
Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g.
nitrile gloves - material thickness: 0,7 mm
Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):
Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)
Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Eye protection:
Tightly fitting safety goggles (splash goggles) (e.g. EN 166), Required when there is a risk of eye contact.

Body protection:
Anti-static protective clothing, Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

General safety and hygiene measures:
Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Ensure adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

9. Physical and Chemical Properties

Form:	liquid	
Colour:	colourless	
Odour:	specific	
pH value:	substance/mixture is non-polar/aprotic	
Melting point:	not determined	
onset of boiling:	126 °C	(calculated)
Flash point:	28 °C	
Flammability (solid/gas):	Flammable liquid and vapour.	

Lower explosion limit:	36.0 %(V)	
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
Self heating ability:	It is not a material capable of spontaneous heating	
Explosion hazard:	not explosive	
Fire promoting properties:	not fire-propagating	
Vapour pressure:	5.00 hPa (20 °C)	(calculated)
	(50 °C) not determined	
Density:	0.873 g/cm3 (20 °C)	
Relative vapour density (air):	Heavier than air.	
Miscibility with water:	immiscible	
Partitioning coefficient n-octanol/water (log Pow):	not applicable for mixtures	
Viscosity, kinematic:	6.0 mm2/s (23 °C)	
	(40 °C) No data available.	
Flow time:	< 30 s (23 °C)	(DIN EN ISO 2431; 3 mm)

10. Stability and Reactivity

Conditions to avoid:
Avoid heat. Avoid direct sunlight. Avoid all sources of ignition: heat, sparks, open flame. Avoid freezing.

Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.

Substances to avoid:
Keep away from highly acidic or alkaline substances as well as oxidants in order to prevent exothermal reactions.

Hazardous reactions:
Vapours may form ignitable mixture with air.

When exposed to high temperatures hazardous decomposition products such as carbon monoxide, carbon dioxide, smoke, oxides of nitrogen may be produced., No hazardous decomposition products if stored and handled as prescribed/indicated.

Chemical stability:
The product is stable if stored and handled as prescribed/indicated.

Reactivity:
No hazardous reactions if stored and handled as prescribed/indicated.

11. Toxicological Information

Routes of exposure

Assessment of acute toxicity

Based on available data, the classification criteria are not met.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated and prolonged exposure to solvents at levels significantly above OELs may lead to the development of long-lasting central nervous system disorders such as chronic toxic encephalopathy, signs of toxicity include changes in behaviour and memory. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Symptoms

Eye irritation aspiration pneumonia dazed state irritation of respiratory tract skin irritation dizziness Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Irritation

Assessment of irritating effects:
The liquid splashed in the eyes may cause irritation and reversible damage. Eye contact causes irritation. Skin contact causes irritation.

Respiratory/Skin sensitization

Assessment of sensitization:
Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Assessment of mutagenicity:
Based on available data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity:
Based on available data, the classification criteria are not met.

Developmental toxicity

Assessment of teratogenicity:
Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Causes temporary irritation of the respiratory tract. Possible narcotic effects (drowsiness or dizziness).

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:
Repeated exposure may affect certain organs.

Aspiration hazard

May also damage the lung at swallowing (aspiration hazard).

12. Ecological Information

Ecotoxicity

Assessment of aquatic toxicity:
Harmful to aquatic life with long lasting effects. Toxic to aquatic life. There are no test results available for this product. Do not allow to enter drains or waterways.

Mobility

Assessment transport between environmental compartments:
No data available.

Persistence and degradability

Assessment biodegradation and elimination (H2O):
Biological degradability of hazardous substances mentioned in section 3:

Information on: ethylbenzene
Elimination information:
70 - 80 % TIC of the ThIC (28 d) (ISO 14593) (aerobic, activated sludge) Readily biodegradable (according to OECD criteria).

Information on: n-Butyl acetate
Elimination information:

80 % BOD of the ThOD (5 d) (OECD 301D; 92/69/EWG, C.4-E) (aerobic, municipal sewage treatment plant effluent)

Information on: xylene
Elimination information:
87.8 % BOD of the ThOD (28 d) (OECD Guideline 301 F) (aerobic, activated sludge, domestic, non-adapted)
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Bioaccumulation potential

Bioaccumulation potential:
No data available.

13. Disposal Considerations

Do not discharge into drains/surface waters/groundwater.
Observe national and local legal requirements.

Contaminated packaging:
Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

14. Transport Information

Domestic transport:

UN number or ID number:	UN 1263
UN proper shipping name:	PAINT RELATED MATERIAL
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	no
Special precautions for user:	None known

Further information
Hazchem Code:3Y
IERG Number:14

Sea transport
IMDG

UN number or ID number:	UN 1263
UN proper shipping name:	PAINT RELATED MATERIAL
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	no Marine pollutant: NO
Special precautions for	EmS: F-E; S-E

user:

Air transport
IATA/ICAO

UN number or ID number:	UN 1263
UN proper shipping name:	PAINT RELATED MATERIAL
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	No Mark as dangerous for the environment is needed
Special precautions for user:	None known

15. Regulatory Information

Other regulations

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.
A certified handler is not required for the handling of this substance.
Tracking requirements do not apply to this substance.

HSNO Approval Number HSR002662
Surface Coatings and Colourants (Flammable) Group Standard 2017

16. Other Information

For multi-pack systems observe material safety data sheets of all components.Restricted to professional users.

Vertical lines in the left hand margin indicate an amendment from the previous version.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

85-02 Thinner Normal

Version	Revision Date:	SDS Number:	Date of last issue: 24.12.2024
2.0	21.11.2025	000000000050800025	Date of first issue: 24.12.2024

Section 1: Identification

Product name : 85-02 Thinner Normal

Product code : 000000000050800025

Manufacturer or supplier's details

BASF Coatings and Chemetall New Zealand Limited
Level 1, 527A Rosebank Road, Avondale
Auckland 1026
New Zealand
Telephone: 008 837 464, +64 9 820 3888
Telefax number: +64 9 820 3979
E-mail address: nzadmin@basf.com

Emergency contact

Telephone: +64 9 255-4300
E-mail address: ProductSafety_EC_APAC@basf.com, nzadmin@basf.com

Emergency telephone : National Poisons Centre: 0800 764 766
BASF Emergency Advice Number: 0800 944 955 (24 hour advice in an emergency only)
BASF Emergency Advice Number: +61 3 8855 6666 (If calling from outside New Zealand)

Recommended use of the chemical and restrictions on use

Recommended use : Thinner

Section 2: Hazard identification

GHS Classification

Flammable liquids : Category 2

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation : Category 2

Specific target organ toxicity - single exposure	:	Category 3 (Respiratory system, Central nervous system)
Specific target organ toxicity - repeated exposure	:	Category 2 (Kidney, Liver, Central nervous system, Auditory system)
Aspiration hazard	:	Category 1
Hazardous to the aquatic environment - chronic hazard	:	Category 3

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements :
H225 Highly flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs (Kidney, Liver, Central nervous system, Auditory system) through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use non-sparking tools.

P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 Get medical advice/ attention if you feel unwell.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification
If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Section 3: Composition/information on ingredients

Chemical nature : organic solvent

Components

Chemical name	Common Name/Synonyms	CAS-No.	Classification	Concentration (% w/w)
n-Butyl acetate	n-butyl acetate	123-86-4	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 25 -< 50
xylene	xylenes	1330-20-7	Flammable liquids, Category 3 Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2 Specific target organ toxicity - single exposure (Respiratory system), Category 3 Specific target organ toxicity - repeated exposure (Kidney, Liver, Central nervous system), Category 2 Aspiration hazard, Category 1	>= 25 -< 50

			Hazardous to the aquatic environment - chronic hazard, Category 3	
1-methoxy-2-propylacetate	2-methoxy-1-methylethyl acetate	108-65-6	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 12.5 -< 15
ethyl acetate	ethyl acetate	141-78-6	Flammable liquids, Category 2 Serious eye damage/eye irritation, Category 2 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 10 -< 12.5
ethylbenzene	ethylbenzene	100-41-4	Flammable liquids, Category 2 Acute toxicity (Inhalation), Category 4 Specific target organ toxicity - repeated exposure (Auditory system), Category 2 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 3	>= 3 -< 5

Section 4: First-aid measures

General advice	:	First aid personnel should pay attention to their own safety. Never give anything by mouth to an unconscious person. Keep patient warm and at rest. Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident. Move out of dangerous area. In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product. Immediately remove contaminated clothing.
If inhaled	:	If breathed in, move person into fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician or poison control center immediately.
In case of skin contact	:	Do NOT use solvents or thinners. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
In case of eye contact	:	If easy to do, remove contact lens, if worn. Call a physician immediately. Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed	:	Rinse mouth with water. Do not induce vomiting due to aspiration hazard. Keep at rest. If swallowed, call a poison control center or doctor immediately.
Most important symptoms and effects, both acute and delayed	:	May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. Risk of product entering the lungs on vomiting after ingestion. When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.
Notes to physician	:	Treat symptomatically. No known specific antidote.

Section 5: Fire-fighting measures

Suitable extinguishing media	:	Dry powder

Carbon dioxide (CO2)

Water spray

Foam

Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire fighting	:	Fire will produce dense black smoke containing hazardous combustion products (see section 10).

Advice for firefighters

Specific extinguishing methods	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Cool containers/tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for fire-fighters	:	Appropriate breathing apparatus may be required.
Hazchem Code	:	3YE

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures	:	Avoid breathing vapours. For non-emergency personnel: Use personal protective equipment. Ensure adequate ventilation, especially in confined areas. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet.
Environmental precautions	:	Do not allow uncontrolled discharge of product into the environment. If the product contaminates rivers and lakes or drains inform respective authorities. Avoid subsoil penetration.
Methods and materials for containment and cleaning up	:	Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Ensure adequate ventilation.

Section 7: Handling and storage

Advice on protection against	:	Avoid all sources of ignition: heat, sparks, open flame.

fire and explosion		Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapors are heavier than air and spread along floors. Vapor forms explosive mixtures with air.
Advice on safe handling	:	Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Do not breathe vapors or spray mist.
Hygiene measures	:	Remove contaminated clothing immediately and dispose of safely. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.
Further information on storage conditions	:	Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel.

Always keep in containers of same material as the original one.

Observe label precautions.

Keep in a dry, cool and well-ventilated place.

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Packaging material : Suitable material: Stainless steel 1.4301 (V2), Carbon steel (Iron), tinned carbon steel (Tinplate)

Section 8: Exposure controls/personal protection

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
n-Butyl acetate	123-86-4	WES-STEL	200 ppm 950 mg/m3	NZ OEL
		WES-TWA	150 ppm 713 mg/m3	NZ OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
xylene	1330-20-7	WES-TWA	50 ppm 217 mg/m3	NZ OEL

	Further information: Ototoxin			
		TWA	20 ppm	ACGIH
ethyl acetate	141-78-6	WES-TWA	200 ppm 720 mg/m3	NZ OEL
		TWA	400 ppm	ACGIH
ethylbenzene	100-41-4	WES-TWA	20 ppm 88 mg/m3	NZ OEL
	Further information: Ototoxin, Skin absorption			
		WES-STEL	40 ppm 176 mg/m3	NZ OEL
	Further information: Ototoxin, Skin absorption			
		TWA	20 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
xylene	1330-20-7	Methylhippuric acid	Urine	End of shift	1.5 g/l	NZ BEI
		Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI

ethylbenzene	100-41-4	Sum of mandelic acid and phenylglyoxylic acids	Urine	End of exposure or end of shift	0.25 g/g creatinine	NZ BEI
		Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

Wear respiratory protection if ventilation is inadequate.

Hand protection

Remarks : Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g.

nitrile gloves - material thickness: 0,35 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer

or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Preventive skin protection

Eye protection : Required when there is a risk of eye contact.

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Skin and body protection : Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

Anti-static protective clothing

Protective measures : Do not breathe vapour/spray.

Eye wash fountains and safety showers must be easily accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Section 9: Physical and chemical properties

Appearance	:	liquid
Color	:	colorless
Odor	:	specific
pH	:	substance/mixture is non-polar/aprotic
Melting point/ range	:	not determined
Boiling point/boiling range	:	126 - 190 °C Method: calculated
Flash point	:	22 °C
Evaporation rate	:	not determined
Flammability	:	Highly flammable liquid and vapour.
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	36.0 %(V)

Vapor pressure	:	5 hPa (20 °C) not determined (50 °C)
Density	:	0.890 g/cm3 (20 °C)
Solubility(ies) Water solubility	: :	 not determined
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	not determined
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity Viscosity, dynamic	: :	 No data available
Viscosity, kinematic	:	6 mm2/s (23 °C) not determined (40 °C)
Flow time	:	< 30 s (23 °C) Cross section: 3 mm Method: ISO 2431
Explosive properties	:	Not explosive

Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Self-heating substances	:	The substance or mixture is not classified as self heating.
Metal corrosion rate	:	Not corrosive to metals.
Particle characteristics		
Particle size	:	The substance / product is marketed or used in a non solid or granular form.

Section 10: Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	Vapours may form ignitable mixture with air.
Conditions to avoid	:	Avoid direct sunlight. Heat, flames and sparks.
Incompatible materials	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

Section 11: Toxicological information

Acute toxicity

Not classified due to lack of data.

Product:

Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l Exposure time: 4 h

Test atmosphere: vapor

Method: Calculation method

Skin corrosion/irritation

Causes skin irritation.

Components:

n-Butyl acetate:

Assessment : Repeated exposure may cause skin dryness or cracking.

ethyl acetate:

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

Not classified due to lack of data.

Respiratory sensitization

Not classified due to lack of data.

Chronic toxicity

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

May cause respiratory irritation.
May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs (Kidney, Liver, Central nervous system, Auditory system) through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Section 12: Ecological information

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Components:

n-Butyl acetate:

Partition coefficient: n-octanol/water	:	Pow: 200 (25 °C) log Pow: 2.3 (25 °C) pH: 7 Method: OECD Test Guideline 117 GLP: yes

xylene:

Partition coefficient: n-octanol/water	:	log Pow: 3.12 - 3.20 (25 °C) GLP: no Remarks: Information taken from reference works and the literature.

1-methoxy-2-propylacetate:

Partition coefficient: n-octanol/water	:	log Pow: 1.2 (20 °C) pH: 6.8 Method: OECD Test Guideline 117 GLP: yes

ethyl acetate:

Partition coefficient: n-octanol/water	:	log Pow: 0.68 (25 °C) pH: 7 GLP: no

ethylbenzene:

Partition coefficient: n-octanol/water	:	Pow: 4,170 (20 °C) log Pow: 3.6 (20 °C) pH: 7.8 GLP: yes

Mobility in soil

No data available

Other adverse effects

No data available

Section 13: Disposal considerations

Disposal methods

Waste from residues	:	Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.
Contaminated packaging	:	Packaging that is not properly emptied must be disposed of as the unused product.

Section 14: Transport information

International Regulations

UNRTDG

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	II
Labels	:	3
Environmentally hazardous	:	no

IATA-DGR

UN/ID No.	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	II
Labels	:	Flammable Liquids
Packing instruction (cargo	:	364

aircraft)

Packing instruction (passenger aircraft)	:	353

IMDG-Code

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	II
Labels	:	3
EmS Code	:	F-E, S-E
Marine pollutant	:	no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
Not applicable for product as supplied.

Domestic regulation

NZS 5433

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	II
Labels	:	3
Hazchem Code	:	3YE
Marine pollutant	:	no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

HSNO Approval Number
HSR002662 Surface Coatings and Colourants Flammable Group Standard

Tolerable Exposure Limits (TEL)
Not applicable

Environmental Exposure Limits (EEL)
Not applicable

HSW Controls
Certified handler certificate not required.
Tracking hazardous substance not required.
Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

Section 16: Other information

Revision Date	:	21.11.2025

Further information

Other information	:	Restricted to professional users. For multi-pack systems observe material safety data sheets of all components.
Date format	:	dd.mm.yyyy

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
NZ BEI	:	New Zealand. Biological Exposure Indices
NZ OEL	:	New Zealand. Workplace Exposure Standards for Atmospheric Contaminants

ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NZ OEL / WES-TWA	:	Workplace Exposure Standard - Time Weighted average
NZ OEL / WES-STEL	:	Workplace Exposure Standard - Short-Term Exposure Limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory

of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NZ / EN

We create chemistry

Safety data sheet

BASF Safety data sheet
Date / Revised: 05.04.2023 Version: 4.0
Product: **85-03 Thinner Slow**

(50446908/SDS_GEN_NZ/EN)
Date of print: 02.05.2024

1. Substance/preparation and manufacturer/supplier identification

Product name:
85-03 Thinner Slow

Use: Thinner

Manufacturer/supplier:
BASF New Zealand Ltd.
5E City Works Depot
77 Cook Street
Auckland Central, Auckland 1010
NEW ZEALAND
Telephone: +64 9 255-4300
Telefax number: +64 9 255-4307

Emergency information:
National Poisons Centre: 0800 764 766
BASF Emergency Advice Number: 0800 944 955 (24 hour advice in an emergency only)
BASF Emergency Advice Number: +61 3 8855 6666 (If calling from outside New Zealand)

2. Hazard identification

Classification of the substance and mixture:
Acute toxicity: Cat.5 (oral)
Acute toxicity: Cat.5 (Inhalation - vapour)
Skin corrosion/irritation: Cat.2
Serious eye damage/eye irritation: Cat.1
Aspiration hazard: Cat.1
Specific target organ toxicity — single exposure: Cat.3 (irritating to respiratory system)
Specific target organ toxicity — single exposure: Cat.3 (Vapours may cause drowsiness and dizziness.)
Specific target organ toxicity — repeated exposure: Cat.2
Hazardous to the aquatic environment - acute: Cat.2
Hazardous to the aquatic environment - chronic: Cat.2

Flammable liquids: Cat.3

Label elements and precautionary statement:

Pictogram:



Signal Word:
Danger

Hazard Statement:

H226	Flammable liquid and vapour.
H303	May be harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H333	May be harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves, protective clothing and eye protection or face protection.
P264	Wash contaminated body parts thoroughly after handling.
P242	Use non-sparking tools.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P243	Take action to prevent static discharges.
P233	Keep container tightly closed.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground and bond container and receiving equipment.
P260	Do not breathe dust or mist.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P370 + P378	In case of fire: Use water spray for extinction.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P310	Immediately call a POISON CENTER or physician.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or physician.
P332 + P313	If skin irritation occurs: Get medical attention.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P304 + P312	IF INHALED: Call a POISON CENTER or physician if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P331	Do NOT induce vomiting.
P391	Collect spillage.

Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.

Other hazards which do not result in classification:
If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

3. Composition/information on ingredients

Chemical nature

Substance nature: mixture

organic solvent

Hazardous ingredients

n-Butyl acetate

Content (W/W): >= 30 % - < 50 %	Flam. Liq.: Cat. 3
CAS Number: 123-86-4	STOT SE: Cat. 3 (drowsiness and dizziness)
	Aquatic Acute: Cat. 3

Solvent naphtha (petroleum), light arom.

Content (W/W): >= 20 % - < 25 % CAS Number: 64742-95-6	Asp. Tox.: Cat. 1 Flam. Liq.: Cat. 3 Skin Corr./Irrit.: Cat. 2 STOT SE: Cat. 3 (drowsiness and dizziness) Aquatic Acute: Cat. 2 Aquatic Chronic: Cat. 2

xylene

Content (W/W): >= 15 % - < 20 % CAS Number: 1330-20-7	Asp. Tox.: Cat. 1 Flam. Liq.: Cat. 3 Acute Tox.: Cat. 5 (Inhalation - vapour) Acute Tox.: Cat. 5 (oral) Skin Corr./Irrit.: Cat. 2 Eye Dam./Irrit.: Cat. 2B STOT SE: Cat. 3 (irr. to respiratory syst.) STOT RE (Central nervous system, Liver, Kidney): Cat. 2 Aquatic Acute: Cat. 2 Aquatic Chronic: Cat. 3

1,2,4-trimethylbenzene

Content (W/W): >= 10 % - < 12.5 % CAS Number: 95-63-6	Asp. Tox.: Cat. 1 Flam. Liq.: Cat. 3 Acute Tox.: Cat. 4 (Inhalation - vapour) Skin Corr./Irrit.: Cat. 2 Aquatic Chronic: Cat. 2 Eye Dam./Irrit.: Cat. 2A STOT SE: Cat. 3 (irr. to respiratory syst.) Aquatic Acute: Cat. 2

cyclohexanone

Content (W/W): >= 7 % - < 10 % CAS Number: 108-94-1	Flam. Liq.: Cat. 3 Acute Tox.: Cat. 4 (Inhalation - vapour) Acute Tox.: Cat. 4 (oral) Acute Tox.: Cat. 4 (dermal) Skin Corr./Irrit.: Cat. 2 Eye Dam./Irrit.: Cat. 1

ethylbenzene

Content (W/W): >= 3 % - < 5 % CAS Number: 100-41-4	Asp. Tox.: Cat. 1 Flam. Liq.: Cat. 2 Acute Tox.: Cat. 4 (Inhalation - vapour) Acute Tox.: Cat. 5 (oral) STOT RE (Auditory organ): Cat. 2 Aquatic Acute: Cat. 2 Aquatic Chronic: Cat. 3

mesitylene

Content (W/W): >= 3 % - < 5 % CAS Number: 108-67-8	Asp. Tox.: Cat. 1 Flam. Liq.: Cat. 3 Skin Corr./Irrit.: Cat. 2 STOT SE: Cat. 3 (irr. to respiratory syst.) Aquatic Acute: Cat. 2 Aquatic Chronic: Cat. 2

Pentanedioic acid, dimethyl ester

Content (W/W): >= 2.5 % - < 3 % CAS Number: 1119-40-0	Aquatic Acute: Cat. 3

cumene

Content (W/W): >= 1 % - < 2 % CAS Number: 98-82-8	Asp. Tox.: Cat. 1 Flam. Liq.: Cat. 3 Acute Tox.: Cat. 5 (oral) STOT SE: Cat. 3 (irr. to respiratory syst.) Aquatic Acute: Cat. 2 Aquatic Chronic: Cat. 2

naphthalene

Content (W/W): >= 0.3 % - < 0.5 % CAS Number: 91-20-3	Flam. Sol.: Cat. 2 Acute Tox.: Cat. 4 (oral) Carc.: Cat. 2 Aquatic Acute: Cat. 1 Aquatic Chronic: Cat. 1 M-factor acute: 1 M-factor chronic: 1

4. First-Aid Measures

General advice:
First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove affected person from danger area. Keep warm, calm and covered up. Immediately remove contaminated clothing. Never give anything by mouth to an unconscious person. In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product. Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.

If inhaled:
Immediate medical attention required. Remove the affected individual into fresh air and keep the person calm. If breathing is irregular or stopped, administer artificial respiration.

On skin contact:
If symptoms persist, seek medical advice. Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

On contact with eyes:
Remove contact lenses, if present. Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Immediate medical attention required.

On ingestion:
Summon medical aid without delay. Do not induce vomiting due to aspiration hazard. Keep at rest. Rinse mouth immediately with water.

Note to physician:
Symptoms: aspiration pneumonia, dazed state, irritation of respiratory tract, skin irritation, dizziness,
Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.
Hazards: If swallowed, in the event of vomiting, risk of product entering the lungs. When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.
Treatment: Symptomatic treatment (decontamination, vital functions).
Antidote: No known specific antidote.

5. Fire-Fighting Measures

Suitable extinguishing media:
carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:
water jet

Specific hazards:
Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

Special protective equipment:
Appropriate breathing apparatus may be required.

Further information:
Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

6. Accidental Release Measures

Personal precautions:
Avoid breathing vapours.For non-emergency personnel:Use personal protective clothing.Ensure adequate ventilation.Keep away from sources of ignition.For emergency responders:Advice on product handling can be found in sections 7 and 8 of this safety data sheet.Information regarding personal protective measures, see section 8.

Environmental precautions:
Do not allow to enter drains or waterways.If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency.Do not discharge into the subsoil/soil.

Methods for cleaning up or taking up:
Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for diposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents. Ensure adequate ventilation.

7. Handling and Storage

Handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:
Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapours are heavier than air and spread along floors. Vapour forms explosive mixtures with air. The relevant fire protection measures should be noted. Use explosion-proof equipment.

Storage

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

Suitable materials for containers: Carbon steel (Iron), tinned carbon steel (Tinplate)
Further information on storage conditions: Keep container dry. Keep away from heat. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Store protected against freezing.

8. Exposure controls and personal protection

Components with occupational exposure limits

naphthalene, 91-20-3;
TWA value 10 ppm (ACGIHTLV)
Skin Designation (ACGIHTLV)
Danger of cutaneous absorption
TWA value 2.6 mg/m3 ; 0.5 ppm (OEL (NZ))
STEL value 10 mg/m3 ; 2 ppm (OEL (NZ))
Skin Designation (OEL (NZ))
Skin absorption can be significant.

1,2,4-trimethylbenzene, 95-63-6;

TWA value 123 mg/m3 ; 25 ppm (OEL (NZ))
TWA value 10 ppm (ACGIHTLV)

cumene, 98-82-8;
STEL value 375 mg/m3 ; 75 ppm (OEL (NZ))
TWA value 125 mg/m3 ; 25 ppm (OEL (NZ))
Skin Designation (OEL (NZ))
Skin absorption can be significant.
TWA value 5 ppm (ACGIHTLV)

ethylbenzene, 100-41-4;
TWA value 20 ppm (ACGIHTLV)
TWA value 88 mg/m3 ; 20 ppm (OEL (NZ))
STEL value 176 mg/m3 ; 40 ppm (OEL (NZ))
Skin Designation (OEL (NZ))
Skin absorption can be significant.

mesitylene, 108-67-8;
TWA value 123 mg/m3 ; 25 ppm (OEL (NZ))
TWA value 10 ppm (ACGIHTLV)

cyclohexanone, 108-94-1;
TWA value 20 ppm (ACGIHTLV)
STEL value 50 ppm (ACGIHTLV)
TWA value 100 mg/m3 ; 25 ppm (OEL (NZ))
Skin Designation (OEL (NZ))
Skin absorption can be significant.
Skin Designation (ACGIHTLV)
Danger of cutaneous absorption
Skin Designation (ACGIHTLV)
Danger of cutaneous absorption

n-Butyl acetate, 123-86-4;
STEL value 150 ppm (ACGIHTLV)
TWA value 50 ppm (ACGIHTLV)
TWA value 713 mg/m3 ; 150 ppm (OEL (NZ))
STEL value 950 mg/m3 ; 200 ppm (OEL (NZ))

xylene, 1330-20-7;
TWA value 20 ppm (ACGIHTLV)
TWA value 217 mg/m3 ; 50 ppm (OEL (NZ))

Personal protective equipment

Respiratory protection:
Wear respiratory protection if ventilation is inadequate. When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators. Use A1P2 breathing-protection half mask in case of contact with aerosols.

Hand protection:
Further information on penetration time is available from the manufacturer of the glove.
Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.
The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).
Follow manufacturer's advice on use, storage, maintenance and replacement of gloves.
The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).
Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g.
nitrile gloves - material thickness: 0,7 mm
Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):
Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)
Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Eye protection:
Tightly fitting safety goggles (splash goggles) (e.g. EN 166), Required when there is a risk of eye contact.

Body protection:
Anti-static protective clothing, Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

General safety and hygiene measures:
Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Ensure adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

9. Physical and Chemical Properties

Form:	liquid
Colour:	colourless
Odour:	specific
pH value:	5.0
Melting point:	not determined
onset of boiling:	not determined
Flash point:	23 °C
Flammability (solid/gas):	Flammable liquid and vapour.

Lower explosion limit:	36 g/m3	
Ignition temperature:	> 200 °C	
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
Self heating ability:	It is not a material capable of spontaneous heating	
Explosion hazard:	not explosive	
Fire promoting properties:	not fire-propagating	
Vapour pressure:	5.00 hPa (20 °C)	(calculated)
	(50 °C) not determined	
Density:	0.887 g/cm3 (20 °C)	
Relative vapour density (air):	Heavier than air.	
Miscibility with water:	No data available.	
Partitioning coefficient n-octanol/water (log Pow):	not applicable for mixtures	
Viscosity, kinematic:	6.0 mm2/s (20 °C)	
	(40 °C) not determined	
Flow time:	< 30 s	(DIN EN ISO 2431; 3 mm)

10. Stability and Reactivity

Conditions to avoid:
Avoid heat. Avoid direct sunlight. Avoid all sources of ignition: heat, sparks, open flame. Avoid freezing.

Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.

Substances to avoid:
Keep away from highly acidic or alkaline substances as well as oxidants in order to prevent exothermal reactions.

Hazardous reactions:
Vapours may form ignitable mixture with air.

When exposed to high temperatures hazardous decomposition products such as carbon monoxide, carbon dioxide, smoke, oxides of nitrogen may be produced., No hazardous decomposition products if stored and handled as prescribed/indicated.

Chemical stability:
The product is stable if stored and handled as prescribed/indicated.

Reactivity:
No hazardous reactions if stored and handled as prescribed/indicated.

11. Toxicological Information

Routes of exposure

Assessment of acute toxicity

Virtually nontoxic by inhalation. Of low toxicity after single ingestion.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated and prolonged exposure to solvents at levels significantly above OELs may lead to the development of long-lasting central nervous system disorders such as chronic toxic encephalopathy, signs of toxicity include changes in behaviour and memory. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Information on: cumene

Acute oral toxicity

Experimental/calculated data:
LD50 rat (oral): 2,910 mg/kg
Literature data.

Information on: ethylbenzene

Acute oral toxicity

Experimental/calculated data:
LD50 rat (oral): 3,500 mg/kg
Literature data.

Information on: xylene

Acute oral toxicity

Experimental/calculated data:
LD50 rat (oral): 3,523 mg/kg (similar to OECD guideline 401)

Information on: 1,2,4-trimethylbenzene

Acute inhalation toxicity

Experimental/calculated data:

LC50 rat (by inhalation): > 10.2 mg/l 4 h (other)
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The vapour was tested.

Symptoms

aspiration pneumonia dazed state irritation of respiratory tract skin irritation dizziness Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Irritation

Assessment of irritating effects:
The liquid splashed in the eyes may cause irritation and reversible damage. Skin contact causes irritation. May cause severe damage to the eyes.

Respiratory/Skin sensitization

Assessment of sensitization:
Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Assessment of mutagenicity:
Based on available data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity:
Based on available data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity:
Based on available data, the classification criteria are not met.

Developmental toxicity

Assessment of teratogenicity:
Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Causes temporary irritation of the respiratory tract. Possible narcotic effects (drowsiness or dizziness).

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:
Repeated exposure may affect certain organs.

Aspiration hazard

May also damage the lung at swallowing (aspiration hazard).

12. Ecological Information

Ecotoxicity

Assessment of aquatic toxicity:
Toxic to aquatic life. Toxic to aquatic life with long lasting effects. There are no test results available for this product. Do not allow to enter drains or waterways.

Mobility

Assessment transport between environmental compartments:
No data available.

Persistence and degradability

Assessment biodegradation and elimination (H2O):
Biological degradability of hazardous substances mentioned in section 3:

Information on: 1,2,4-trimethylbenzene
Elimination information:
> 20 % BOD of the ThOD (28 d) (OECD 301F; ISO 9408; 92/69/EEC, C.4-D) (aerobic, activated sludge, domestic)
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on: cumene
Elimination information:
70 % BOD of the ThOD (20 d) (ISO 10708) (aerobic, activated sludge, domestic)
Literature data.

Information on: ethylbenzene
Elimination information:
70 - 80 % TIC of the ThIC (28 d) (ISO 14593) (aerobic, activated sludge) Readily biodegradable (according to OECD criteria).

Information on: mesitylene
Elimination information:
61 % BOD of the ThOD (28 d) (OECD 301F; ISO 9408; 92/69/EEC, C.4-D) (aerobic, other)

Information on: n-Butyl acetate
Elimination information:
80 % BOD of the ThOD (5 d) (OECD 301D; EEC 92/69, C.4-E) (aerobic, municipal sewage treatment plant effluent)

Information on: Dimethyl glutarate
Elimination information:
90 % BOD of the ThOD (14 d) (OECD 301C; ISO 9408; 92/69/EEC, C.4-F) (aerobic, Inoculum conforming to MITI requirements (OECD 301C)) Readily biodegradable.

Information on: xylene
Elimination information:

87.8 % BOD of the ThOD (28 d) (OECD Guideline 301 F) (aerobic, activated sludge, domestic, non-adapted)
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on: Solvent naphtha (petroleum), light arom.
Elimination information:
77 % BOD of the ThOD (28 d) (OECD 301F; ISO 9408; 92/69/EEC, C.4-D) (aerobic, activated sludge, domestic, non-adapted)

96 % CO2 formation relative to the theoretical value (28 d) (ISO 14593) (aerobic, activated sludge, domestic, adapted)

Bioaccumulation potential

Bioaccumulation potential:
No data available.

13. Disposal Considerations

Do not discharge into drains/surface waters/groundwater.
Observe national and local legal requirements.

Contaminated packaging:
Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

14. Transport Information

Domestic transport:

UN number or ID number:	UN 1263
UN proper shipping name:	PAINT RELATED MATERIAL
Transport hazard class(es):	3, EHSM
Packing group:	III
Environmental hazards:	yes
Special precautions for user:	None known

Further information
Hazchem Code:3Y
IERG Number:14

Sea transport
IMDG

UN number or ID number:	UN 1263
UN proper shipping name:	PAINT RELATED MATERIAL (SOLVENT NAPHTHA)
Transport hazard class(es):	3, EHSM
Packing group:	III

Environmental hazards:	yes Marine pollutant: YES
Special precautions for user:	EmS: F-E; S-E

Air transport
IATA/ICAO

UN number or ID number:	UN 1263
UN proper shipping name:	PAINT RELATED MATERIAL
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	No Mark as dangerous for the environment is needed
Special precautions for user:	None known

15. Regulatory Information

Other regulations

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.
Tracking requirements do not apply to this substance.
A certified handler is not required for the handling of this substance.

HSNO Approval Number HSR002662
Surface Coatings and Colourants (Flammable) Group Standard 2017

16. Other Information

For multi-pack systems observe material safety data sheets of all components.Restricted to professional users.

Vertical lines in the left hand margin indicate an amendment from the previous version.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

352-30 Reducer normal 5L G2

Version	Revision Date:	SDS Number:	Date of last issue: 19.08.2025
6.0	14.11.2025	000000000050794060	Date of first issue: 28.11.2024

Section 1: Identification

Product name : 352-30 Reducer normal 5L G2

Product code : 000000000050794060

Manufacturer or supplier's details

BASF Coatings and Chemetall New Zealand Limited
Level 1, 527A Rosebank Road, Avondale
Auckland 1026
New Zealand
Telephone: 008 837 464, +64 9 820 3888
Telefax number: +64 9 820 3979
E-mail address: nzadmin@basf.com

Emergency contact

Telephone: +64 9 255-4300
E-mail address: ProductSafety_EC_APAC@basf.com, nzadmin@basf.com

Emergency telephone : National Poisons Centre: 0800 764 766
BASF Emergency Advice Number: 0800 944 955 (24 hour advice in an emergency only)
BASF Emergency Advice Number: +61 3 8855 6666 (If calling from outside New Zealand)

Recommended use of the chemical and restrictions on use

Recommended use : Spraying
Thinner

Section 2: Hazard identification

GHS Classification

Flammable liquids : Category 3

Skin corrosion/irritation : Category 2

Serious eye damage/eye : Category 2

irritation

Reproductive toxicity	:	Category 2
Specific target organ toxicity - single exposure	:	Category 3 (Central nervous system)
Specific target organ toxicity - repeated exposure	:	Category 2 (Kidney, Liver, Central nervous system, Auditory system)
Aspiration hazard	:	Category 1
Hazardous to the aquatic environment - chronic hazard	:	Category 3

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs (Kidney, Liver, Central nervous system, Auditory system) through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before

reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification
If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Section 3: Composition/information on ingredients

Chemical nature : organic solvent

Components

Chemical name	Common Name/Synonyms	CAS-No.	Classification	Concentration (% w/w)
2-heptanone	heptan-2-one	110-43-0	Flammable liquids, Category 3 Acute toxicity (Oral), Category 4 Acute toxicity (Inhalation), Category 4 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 30 -< 50
Hydrocarbons, C9-C10, n-alkanes,	Hydrocarbons, C9-C10, n-alkanes,	64742-49-0	Flammable liquids, Category 3	>= 20 -< 25

isoalkanes, cyclics, <2% aromatics	isoalkanes, cyclics, <2% aromatics		Specific target organ toxicity - single exposure (Central nervous system), Category 3 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 3	
xylene	xylenes	1330-20-7	Flammable liquids, Category 3 Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2 Specific target organ toxicity - single exposure (Respiratory system), Category 3 Specific target organ toxicity - repeated exposure (Kidney, Liver, Central nervous system), Category 2 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 3	>= 10 -< 20

2-butoxyethyl acetate	2-butoxyethyl acetate	112-07-2	Flammable liquids, Category 4 Acute toxicity (Oral), Category 4 Acute toxicity (Dermal), Category 4	>= 1 -< 10
ethylbenzene	ethylbenzene	100-41-4	Flammable liquids, Category 2 Acute toxicity (Inhalation), Category 4 Specific target organ toxicity - repeated exposure (Auditory system), Category 2 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 3	>= 2.5 -< 10
n-hexane	n-hexane	110-54-3	Flammable liquids, Category 2 Skin corrosion/irritation, Category 2 Reproductive toxicity, Category 2 Specific target organ toxicity - single exposure (Central nervous system), Category 3 Specific target organ	>= 0.1 -< 0.25

			toxicity - repeated exposure, Category 1 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 2	

Section 4: First-aid measures

General advice : In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product.
Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.
Keep patient warm and at rest.
Never give anything by mouth to an unconscious person.
Move out of dangerous area.
Immediately remove contaminated clothing.
First aid personnel should pay attention to their own safety.

If inhaled : If breathed in, move person into fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician or poison control center immediately.

In case of skin contact : Do NOT use solvents or thinners.

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

If symptoms persist, call a physician.

In case of eye contact : Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

Call a physician immediately.

If easy to do, remove contact lens, if worn.

If swallowed : Rinse mouth with water.

Do not induce vomiting due to aspiration hazard.

Keep at rest.

If swallowed, call a poison control center or doctor immediately.

Most important symptoms and effects, both acute and delayed : Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.

Risk of product entering the lungs on vomiting after ingestion.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure.

Notes to physician	:	Treat symptomatically. No known specific antidote.

Section 5: Fire-fighting measures

Suitable extinguishing media	:	Water spray Dry powder Foam Carbon dioxide (CO_2)
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire fighting	:	Fire will produce dense black smoke containing hazardous combustion products (see section 10).

Advice for firefighters

Specific extinguishing methods	:	Cool containers/tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Special protective equipment for fire-fighters	:	Appropriate breathing apparatus may be required.

Hazchem Code	:	3Y

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures	:	Avoid breathing vapours. For non-emergency personnel: Use personal protective equipment. Ensure adequate ventilation, especially in confined areas. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet.
Environmental precautions	:	If the product contaminates rivers and lakes or drains inform respective authorities. Avoid subsoil penetration. Do not allow uncontrolled discharge of product into the environment.
Methods and materials for containment and cleaning up	:	Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local /

national regulations (see section 13).

Ensure adequate ventilation.

Section 7: Handling and storage

Advice on protection against fire and explosion : Avoid all sources of ignition: heat, sparks, open flame.

Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear.

Solvent vapors are heavier than air and spread along floors. Vapor forms explosive mixtures with air.

The relevant fire protection measures should be noted.

Use explosion-proof equipment.

Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).

Do not return residues to the storage containers.

Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen

		below the exposure limits. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Do not breathe vapors or spray mist.
Hygiene measures	:	Remove contaminated clothing immediately and dispose of safely. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.
Further information on storage conditions	:	Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Keep in a dry, cool and well-ventilated place.
Materials to avoid	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Packaging material	:	Suitable material: Carbon steel (Iron), tinned carbon steel (Tinplate)

Section 8: Exposure controls/personal protection

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-heptanone	110-43-0	WES-TWA	50 ppm 233 mg/m3	NZ OEL
		TWA	50 ppm	ACGIH
xylene	1330-20-7	WES-TWA	50 ppm 217 mg/m3	NZ OEL
	Further information: Ototoxin			
		TWA	20 ppm	ACGIH
2-butoxyethyl acetate	112-07-2	TWA	20 ppm	ACGIH
ethylbenzene	100-41-4	WES-TWA	20 ppm 88 mg/m3	NZ OEL
	Further information: Ototoxin, Skin absorption			
		WES-STEL	40 ppm 176 mg/m3	NZ OEL
	Further information: Ototoxin, Skin absorption			
		TWA	20 ppm	ACGIH
n-hexane	110-54-3	WES-TWA	20 ppm 72 mg/m3	NZ OEL

	Further information: Ototoxin, Exposure can also be estimated by biological monitoring			
		TWA	50 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
xylene	1330-20-7	Methylhippuric acid	Urine	End of shift	1.5 g/l	NZ BEI
		Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI
ethylbenzene	100-41-4	Sum of mandelic acid and phenylglyoxylic acids	Urine	End of exposure or end of shift	0.25 g/g creatinine	NZ BEI
		Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI
n-hexane	110-54-3	2,5-hexanedion	Urine	End of	5 mg/l	NZ BEI

		e		shift		
		2,5-Hexanedione	Urine	End of shift	0.5 mg/l	ACGIH BEI

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Suitable respiratory equipment:

half-mask with A2P2 class combination filter

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection

Remarks	:	Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. butyl rubber gloves - material thickness: 0.5 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Preventive skin protection Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)
Eye protection	:	Required when there is a risk of eye contact. Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Skin and body protection	:	Anti-static protective clothing Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.
Protective measures	:	Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Section 9: Physical and chemical properties

Appearance	:	liquid
Color	:	colorless
Odor	:	ketone-like
pH	:	substance/mixture is non-polar/aprotic
Melting point/ range	:	not determined
Boiling point/boiling range	:	116.00 °C

Flash point	:	29 °C Method: ISO 3679
Evaporation rate	:	not determined
Flammability	:	Flammable liquid and vapour.
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	> 35.0 g/m3
Vapor pressure	:	20.0000 hPa (20 °C) not determined (50 °C)
Density	:	0.830 g/cm3 (20 °C)
Solubility(ies) Water solubility	:	not determined
Partition coefficient: n-octanol/water	:	not applicable for mixtures

Autoignition temperature	:	> 200 °C
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	7.3 mm2/s (23 °C) 1.96 mm2/s (40 °C)
Flow time	:	> 30 s (23 °C) Cross section: 3 mm Method: ISO 2431
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Self-heating substances	:	The substance or mixture is not classified as self heating.
Metal corrosion rate	:	Not corrosive to metals.
Particle characteristics		
Particle size	:	The substance / product is marketed or used in a non solid or granular form.

Section 10: Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.

Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	Vapours may form ignitable mixture with air.
Conditions to avoid	:	Avoid direct sunlight. Heat, flames and sparks.
Incompatible materials	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

Section 11: Toxicological information

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method

Components:

2-heptanone:

Acute oral toxicity	:	LD50 (Rat): 1,600 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 16.7 mg/l Exposure time: 4 h Test atmosphere: vapor

2-butoxyethyl acetate:

Acute oral toxicity	:	LD50 (Rat): 1,880 mg/kg
Acute dermal toxicity	:	LD50 (Rabbit): 1,500 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Assessment	:	Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

Based on available data, the classification criteria are not met.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Chronic toxicity

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs (Kidney, Liver, Central nervous system, Auditory system) through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Section 12: Ecological information

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Components:

2-heptanone:

Partition coefficient: n-octanol/water	:	log Pow: 2.26 (30 °C) pH: 7 Method: Regulation (EC) No. 440/2008, Annex, A.8

GLP: yes

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Partition coefficient: n-octanol/water : log Pow: > 4

log Pow: > 4

xylene:

Partition coefficient: n-octanol/water : log Pow: 3.12 - 3.20 (25 °C)

GLP: no

Remarks: Information taken from reference works and the literature.

2-butoxyethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 1.51 (25 °C)

pH: 7

Method: OECD Test Guideline 107

GLP: no

ethylbenzene:

Partition coefficient: n-octanol/water : Pow: 4,170 (20 °C)

log Pow: 3.6 (20 °C)

		pH: 7.8 GLP: yes
n-hexane:		
Partition coefficient: n-octanol/water	:	log Pow: 4 (20 °C) pH: 7 Remarks: Information taken from reference works and the literature.

Mobility in soil

No data available

Other adverse effects

No data available

Section 13: Disposal considerations

Disposal methods

Waste from residues	:	Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.
Contaminated packaging	:	Packaging that is not properly emptied must be disposed of as the unused product.

Section 14: Transport information

International Regulations

UNRTDG

UN number	:	UN 1263

Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
Environmentally hazardous	:	no

IATA-DGR

UN/ID No.	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	Flammable Liquids
Packing instruction (cargo aircraft)	:	366
Packing instruction (passenger aircraft)	:	355

IMDG-Code

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
EmS Code	:	F-E, S-E

Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
Not applicable for product as supplied.

Domestic regulation

NZS 5433

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
Hazchem Code	:	3Y
Marine pollutant	:	no

Special precautions for user
The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

HSNO Approval Number
HSR002662 Surface Coatings and Colourants Flammable Group Standard

Tolerable Exposure Limits (TEL)
Not applicable

Environmental Exposure Limits (EEL)

Not applicable

HSW Controls
Certified handler certificate not required.
Tracking hazardous substance not required.
Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

Section 16: Other information

Revision Date	:	14.11.2025

Further information

Other information	:	For multi-pack systems observe material safety data sheets of all components. Restricted to professional users.
Date format	:	dd.mm.yyyy

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
NZ BEI	:	New Zealand. Biological Exposure Indices
NZ OEL	:	New Zealand. Workplace Exposure Standards for Atmospheric Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
NZ OEL / WES-TWA	:	Workplace Exposure Standard - Time Weighted average
NZ OEL / WES-STEL	:	Workplace Exposure Standard - Short-Term Exposure Limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NZ / EN

352-40 Reducer slow 5L G2

Version	Revision Date:	SDS Number:	Date of last issue: 22.08.2025
5.0	14.11.2025	000000000050411596	Date of first issue: 01.10.2024

Section 1: Identification

Product name : 352-40 Reducer slow 5L G2

Product code : 000000000050411596

Manufacturer or supplier's details

Chemetall Kft., org. složka
Radlická 354/107b
158 00 Praha 5
Czech Republic

Distributor:
BASF New Zealand Ltd.
5E City Works Depot
77 Cook Street
Auckland Central, Auckland 1010
New Zealand

Emergency contact
Telephone: +64 9 255-4300

Emergency telephone : National Poisons Centre: 0800 764 766
BASF Emergency Advice Number: 0800 944 955 (24 hour advice in an emergency only)
BASF Emergency Advice Number: +61 3 8855 6666 (If calling from outside New Zealand)

Recommended use of the chemical and restrictions on use

Recommended use : Spraying
Thinner

Section 2: Hazard identification

GHS Classification

Flammable liquids : Category 3

Reproductive toxicity : Category 2

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

Aspiration hazard : Category 1

Hazardous to the aquatic environment - chronic hazard	:	Category 3

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements :
H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements :

Prevention:
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing mist or vapors.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off

immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification
If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Section 3: Composition/information on ingredients

Chemical nature : organic solvent

Components

Chemical name	Common Name/Synonyms	CAS-No.	Classification	Concentration (% w/w)
2-heptanone	heptan-2-one	110-43-0	Flammable liquids, Category 3 Acute toxicity (Oral), Category 4 Acute toxicity (Inhalation), Category 4 Specific target organ toxicity - single exposure (Central	>= 30 -< 50

			nervous system), Category 3	
n-Butyl acetate	n-butyl acetate	123-86-4	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 20 -< 30
Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0)	Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0)	64742-95-6	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Respiratory system, Central nervous system), Category 3 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 2	>= 10 -< 20
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-49-0	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Central nervous system), Category 3 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 3	>= 2.5 -< 10

2-butoxyethyl acetate	2-butoxyethyl acetate	112-07-2	Flammable liquids, Category 4 Acute toxicity (Oral), Category 4 Acute toxicity (Dermal), Category 4	>= 1 -< 10
n-hexane	n-hexane	110-54-3	Flammable liquids, Category 2 Skin corrosion/irritation, Category 2 Reproductive toxicity, Category 2 Specific target organ toxicity - single exposure (Central nervous system), Category 3 Specific target organ toxicity - repeated exposure, Category 1 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 2	>= 0.1 -< 0.25

Section 4: First-aid measures

General advice : Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the

accident.
Keep patient warm and at rest.
In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product.
Never give anything by mouth to an unconscious person.
Move out of dangerous area.
Immediately remove contaminated clothing.
First aid personnel should pay attention to their own safety.

If inhaled : If breathed in, move person into fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician or poison control center immediately.

In case of skin contact : Do NOT use solvents or thinners.

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

If symptoms persist, call a physician.

In case of eye contact : In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

If symptoms persist, call a physician.

If swallowed : Rinse mouth with water.

Do not induce vomiting due to aspiration hazard.

Keep at rest.

If swallowed, call a poison control center or doctor immediately.

Most important symptoms and effects, both acute and : May be fatal if swallowed and enters airways.

delayed		May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia. Risk of product entering the lungs on vomiting after ingestion.
Notes to physician	:	No known specific antidote. Treat symptomatically.

Section 5: Fire-fighting measures

Suitable extinguishing media	:	Water spray Dry powder Foam Carbon dioxide (CO2)
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire fighting	:	Fire will produce dense black smoke containing hazardous combustion products (see section 10).

Advice for firefighters

Specific extinguishing methods	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cool containers/tanks with water spray.
Special protective equipment for fire-fighters	:	Appropriate breathing apparatus may be required.
Hazchem Code	:	3Y

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures	:	Avoid breathing vapours. For non-emergency personnel: Use personal protective equipment. Ensure adequate ventilation, especially in confined areas. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet.
Environmental precautions	:	If the product contaminates rivers and lakes or drains inform respective authorities.

Avoid subsoil penetration.

Do not allow uncontrolled discharge of product into the environment.

Methods and materials for containment and cleaning up : Ensure adequate ventilation.

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

Section 7: Handling and storage

Advice on protection against fire and explosion : Avoid all sources of ignition: heat, sparks, open flame.

Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear.

Solvent vapors are heavier than air and spread along floors. Vapor forms explosive mixtures with air.

The relevant fire protection measures should be noted.

Use explosion-proof equipment.

Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).

Do not return residues to the storage containers.

Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

The workplace should be equipped with an emergency shower and eye-rinsing facility.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Do not breathe vapors or spray mist.

Hygiene measures : Remove contaminated clothing immediately and dispose of safely.

Wash hands before breaks and at the end of workday.

Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions : Avoid direct sunlight.

Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel.

Always keep in containers of same material as the original one.

Observe label precautions.

Keep in a dry, cool and well-ventilated place.

Materials to avoid	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Packaging material	:	Suitable material: Carbon steel (Iron), tinned carbon steel (Tinplate)

Section 8: Exposure controls/personal protection

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-heptanone	110-43-0	WES-TWA	50 ppm 233 mg/m3	NZ OEL
		TWA	50 ppm	ACGIH
n-Butyl acetate	123-86-4	WES-STEL	200 ppm 950 mg/m3	NZ OEL
		WES-TWA	150 ppm 713 mg/m3	NZ OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0)	64742-95-6	WES-TWA	300 ppm 890 mg/m3	NZ OEL
		WES-STEL	500 ppm	NZ OEL

			1,480 mg/m3	
2-butoxyethyl acetate	112-07-2	TWA	20 ppm	ACGIH
n-hexane	110-54-3	WES-TWA	20 ppm 72 mg/m3	NZ OEL
	Further information: Ototoxin, Exposure can also be estimated by biological monitoring			
		TWA	50 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
n-hexane	110-54-3	2,5-hexanedione	Urine	End of shift	5 mg/l	NZ BEI
		2,5-Hexanedione	Urine	End of shift	0.5 mg/l	ACGIH BEI

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Suitable respiratory equipment:

half-mask with A1P2 class combination filter

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection

Remarks	:	Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. butyl rubber gloves - material thickness: 0.5 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any

indication of degradation or chemical breakthrough.

Preventive skin protection

Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Eye protection : Required when there is a risk of eye contact.

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Skin and body protection : Anti-static protective clothing

Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

Protective measures : Do not breathe vapour/spray.

Eye wash fountains and safety showers must be easily accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Section 9: Physical and chemical properties

Appearance : liquid

Color	:	colorless
Odor	:	ketone-like
pH	:	substance/mixture is non-polar/aprotic
Melting point/ range	:	not determined
Boiling point/boiling range	:	124.00 °C
Flash point	:	31 °C Method: ISO 3679
Flammability	:	Flammable liquid and vapour.
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	> 35.0 g/m3
Vapor pressure	:	11.0 hPa (20 °C)

		not determined (50 °C)
Density	:	0.868 g/cm3 (20 °C)
Solubility(ies)		
Water solubility	:	not determined
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	> 200 °C
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity		
Viscosity, kinematic	:	0.900 mm2/s (40 °C)
		411.6 mm2/s (23 °C)
Flow time	:	> 60 s (23 °C) Cross section: 6 mm Method: ISO 2431
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Self-heating substances	:	The substance or mixture is not classified as self heating.
Metal corrosion rate	:	Not corrosive to metals.

Particle characteristics

Particle size : The substance / product is marketed or used in a non solid or granular form.

Section 10: Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : Vapours may form ignitable mixture with air.

Conditions to avoid : Avoid direct sunlight.

Heat, flames and sparks.

Incompatible materials : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Hazardous decomposition products : No decomposition if stored and applied as directed.

Section 11: Toxicological information

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h

Test atmosphere: vapor

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Components:

2-heptanone:

Acute oral toxicity : LD50 (Rat): 1,600 mg/kg

Acute inhalation toxicity : LC50 (Rat): 16.7 mg/l
Exposure time: 4 h

Test atmosphere: vapor

2-butoxyethyl acetate:

Acute oral toxicity : LD50 (Rat): 1,880 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 1,500 mg/kg

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Components:

n-Butyl acetate:

Assessment : Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Skin sensitization

Based on available data, the classification criteria are not met.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Chronic toxicity

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Section 12: Ecological information

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Components:

2-heptanone:

Partition coefficient: n-octanol/water	:	log Pow: 2.26 (30 °C) pH: 7 Method: Regulation (EC) No. 440/2008, Annex, A.8 GLP: yes

n-Butyl acetate:

Partition coefficient: n-octanol/water	:	Pow: 200 (25 °C) log Pow: 2.3 (25 °C) pH: 7 Method: OECD Test Guideline 117 GLP: yes

Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0):

Partition coefficient: n-octanol/water	:	log Pow: 3.17 GLP: no

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Partition coefficient: n-octanol/water	:	log Pow: > 4 log Pow: > 4

2-butoxyethyl acetate:

Partition coefficient: n-octanol/water	:	log Pow: 1.51 (25 °C) pH: 7 Method: OECD Test Guideline 107 GLP: no

n-hexane:

Partition coefficient: n-octanol/water	:	log Pow: 4 (20 °C) pH: 7 Remarks: Information taken from reference works and the literature.

Mobility in soil

No data available

Other adverse effects

No data available

Section 13: Disposal considerations

Disposal methods

Waste from residues	:	Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.
Contaminated packaging	:	Packaging that is not properly emptied must be disposed of as the unused product.

Section 14: Transport information

International Regulations

UNRTDG

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
Environmentally hazardous	:	no

IATA-DGR

UN/ID No.	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	Flammable Liquids
Packing instruction (cargo aircraft)	:	366
Packing instruction (passenger aircraft)	:	355

IMDG-Code

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3

Packing group	:	III
Labels	:	3
EmS Code	:	F-E, S-E
Marine pollutant	:	no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
Not applicable for product as supplied.

Domestic regulation

NZS 5433

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
Hazchem Code	:	3Y
Marine pollutant	:	no

Special precautions for user
The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

HSNO Approval Number
HSR002662 Surface Coatings and Colourants Flammable Group Standard

Tolerable Exposure Limits (TEL)

Not applicable

Environmental Exposure Limits (EEL)
Not applicable

HSW Controls
Certified handler certificate not required.
Tracking hazardous substance not required.
Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

Section 16: Other information

Revision Date	:	14.11.2025

Further information

Other information	:	For multi-pack systems observe material safety data sheets of all components. Restricted to professional users.
Date format	:	dd.mm.yyyy

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
NZ BEI	:	New Zealand. Biological Exposure Indices
NZ OEL	:	New Zealand. Workplace Exposure Standards for Atmospheric Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit

NZ OEL / WES-TWA	:	Workplace Exposure Standard - Time Weighted average
NZ OEL / WES-STEL	:	Workplace Exposure Standard - Short-Term Exposure Limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NZ / EN

SAFETY DATA SHEET

352-50 5L Reducer fast G2

Version	Revision Date:	SDS Number:	Date of last issue: 15.08.2025
6.0	14.11.2025	000000000050411565	Date of first issue: 01.10.2024

Section 1: Identification

Product name : 352-50 5L Reducer fast G2

Product code : 000000000050411565

Manufacturer or supplier's details

Chemetall Kft., org. složka
Radlická 354/107b
158 00 Praha 5
Czech Republic

Distributor:
BASF New Zealand Ltd.
5E City Works Depot
77 Cook Street
Auckland Central, Auckland 1010
New Zealand

Emergency contact
Telephone: +64 9 255-4300

Emergency telephone : National Poisons Centre: 0800 764 766
BASF Emergency Advice Number: 0800 944 955 (24 hour advice in an emergency only)
BASF Emergency Advice Number: +61 3 8855 6666 (If calling from outside New Zealand)

Recommended use of the chemical and restrictions on use

Recommended use : Spraying
Thinner

Section 2: Hazard identification

GHS Classification

Flammable liquids : Category 3

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation : Category 2

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

Specific target organ toxicity - repeated exposure	:	Category 2 (Kidney, Liver, Central nervous system, Auditory system)
Aspiration hazard	:	Category 1

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements :
H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs (Kidney, Liver, Central nervous system, Auditory system) through prolonged or repeated exposure.

Precautionary Statements :
Prevention:
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 Get medical advice/ attention if you feel unwell.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification
If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Section 3: Composition/information on ingredients

Chemical nature : organic solvent

Components

Chemical name	Common Name/Synonyms	CAS-No.	Classification	Concentration (% w/w)
n-Butyl acetate	n-butyl acetate	123-86-4	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 50 -< 70
isobutyl acetate	isobutyl acetate	110-19-0	Flammable liquids, Category 2 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 20 -< 30
xylene	xylenes	1330-20-7	Flammable liquids, Category 3 Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2 Specific target organ toxicity - single exposure (Respiratory system), Category 3 Specific target organ toxicity - repeated exposure (Kidney, Liver, Central nervous system), Category 2 Aspiration hazard, Category 1	>= 10 -< 20

			Hazardous to the aquatic environment - chronic hazard, Category 3	
1-methoxy-2-propylacetate	2-methoxy-1-methylethyl acetate	108-65-6	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 1 -< 10
ethylbenzene	ethylbenzene	100-41-4	Flammable liquids, Category 2 Acute toxicity (Inhalation), Category 4 Specific target organ toxicity - repeated exposure (Auditory system), Category 2 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 3	>= 2.5 -< 10

Section 4: First-aid measures

General advice : In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product.
Symptoms of poisoning may occur even after several hours,

		continue medical observation for at least 48 hours after the accident. Keep patient warm and at rest. Never give anything by mouth to an unconscious person. Move out of dangerous area. Immediately remove contaminated clothing. First aid personnel should pay attention to their own safety.
If inhaled	:	If breathed in, move person into fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician or poison control center immediately.
In case of skin contact	:	Do NOT use solvents or thinners. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
In case of eye contact	:	Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Call a physician immediately. If easy to do, remove contact lens, if worn.
If swallowed	:	Rinse mouth with water. Do not induce vomiting due to aspiration hazard. Keep at rest. If swallowed, call a poison control center or doctor immediately.
Most important symptoms and effects, both acute and	:	May be fatal if swallowed and enters airways. Causes skin irritation.

delayed		Causes serious eye irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia. Risk of product entering the lungs on vomiting after ingestion.
Notes to physician	:	No known specific antidote. Treat symptomatically.

Section 5: Fire-fighting measures

Suitable extinguishing media	:	Water spray Dry powder Foam Carbon dioxide (CO2)
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire fighting	:	Fire will produce dense black smoke containing hazardous combustion products (see section 10).

Advice for firefighters

Specific extinguishing methods	:	Cool containers/tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Special protective equipment for fire-fighters	:	Appropriate breathing apparatus may be required.
Hazchem Code	:	3Y

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures	:	Avoid breathing vapours. For non-emergency personnel: Use personal protective equipment. Ensure adequate ventilation, especially in confined areas. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet.
Environmental precautions	:	If the product contaminates rivers and lakes or drains inform respective authorities.

Avoid subsoil penetration.

Do not allow uncontrolled discharge of product into the environment.

Methods and materials for containment and cleaning up	:	Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Ensure adequate ventilation.

Section 7: Handling and storage

Advice on protection against fire and explosion	:	Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapors are heavier than air and spread along floors. Vapor forms explosive mixtures with air. The relevant fire protection measures should be noted. Use explosion-proof equipment.
Advice on safe handling	:	Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers.

Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

The workplace should be equipped with an emergency shower and eye-rinsing facility.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Do not breathe vapors or spray mist.

Hygiene measures : Remove contaminated clothing immediately and dispose of safely.

Wash hands before breaks and at the end of workday.

Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions : Avoid direct sunlight.

Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel.

Always keep in containers of same material as the original one.

Observe label precautions.

Keep in a dry, cool and well-ventilated place.

Materials to avoid	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Packaging material	:	Suitable material: Carbon steel (Iron), tinned carbon steel (Tinplate)

Section 8: Exposure controls/personal protection

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
n-Butyl acetate	123-86-4	WES-STEL	200 ppm 950 mg/m3	NZ OEL
		WES-TWA	150 ppm 713 mg/m3	NZ OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
isobutyl acetate	110-19-0	WES-TWA	150 ppm 713 mg/m3	NZ OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
xylene	1330-20-7	WES-TWA	50 ppm 217 mg/m3	NZ OEL

	Further information: Ototoxin			
		TWA	20 ppm	ACGIH
ethylbenzene	100-41-4	WES-TWA	20 ppm 88 mg/m3	NZ OEL
	Further information: Ototoxin, Skin absorption			
		WES-STEL	40 ppm 176 mg/m3	NZ OEL
	Further information: Ototoxin, Skin absorption			
		TWA	20 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
xylene	1330-20-7	Methylhippuric acid	Urine	End of shift	1.5 g/l	NZ BEI
		Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI
ethylbenzene	100-41-4	Sum of mandelic acid and phenylglyoxylic acids	Urine	End of exposure or end of shift	0.25 g/g creatinine	NZ BEI

		Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Suitable respiratory equipment:

half-mask with A2P2 class combination filter

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection

Remarks	:	Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. nitrile gloves - material thickness: 0,35 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Preventive skin protection Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)
Eye protection	:	Required when there is a risk of eye contact. Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Skin and body protection	:	Anti-static protective clothing Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.
Protective measures	:	Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Section 9: Physical and chemical properties

Appearance	:	liquid
Color	:	colorless
Odor	:	hydrocarbon-like
pH	:	substance/mixture is non-polar/aprotic
Melting point/ range	:	not determined
	:	111.00 - 147.00 °C

Flash point	:	24 °C Method: ISO 3679
Flammability	:	Flammable liquid and vapour.
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	> 35.0 g/m3
Vapor pressure	:	not determined (20 °C) not determined (50 °C)
Density	:	0.875 g/cm3 (20 °C)
Solubility(ies) Water solubility	:	not determined
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	> 200 °C

Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity		
Viscosity, kinematic	:	6.0 mm2/s (23 °C)
		not determined (40 °C)
Flow time	:	< 30 s (23 °C) Cross section: 3 mm Method: ISO 2431
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Self-heating substances	:	The substance or mixture is not classified as self heating.
Metal corrosion rate	:	Not corrosive to metals.
Particle characteristics		
Particle size	:	The substance / product is marketed or used in a non solid or granular form.

Section 10: Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	Vapours may form ignitable mixture with air.
Conditions to avoid	:	Avoid direct sunlight.
		Heat, flames and sparks.

Incompatible materials	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

Section 11: Toxicological information

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method

Skin corrosion/irritation

Causes skin irritation.

Components:

n-Butyl acetate:

Assessment	:	Repeated exposure may cause skin dryness or cracking.

isobutyl acetate:

Assessment	:	Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

Based on available data, the classification criteria are not met.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Chronic toxicity

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs (Kidney, Liver, Central nervous system, Auditory system) through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Section 12: Ecological information

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Components:

n-Butyl acetate:

Partition coefficient: n-octanol/water	:	Pow: 200 (25 °C) log Pow: 2.3 (25 °C) pH: 7 Method: OECD Test Guideline 117

		GLP: yes
isobutyl acetate:		
Partition coefficient: n-octanol/water	:	log Pow: 2.3 (25 °C) pH: 7 Method: OECD Test Guideline 117 GLP: yes
xylene:		
Partition coefficient: n-octanol/water	:	log Pow: 3.12 - 3.20 (25 °C) GLP: no Remarks: Information taken from reference works and the literature.
1-methoxy-2-propylacetate:		
Partition coefficient: n-octanol/water	:	log Pow: 1.2 (20 °C) pH: 6.8 Method: OECD Test Guideline 117 GLP: yes
ethylbenzene:		
Partition coefficient: n-octanol/water	:	Pow: 4,170 (20 °C) log Pow: 3.6 (20 °C)

pH: 7.8

GLP: yes

Mobility in soil

No data available

Other adverse effects

No data available

Section 13: Disposal considerations

Disposal methods

Waste from residues	:	Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.
Contaminated packaging	:	Packaging that is not properly emptied must be disposed of as the unused product.

Section 14: Transport information

International Regulations

UNRTDG

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
Environmentally hazardous	:	no

IATA-DGR

UN/ID No.	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	Flammable Liquids
Packing instruction (cargo aircraft)	:	366
Packing instruction (passenger aircraft)	:	355

IMDG-Code

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
EmS Code	:	F-E, S-E
Marine pollutant	:	no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

NZS 5433

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL

Class	:	3
Packing group	:	III
Labels	:	3
Hazchem Code	:	3Y
Marine pollutant	:	no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

HSNO Approval Number

HSR002662 Surface Coatings and Colourants Flammable Group Standard

Tolerable Exposure Limits (TEL)

Not applicable

Environmental Exposure Limits (EEL)

Not applicable

HSW Controls

Certified handler certificate not required.
Tracking hazardous substance not required.
Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

Section 16: Other information

Revision Date	:	14.11.2025

Further information

Other information	:	For multi-pack systems observe material safety data sheets of all components. Restricted to professional users.
Date format	:	dd.mm.yyyy

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
NZ BEI	:	New Zealand. Biological Exposure Indices
NZ OEL	:	New Zealand. Workplace Exposure Standards for Atmospheric Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NZ OEL / WES-TWA	:	Workplace Exposure Standard - Time Weighted average
NZ OEL / WES-STEL	:	Workplace Exposure Standard - Short-Term Exposure Limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG -

International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NZ / EN

SAFETY DATA SHEET

352-70 REDUCER EXTRA SLOW 5L G2

Version	Revision Date:	SDS Number:	Date of last issue: 22.08.2025
5.0	14.11.2025	000000000050652947	Date of first issue: 20.07.2023

Section 1: Identification

Product name : 352-70 REDUCER EXTRA SLOW 5L G2

Product code : 000000000050652947

Manufacturer or supplier's details

Chemetall Kft., org. složka
Radlická 354/107b
158 00 Praha 5
Czech Republic

Distributor:
BASF New Zealand Ltd.
5E City Works Depot
77 Cook Street
Auckland Central, Auckland 1010
New Zealand

Emergency contact
Telephone: +64 9 255-4300

Emergency telephone : National Poisons Centre: 0800 764 766
BASF Emergency Advice Number: 0800 944 955 (24 hour advice in an emergency only)
BASF Emergency Advice Number: +61 3 8855 6666 (If calling from outside New Zealand)

Recommended use of the chemical and restrictions on use

Recommended use : Spraying
Thinner

Section 2: Hazard identification

GHS Classification

Flammable liquids : Category 3

Serious eye damage/eye irritation : Category 2

Carcinogenicity : Category 2

Specific target organ toxicity - : Category 3 (Central nervous system)

single exposure

Specific target organ toxicity - repeated exposure (Inhalation)	:	Category 2 (Lungs)
Aspiration hazard	:	Category 1
Hazardous to the aquatic environment - chronic hazard	:	Category 2

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements :
H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H373 May cause damage to organs (Lungs) through prolonged or repeated exposure if inhaled.
H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements :
Prevention:
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391 Collect spillage.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification
If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Section 3: Composition/information on ingredients

Chemical nature : organic solvent

Components

Chemical name	Common Name/Synonyms	CAS-No.	Classification	Concentration (% w/w)
2-heptanone	heptan-2-one	110-43-0	Flammable liquids, Category 3 Acute toxicity (Oral), Category 4 Acute toxicity (Inhalation), Category 4 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 50 -< 70
Solvent naphtha (petroleum), heavy arom.	Solvent naphtha, petroleum, heavy arom.	64742-94-5	Specific target organ toxicity - single exposure (Central nervous system), Category 3 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 2	>= 30 -< 50

2-butoxyethyl acetate	2-butoxyethyl acetate	112-07-2	Flammable liquids, Category 4 Acute toxicity (Oral), Category 4 Acute toxicity (Dermal), Category 4	>= 10 -< 20
Benzoic acid	benzoic acid	65-85-0	Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 1 Specific target organ toxicity - repeated exposure (Inhalation) (Lungs), Category 1	>= 1 -< 3
naphthalene	naphthalene	91-20-3	Flammable solids, Category 2 Acute toxicity (Oral), Category 4 Carcinogenicity, Category 2 Hazardous to the aquatic environment - acute hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 1	>= 0.25 -< 1

Section 4: First-aid measures

General advice	:	In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product. Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident. Keep patient warm and at rest. Never give anything by mouth to an unconscious person. Move out of dangerous area. Immediately remove contaminated clothing. First aid personnel should pay attention to their own safety.
If inhaled	:	If breathed in, move person into fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician or poison control center immediately.
In case of skin contact	:	Do NOT use solvents or thinners. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
In case of eye contact	:	Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Call a physician immediately. If easy to do, remove contact lens, if worn.
If swallowed	:	Rinse mouth with water.

Do not induce vomiting due to aspiration hazard.

Keep at rest.

If swallowed, call a poison control center or doctor immediately.

Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Suspected of causing cancer.

May cause damage to organs through prolonged or repeated exposure if inhaled.

Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.

Risk of product entering the lungs on vomiting after ingestion.

Notes to physician : No known specific antidote.
Treat symptomatically.

Section 5: Fire-fighting measures

Suitable extinguishing media : Water spray

Dry powder

Foam

Carbon dioxide (CO2)

Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire fighting	:	Fire will produce dense black smoke containing hazardous combustion products (see section 10).

Advice for firefighters

Specific extinguishing methods	:	Cool containers/tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Special protective equipment for fire-fighters	:	Appropriate breathing apparatus may be required.
Hazchem Code	:	3Y

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures	:	Avoid breathing vapours. For non-emergency personnel: Use personal protective equipment.

Ensure adequate ventilation, especially in confined areas.

Keep away from sources of ignition.

For emergency responders:

Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.

Avoid subsoil penetration.

If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Ensure adequate ventilation.

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

Section 7: Handling and storage

Advice on protection against fire and explosion : Avoid all sources of ignition: heat, sparks, open flame.

Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear.

Solvent vapors are heavier than air and spread along floors. Vapor forms explosive mixtures with air.

The relevant fire protection measures should be noted.

Use explosion-proof equipment.

Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).

Do not return residues to the storage containers.

Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

The workplace should be equipped with an emergency shower and eye-rinsing facility.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Do not breathe vapors or spray mist.

Hygiene measures : Remove contaminated clothing immediately and dispose of safely.

		Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.
Further information on storage conditions	:	Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Keep in a dry, cool and well-ventilated place.
Materials to avoid	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Packaging material	:	Suitable material: Stove-lacquer RDL 50, Stove-lacquer R 78433, Stove-lacquer 79/14/3 (Müller/CH), Stove-lacquer EHD0022, Stove-lacquer Vitalure 745, Standard interior paint, Stove-lacquer C222A/C221A, Carbon steel (Iron), tinned carbon steel (Tinplate)

Section 8: Exposure controls/personal protection

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-heptanone	110-43-0	WES-TWA	50 ppm	NZ OEL

			233 mg/m3	
		TWA	50 ppm	ACGIH
Solvent naphtha (petroleum), heavy arom.	64742-94-5	TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
2-butoxyethyl acetate	112-07-2	TWA	20 ppm	ACGIH
Benzoic acid	65-85-0	TWA (Inhalable fraction and vapor)	0.5 mg/m3	ACGIH
naphthalene	91-20-3	WES-TWA	0.5 ppm 2.6 mg/m3	NZ OEL
	Further information: Suspected human carcinogen, Skin absorption			
		WES-STEL	2 ppm 10 mg/m3	NZ OEL
	Further information: Suspected human carcinogen, Skin absorption			
		TWA	10 ppm	ACGIH

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Suitable respiratory equipment:

half-mask with A1P2 class combination filter

In case of mist, spray or aerosol exposure wear suitable

personal respiratory protection and protective suit.

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection

Remarks : Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g.

butyl rubber gloves - material thickness: 0.5 mm

Further information on penetration time is available from the manufacturer of the glove.

Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.

The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Request information on glove permeation properties from the glove supplier.

Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Preventive skin protection

Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Eye protection : Required when there is a risk of eye contact.

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Skin and body protection : Anti-static protective clothing

Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

Protective measures : Do not breathe vapour/spray.

Eye wash fountains and safety showers must be easily accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Section 9: Physical and chemical properties

Appearance	:	liquid
Color	:	colorless
Odor	:	ester-like
pH	:	substance/mixture is non-polar/aprotic
Melting point/ range	:	not determined
Boiling point/boiling range	:	180.00 °C
Flash point	:	42 °C Method: ISO 3679
Flammability	:	Flammable liquid and vapour.
Upper explosion limit / Upper flammability limit	:	not determined

Lower explosion limit / Lower flammability limit	:	> 35.0 g/m3
Vapor pressure	:	0.3 hPa (20 °C) not determined (50 °C)
Density	:	0.877 g/cm3 (20 °C)
Solubility(ies) Water solubility	: :	 not determined
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	> 200 °C
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity Viscosity, kinematic	: :	 not determined (40 °C) 6.0 mm2/s (23 °C)
Flow time	:	< 30 s (23 °C) Cross section: 3 mm

		Method: ISO 2431
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Self-heating substances	:	The substance or mixture is not classified as self heating.
Metal corrosion rate	:	Not corrosive to metals.
Particle characteristics Particle size	:	The substance / product is marketed or used in a non solid or granular form.

Section 10: Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	Vapours may form ignitable mixture with air.
Conditions to avoid	:	Avoid direct sunlight. Heat, flames and sparks.
Incompatible materials	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

Section 11: Toxicological information

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h

Test atmosphere: vapor

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Components:

2-heptanone:

Acute oral toxicity : LD50 (Rat): 1,600 mg/kg

Acute inhalation toxicity : LC50 (Rat): 16.7 mg/l
Exposure time: 4 h

Test atmosphere: vapor

2-butoxyethyl acetate:

Acute oral toxicity : LD50 (Rat): 1,880 mg/kg

Acute dermal toxicity	:	LD50 (Rabbit): 1,500 mg/kg

Skin corrosion/irritation
Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation
Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization
Based on available data, the classification criteria are not met.

Respiratory sensitization
Based on available data, the classification criteria are not met.

Chronic toxicity

Germ cell mutagenicity
Based on available data, the classification criteria are not met.

Carcinogenicity
Suspected of causing cancer.

Reproductive toxicity
Based on available data, the classification criteria are not met.

STOT-single exposure
May cause drowsiness or dizziness.

STOT-repeated exposure
May cause damage to organs (Lungs) through prolonged or repeated exposure if inhaled.

Aspiration toxicity
May be fatal if swallowed and enters airways.

Section 12: Ecological information

Ecotoxicity
No data available

Persistence and degradability

No data available

Bioaccumulative potential

Components:

2-heptanone:

Partition coefficient: n-octanol/water	:	log Pow: 2.26 (30 °C) pH: 7 Method: Regulation (EC) No. 440/2008, Annex, A.8 GLP: yes

Solvent naphtha (petroleum), heavy arom.:

Partition coefficient: n-octanol/water	:	log Pow: 2.9 - 6.1 Method: OECD Test Guideline 117

2-butoxyethyl acetate:

Partition coefficient: n-octanol/water	:	log Pow: 1.51 (25 °C) pH: 7 Method: OECD Test Guideline 107 GLP: no

Benzoic acid:

Partition coefficient: n-octanol/water	:	log Pow: 1.88

naphthalene:

Partition coefficient: n-octanol/water	:	log Pow: 3.4 (25 °C) Method: OECD Test Guideline 107

Mobility in soil

No data available

Other adverse effects

No data available

Section 13: Disposal considerations

Disposal methods

Waste from residues	:	Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.
Contaminated packaging	:	Packaging that is not properly emptied must be disposed of as the unused product.

Section 14: Transport information

International Regulations

UNRTDG

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3

Environmentally hazardous	:	yes

IATA-DGR

UN/ID No.	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	Flammable Liquids
Packing instruction (cargo aircraft)	:	366
Packing instruction (passenger aircraft)	:	355

IMDG-Code

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL (SOLVENT NAPHTHA, NAPHTHALENE)
Class	:	3
Packing group	:	III
Labels	:	3
EmS Code	:	F-E, S-E
Marine pollutant	:	yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

NZS 5433

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
Hazchem Code	:	3Y
Marine pollutant	:	yes

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

HSNO Approval Number

HSR002669 Surface Coatings and Colourants Flammable Carcinogenic Group Standard

Tolerable Exposure Limits (TEL)

Not applicable

Environmental Exposure Limits (EEL)

Not applicable

HSW Controls

Certified handler certificate not required.
Tracking hazardous substance not required.
Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

Section 16: Other information

Revision Date : 14.11.2025

Further information

Other information : For multi-pack systems observe material safety data sheets of all components.
Restricted to professional users.

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

NZ OEL : New Zealand. Workplace Exposure Standards for Atmospheric Contaminants

ACGIH / TWA : 8-hour, time-weighted average

NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average

NZ OEL / WES-STEL : Workplace Exposure Standard - Short-Term Exposure Limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NZ / EN

SAFETY DATA SHEET

352-70 REDUCER EXTRA SLOW 5L G2

Version	Revision Date:	SDS Number:	Date of last issue: 22.08.2025
5.0	14.11.2025	000000000050652947	Date of first issue: 20.07.2023

Section 1: Identification

Product name : 352-70 REDUCER EXTRA SLOW 5L G2

Product code : 000000000050652947

Manufacturer or supplier's details

Chemetall Kft., org. složka
Radlická 354/107b
158 00 Praha 5
Czech Republic

Distributor:
BASF New Zealand Ltd.
5E City Works Depot
77 Cook Street
Auckland Central, Auckland 1010
New Zealand

Emergency contact
Telephone: +64 9 255-4300

Emergency telephone : National Poisons Centre: 0800 764 766
BASF Emergency Advice Number: 0800 944 955 (24 hour advice in an emergency only)
BASF Emergency Advice Number: +61 3 8855 6666 (If calling from outside New Zealand)

Recommended use of the chemical and restrictions on use

Recommended use : Spraying
Thinner

Section 2: Hazard identification

GHS Classification

Flammable liquids : Category 3

Serious eye damage/eye irritation : Category 2

Carcinogenicity : Category 2

Specific target organ toxicity - : Category 3 (Central nervous system)

single exposure

Specific target organ toxicity - repeated exposure (Inhalation)	:	Category 2 (Lungs)
Aspiration hazard	:	Category 1
Hazardous to the aquatic environment - chronic hazard	:	Category 2

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements :
H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H373 May cause damage to organs (Lungs) through prolonged or repeated exposure if inhaled.
H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements :
Prevention:
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391 Collect spillage.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification
If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Section 3: Composition/information on ingredients

Chemical nature : organic solvent

Components

Chemical name	Common Name/Synonyms	CAS-No.	Classification	Concentration (% w/w)
2-heptanone	heptan-2-one	110-43-0	Flammable liquids, Category 3 Acute toxicity (Oral), Category 4 Acute toxicity (Inhalation), Category 4 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 50 -< 70
Solvent naphtha (petroleum), heavy arom.	Solvent naphtha, petroleum, heavy arom.	64742-94-5	Specific target organ toxicity - single exposure (Central nervous system), Category 3 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 2	>= 30 -< 50

2-butoxyethyl acetate	2-butoxyethyl acetate	112-07-2	Flammable liquids, Category 4 Acute toxicity (Oral), Category 4 Acute toxicity (Dermal), Category 4	>= 10 -< 20
Benzoic acid	benzoic acid	65-85-0	Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 1 Specific target organ toxicity - repeated exposure (Inhalation) (Lungs), Category 1	>= 1 -< 3
naphthalene	naphthalene	91-20-3	Flammable solids, Category 2 Acute toxicity (Oral), Category 4 Carcinogenicity, Category 2 Hazardous to the aquatic environment - acute hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 1	>= 0.25 -< 1

Section 4: First-aid measures

General advice	:	In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product. Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident. Keep patient warm and at rest. Never give anything by mouth to an unconscious person. Move out of dangerous area. Immediately remove contaminated clothing. First aid personnel should pay attention to their own safety.
If inhaled	:	If breathed in, move person into fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician or poison control center immediately.
In case of skin contact	:	Do NOT use solvents or thinners. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
In case of eye contact	:	Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Call a physician immediately. If easy to do, remove contact lens, if worn.
If swallowed	:	Rinse mouth with water.

Do not induce vomiting due to aspiration hazard.

Keep at rest.

If swallowed, call a poison control center or doctor immediately.

Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Suspected of causing cancer.

May cause damage to organs through prolonged or repeated exposure if inhaled.

Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.

Risk of product entering the lungs on vomiting after ingestion.

Notes to physician : No known specific antidote.
Treat symptomatically.

Section 5: Fire-fighting measures

Suitable extinguishing media : Water spray

Dry powder

Foam

Carbon dioxide (CO2)

Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire fighting	:	Fire will produce dense black smoke containing hazardous combustion products (see section 10).

Advice for firefighters

Specific extinguishing methods	:	Cool containers/tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Special protective equipment for fire-fighters	:	Appropriate breathing apparatus may be required.
Hazchem Code	:	3Y

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures	:	Avoid breathing vapours. For non-emergency personnel: Use personal protective equipment.

Ensure adequate ventilation, especially in confined areas.

Keep away from sources of ignition.

For emergency responders:

Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.

Avoid subsoil penetration.

If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Ensure adequate ventilation.

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

Section 7: Handling and storage

Advice on protection against fire and explosion : Avoid all sources of ignition: heat, sparks, open flame.

Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear.

Solvent vapors are heavier than air and spread along floors. Vapor forms explosive mixtures with air.

The relevant fire protection measures should be noted.

Use explosion-proof equipment.

Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).

Do not return residues to the storage containers.

Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

The workplace should be equipped with an emergency shower and eye-rinsing facility.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Do not breathe vapors or spray mist.

Hygiene measures : Remove contaminated clothing immediately and dispose of safely.

		Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.
Further information on storage conditions	:	Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Keep in a dry, cool and well-ventilated place.
Materials to avoid	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Packaging material	:	Suitable material: Stove-lacquer RDL 50, Stove-lacquer R 78433, Stove-lacquer 79/14/3 (Müller/CH), Stove-lacquer EHD0022, Stove-lacquer Vitalure 745, Standard interior paint, Stove-lacquer C222A/C221A, Carbon steel (Iron), tinned carbon steel (Tinplate)

Section 8: Exposure controls/personal protection

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-heptanone	110-43-0	WES-TWA	50 ppm	NZ OEL

			233 mg/m3	
		TWA	50 ppm	ACGIH
Solvent naphtha (petroleum), heavy arom.	64742-94-5	TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
2-butoxyethyl acetate	112-07-2	TWA	20 ppm	ACGIH
Benzoic acid	65-85-0	TWA (Inhalable fraction and vapor)	0.5 mg/m3	ACGIH
naphthalene	91-20-3	WES-TWA	0.5 ppm 2.6 mg/m3	NZ OEL
	Further information: Suspected human carcinogen, Skin absorption			
		WES-STEL	2 ppm 10 mg/m3	NZ OEL
	Further information: Suspected human carcinogen, Skin absorption			
		TWA	10 ppm	ACGIH

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Suitable respiratory equipment:

half-mask with A1P2 class combination filter

In case of mist, spray or aerosol exposure wear suitable

personal respiratory protection and protective suit.

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection

Remarks : Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g.

butyl rubber gloves - material thickness: 0.5 mm

Further information on penetration time is available from the manufacturer of the glove.

Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.

The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Request information on glove permeation properties from the glove supplier.

Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Preventive skin protection

Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Eye protection : Required when there is a risk of eye contact.

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Skin and body protection : Anti-static protective clothing

Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

Protective measures : Do not breathe vapour/spray.

Eye wash fountains and safety showers must be easily accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Section 9: Physical and chemical properties

Appearance	:	liquid
Color	:	colorless
Odor	:	ester-like
pH	:	substance/mixture is non-polar/aprotic
Melting point/ range	:	not determined
Boiling point/boiling range	:	180.00 °C
Flash point	:	42 °C Method: ISO 3679
Flammability	:	Flammable liquid and vapour.
Upper explosion limit / Upper flammability limit	:	not determined

Lower explosion limit / Lower flammability limit	:	> 35.0 g/m3
Vapor pressure	:	0.3 hPa (20 °C) not determined (50 °C)
Density	:	0.877 g/cm3 (20 °C)
Solubility(ies) Water solubility	: :	 not determined
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	> 200 °C
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity Viscosity, kinematic	: :	 not determined (40 °C) 6.0 mm2/s (23 °C)
Flow time	:	< 30 s (23 °C) Cross section: 3 mm

		Method: ISO 2431
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Self-heating substances	:	The substance or mixture is not classified as self heating.
Metal corrosion rate	:	Not corrosive to metals.
Particle characteristics Particle size	:	The substance / product is marketed or used in a non solid or granular form.

Section 10: Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	Vapours may form ignitable mixture with air.
Conditions to avoid	:	Avoid direct sunlight. Heat, flames and sparks.
Incompatible materials	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

Section 11: Toxicological information

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h

Test atmosphere: vapor

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Components:

2-heptanone:

Acute oral toxicity : LD50 (Rat): 1,600 mg/kg

Acute inhalation toxicity : LC50 (Rat): 16.7 mg/l
Exposure time: 4 h

Test atmosphere: vapor

2-butoxyethyl acetate:

Acute oral toxicity : LD50 (Rat): 1,880 mg/kg

Acute dermal toxicity	:	LD50 (Rabbit): 1,500 mg/kg

Skin corrosion/irritation
Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation
Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization
Based on available data, the classification criteria are not met.

Respiratory sensitization
Based on available data, the classification criteria are not met.

Chronic toxicity

Germ cell mutagenicity
Based on available data, the classification criteria are not met.

Carcinogenicity
Suspected of causing cancer.

Reproductive toxicity
Based on available data, the classification criteria are not met.

STOT-single exposure
May cause drowsiness or dizziness.

STOT-repeated exposure
May cause damage to organs (Lungs) through prolonged or repeated exposure if inhaled.

Aspiration toxicity
May be fatal if swallowed and enters airways.

Section 12: Ecological information

Ecotoxicity
No data available

Persistence and degradability

No data available

Bioaccumulative potential

Components:

2-heptanone:

Partition coefficient: n-octanol/water	:	log Pow: 2.26 (30 °C) pH: 7 Method: Regulation (EC) No. 440/2008, Annex, A.8 GLP: yes

Solvent naphtha (petroleum), heavy arom.:

Partition coefficient: n-octanol/water	:	log Pow: 2.9 - 6.1 Method: OECD Test Guideline 117

2-butoxyethyl acetate:

Partition coefficient: n-octanol/water	:	log Pow: 1.51 (25 °C) pH: 7 Method: OECD Test Guideline 107 GLP: no

Benzoic acid:

Partition coefficient: n-octanol/water	:	log Pow: 1.88

naphthalene:

Partition coefficient: n-octanol/water	:	log Pow: 3.4 (25 °C) Method: OECD Test Guideline 107

Mobility in soil

No data available

Other adverse effects

No data available

Section 13: Disposal considerations

Disposal methods

Waste from residues	:	Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.
Contaminated packaging	:	Packaging that is not properly emptied must be disposed of as the unused product.

Section 14: Transport information

International Regulations

UNRTDG

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3

Environmentally hazardous	:	yes

IATA-DGR

UN/ID No.	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	Flammable Liquids
Packing instruction (cargo aircraft)	:	366
Packing instruction (passenger aircraft)	:	355

IMDG-Code

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL (SOLVENT NAPHTHA, NAPHTHALENE)
Class	:	3
Packing group	:	III
Labels	:	3
EmS Code	:	F-E, S-E
Marine pollutant	:	yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

NZS 5433

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
Hazchem Code	:	3Y
Marine pollutant	:	yes

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

HSNO Approval Number

HSR002669 Surface Coatings and Colourants Flammable Carcinogenic Group Standard

Tolerable Exposure Limits (TEL)

Not applicable

Environmental Exposure Limits (EEL)

Not applicable

HSW Controls

Certified handler certificate not required.
Tracking hazardous substance not required.
Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

Section 16: Other information

Revision Date : 14.11.2025

Further information

Other information : For multi-pack systems observe material safety data sheets of all components.
Restricted to professional users.

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

NZ OEL : New Zealand. Workplace Exposure Standards for Atmospheric Contaminants

ACGIH / TWA : 8-hour, time-weighted average

NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average

NZ OEL / WES-STEL : Workplace Exposure Standard - Short-Term Exposure Limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NZ / EN

352-91 5L Reducer normal G2

Version	Revision Date:	SDS Number:	Date of last issue: 15.08.2025
6.0	14.11.2025	000000000050411580	Date of first issue: 03.06.2024

Section 1: Identification

Product name : 352-91 5L Reducer normal G2

Product code : 000000000050411580

Manufacturer or supplier's details

Chemetall Kft., org. složka
Radlická 354/107b
158 00 Praha 5
Czech Republic

Distributor:
BASF New Zealand Ltd.
5E City Works Depot
77 Cook Street
Auckland Central, Auckland 1010
New Zealand

Emergency contact
Telephone: +64 9 255-4300

Emergency telephone : National Poisons Centre: 0800 764 766
BASF Emergency Advice Number: 0800 944 955 (24 hour advice in an emergency only)
BASF Emergency Advice Number: +61 3 8855 6666 (If calling from outside New Zealand)

Recommended use of the chemical and restrictions on use

Recommended use : Spraying
Thinner
Spraying

Section 2: Hazard identification

GHS Classification

Flammable liquids : Category 3

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation : Category 2

Skin sensitization	:	Category 1
Reproductive toxicity	:	Category 2
Specific target organ toxicity - single exposure	:	Category 3 (Respiratory system, Central nervous system)
Specific target organ toxicity - repeated exposure	:	Category 2 (Kidney, Liver, Central nervous system, Auditory system)
Aspiration hazard	:	Category 1
Hazardous to the aquatic environment - chronic hazard	:	Category 3

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs (Kidney, Liver, Central nervous system, Auditory system) through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification
If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Section 3: Composition/information on ingredients

Chemical nature : organic solvent

Components

Chemical name	Common Name/Synonyms	CAS-No.	Classification	Concentration (% w/w)
n-Butyl acetate	n-butyl acetate	123-86-4	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 50 -< 70
Solvent naphtha	Solvent naphtha	64742-95-6	Flammable liquids,	>= 10 -< 20

(petroleum), light arom. (CAS EU: 128601-23-0)	(petroleum), light arom. (CAS EU: 128601-23-0)		Category 3 Specific target organ toxicity - single exposure (Respiratory system, Central nervous system), Category 3 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 2	
xylene	xylenes	1330-20-7	Flammable liquids, Category 3 Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2 Specific target organ toxicity - single exposure (Respiratory system), Category 3 Specific target organ toxicity - repeated exposure (Kidney, Liver, Central nervous system), Category 2 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard,	>= 10 -< 20

			Category 3	
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-49-0	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Central nervous system), Category 3 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 3	>= 2.5 -< 10
1-methoxy-2-propylacetate	2-methoxy-1-methylethyl acetate	108-65-6	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 1 -< 10
2-butoxyethyl acetate	2-butoxyethyl acetate	112-07-2	Flammable liquids, Category 4 Acute toxicity (Oral), Category 4 Acute toxicity (Dermal), Category 4	>= 1 -< 10
ethylbenzene	ethylbenzene	100-41-4	Flammable liquids, Category 2 Acute toxicity (Inhalation), Category 4	>= 1 -< 2.5

			Specific target organ toxicity - repeated exposure (Auditory system), Category 2 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 3	
Hydrocarbons, by-products with terpene processing	Hydrocarbons, terpene processing by-products	68956-56-9	Flammable liquids, Category 3 Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2 Skin sensitization, Category 1 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 2	>= 1 -< 2.5
n-hexane	n-hexane	110-54-3	Flammable liquids, Category 2 Skin corrosion/irritation, Category 2 Reproductive toxicity, Category 2 Specific target organ toxicity - single	>= 0.1 -< 0.25

			exposure (Central nervous system), Category 3 Specific target organ toxicity - repeated exposure, Category 1 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 2	

Section 4: First-aid measures

General advice : In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product.
Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.
Never give anything by mouth to an unconscious person.
Move out of dangerous area.
Immediately remove contaminated clothing.
First aid personnel should pay attention to their own safety.
Keep patient warm and at rest.

If inhaled : If breathed in, move person into fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician or poison control center immediately.

In case of skin contact	:	Do NOT use solvents or thinners. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
In case of eye contact	:	If easy to do, remove contact lens, if worn. Call a physician immediately. Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
If swallowed	:	Rinse mouth with water. Do not induce vomiting due to aspiration hazard. Keep at rest. If swallowed, call a poison control center or doctor immediately.
Most important symptoms and effects, both acute and delayed	:	May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. Information, i.e. additional information on symptoms and

effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.

Risk of product entering the lungs on vomiting after ingestion.

Notes to physician : No known specific antidote.
Treat symptomatically.

Section 5: Fire-fighting measures

Suitable extinguishing media : Dry powder

Carbon dioxide (CO2)

Water spray

Foam

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire fighting : Fire will produce dense black smoke containing hazardous combustion products (see section 10).

Advice for firefighters

Specific extinguishing methods	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cool containers/tanks with water spray.
Special protective equipment for fire-fighters	:	Appropriate breathing apparatus may be required.
Hazchem Code	:	3Y

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures	:	Avoid breathing vapours. For non-emergency personnel: Use personal protective equipment. Ensure adequate ventilation, especially in confined areas. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet.
Environmental precautions	:	If the product contaminates rivers and lakes or drains inform

respective authorities.

Avoid subsoil penetration.

Do not allow uncontrolled discharge of product into the environment.

Methods and materials for containment and cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

Ensure adequate ventilation.

Section 7: Handling and storage

Advice on protection against fire and explosion : Avoid all sources of ignition: heat, sparks, open flame.

Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear.

Solvent vapors are heavier than air and spread along floors. Vapor forms explosive mixtures with air.

Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).

Do not return residues to the storage containers.

Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the

health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

The workplace should be equipped with an emergency shower and eye-rinsing facility.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Do not breathe vapors or spray mist.

Hygiene measures : Remove contaminated clothing immediately and dispose of safely.

Wash hands before breaks and at the end of workday.

Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions : Keep away from heat.

Avoid direct sunlight.

Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel.

Always keep in containers of same material as the original one.

Observe label precautions.

Store protected against freezing.

Keep in a dry, cool and well-ventilated place.

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Recommended storage temperature : 5.00 - 35.00 °C

Packaging material : Suitable material: Carbon steel (Iron), tinned carbon steel (Tinplate)

Section 8: Exposure controls/personal protection

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
n-Butyl acetate	123-86-4	WES-STEL	200 ppm 950 mg/m3	NZ OEL
		WES-TWA	150 ppm 713 mg/m3	NZ OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
Solvent naphtha (petroleum), light arom. (CAS EU: 128601-	64742-95-6	WES-TWA	300 ppm	NZ OEL

23-0)			890 mg/m3	
		WES-STEL	500 ppm 1,480 mg/m3	NZ OEL
xylene	1330-20-7	WES-TWA	50 ppm 217 mg/m3	NZ OEL
	Further information: Ototoxin			
		TWA	20 ppm	ACGIH
2-butoxyethyl acetate	112-07-2	TWA	20 ppm	ACGIH
ethylbenzene	100-41-4	WES-TWA	20 ppm 88 mg/m3	NZ OEL
	Further information: Ototoxin, Skin absorption			
		WES-STEL	40 ppm 176 mg/m3	NZ OEL
	Further information: Ototoxin, Skin absorption			
		TWA	20 ppm	ACGIH
n-hexane	110-54-3	WES-TWA	20 ppm 72 mg/m3	NZ OEL
	Further information: Ototoxin, Exposure can also be estimated by biological monitoring			
		TWA	50 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
xylene	1330-20-7	Methylhippuric acid	Urine	End of shift	1.5 g/l	NZ BEI
		Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI
ethylbenzene	100-41-4	Sum of mandelic acid and phenylglyoxylic acids	Urine	End of exposure or end of shift	0.25 g/g creatinine	NZ BEI
		Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI
n-hexane	110-54-3	2,5-hexanedione	Urine	End of shift	5 mg/l	NZ BEI
		2,5-Hexanedion	Urine	End of shift	0.5 mg/l	ACGIH BEI

		e				

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Suitable respiratory equipment:

half-mask with A2P2 class combination filter

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection

Remarks : Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g.

nitrile gloves - material thickness: 0,35 mm

Further information on penetration time is available from the manufacturer of the glove.

Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.

The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Request information on glove permeation properties from the glove supplier.

Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Preventive skin protection

Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Eye protection : Required when there is a risk of eye contact.

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Skin and body protection : Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

chemical-resistant disposable coveralls

Protective measures	:	Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Section 9: Physical and chemical properties

Appearance	:	liquid
Color	:	colorless
Odor	:	hydrocarbon-like
pH	:	substance/mixture is non-polar/aprotic
Melting point/ range	:	not determined
Boiling point/boiling range	:	126.00 - 190.00 °C
Flash point	:	27 °C Method: ISO 3679

Evaporation rate	:	No data available
Flammability	:	Flammable liquid and vapour.
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	> 35.0 g/m3
Vapor pressure	:	5.0 hPa (20 °C) 48.0 hPa (50 °C)
Density	:	0.867 g/cm3 (20 °C)
Solubility(ies) Water solubility	:	not determined
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	> 200 °C

Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity		
Viscosity, kinematic	:	6.0 mm2/s (23 °C)
		not determined (40 °C)
Flow time	:	< 30 s (23 °C) Cross section: 3 mm Method: ISO 2431
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Self-heating substances	:	The substance or mixture is not classified as self heating.
Metal corrosion rate	:	Not corrosive to metals.
Particle characteristics		
Particle size	:	The substance / product is marketed or used in a non solid or granular form.

Section 10: Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	Vapours may form ignitable mixture with air.
Conditions to avoid	:	Avoid direct sunlight.

		Heat, flames and sparks. Heat. Protect from frost.
Incompatible materials	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

Section 11: Toxicological information

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method

Components:

2-butoxyethyl acetate:

Acute oral toxicity	:	LD50 (Rat): 1,880 mg/kg
Acute dermal toxicity	:	LD50 (Rabbit): 1,500 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:

n-Butyl acetate:

Assessment	:	Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Assessment	:	Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Chronic toxicity

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT-single exposure

May cause respiratory irritation.
May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs (Kidney, Liver, Central nervous system, Auditory system) through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Section 12: Ecological information

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Components:

n-Butyl acetate:

Partition coefficient: n-octanol/water	:	Pow: 200 (25 °C) log Pow: 2.3 (25 °C) pH: 7 Method: OECD Test Guideline 117 GLP: yes

Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0):

Partition coefficient: n-octanol/water	:	log Pow: 3.17

GLP: no

xylene:

Partition coefficient: n-octanol/water : log Pow: 3.12 - 3.20 (25 °C)

GLP: no

Remarks: Information taken from reference works and the literature.

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Partition coefficient: n-octanol/water : log Pow: > 4

log Pow: > 4

1-methoxy-2-propylacetate:

Partition coefficient: n-octanol/water : log Pow: 1.2 (20 °C)

pH: 6.8

Method: OECD Test Guideline 117

GLP: yes

2-butoxyethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 1.51 (25 °C)

pH: 7

Method: OECD Test Guideline 107

GLP: no

ethylbenzene:

Partition coefficient: n-octanol/water : Pow: 4,170 (20 °C)

log Pow: 3.6 (20 °C)

pH: 7.8

GLP: yes

Hydrocarbons, by-products with terpene processing:

Partition coefficient: n-octanol/water : Pow: 31,770 (25 °C)

log Pow: 4.5 (25 °C)

Method: OECD Test Guideline 107

n-hexane:

Partition coefficient: n-octanol/water : log Pow: 4 (20 °C)

pH: 7

Remarks: Information taken from reference works and the literature.

Mobility in soil

No data available

Other adverse effects

No data available

Section 13: Disposal considerations

Disposal methods

Waste from residues	:	Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.
Contaminated packaging	:	Packaging that is not properly emptied must be disposed of as the unused product.

Section 14: Transport information

International Regulations

UNRTDG

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
Environmentally hazardous	:	no

IATA-DGR

UN/ID No.	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III

Labels	:	Flammable Liquids
Packing instruction (cargo aircraft)	:	366
Packing instruction (passenger aircraft)	:	355

IMDG-Code

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
EmS Code	:	F-E, S-E
Marine pollutant	:	no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
Not applicable for product as supplied.

Domestic regulation

NZS 5433

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3

Hazchem Code	:	3Y
Marine pollutant	:	no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

HSNO Approval Number

HSR002662 Surface Coatings and Colourants Flammable Group Standard

Tolerable Exposure Limits (TEL)

Not applicable

Environmental Exposure Limits (EEL)

Not applicable

HSW Controls

Certified handler certificate not required.
Tracking hazardous substance not required.
Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

Section 16: Other information

Revision Date	:	14.11.2025

Further information

Other information	:	For multi-pack systems observe material safety data sheets of

all components.
Restricted to professional users.

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)

NZ BEI : New Zealand. Biological Exposure Indices

NZ OEL : New Zealand. Workplace Exposure Standards for Atmospheric Contaminants

ACGIH / TWA : 8-hour, time-weighted average

ACGIH / STEL : Short-term exposure limit

NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average

NZ OEL / WES-STEL : Workplace Exposure Standard - Short-Term Exposure Limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 -

Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NZ / EN

352-91 REDUCER NORMAL

Version	Revision Date:	SDS Number:	Date of last issue: 15.08.2025
6.0	14.11.2025	000000000050273420	Date of first issue: 03.06.2024

Section 1: Identification

Product name : 352-91 REDUCER NORMAL

Product code : 000000000050273420

Manufacturer or supplier's details

Chemetall Kft., org. složka
Radlická 354/107b
158 00 Praha 5
Czech Republic

Distributor:
BASF New Zealand Ltd.
5E City Works Depot
77 Cook Street
Auckland Central, Auckland 1010
New Zealand

Emergency contact
Telephone: +64 9 255-4300

Emergency telephone : National Poisons Centre: 0800 764 766
BASF Emergency Advice Number: 0800 944 955 (24 hour advice in an emergency only)
BASF Emergency Advice Number: +61 3 8855 6666 (If calling from outside New Zealand)

Recommended use of the chemical and restrictions on use

Recommended use : Spraying
Thinner
Spraying

Section 2: Hazard identification

GHS Classification

Flammable liquids : Category 3

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation : Category 2

Skin sensitization	:	Category 1
Reproductive toxicity	:	Category 2
Specific target organ toxicity - single exposure	:	Category 3 (Respiratory system, Central nervous system)
Specific target organ toxicity - repeated exposure	:	Category 2 (Kidney, Liver, Central nervous system, Auditory system)
Aspiration hazard	:	Category 1
Hazardous to the aquatic environment - chronic hazard	:	Category 3

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements :
H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs (Kidney, Liver, Central nervous system, Auditory system) through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification
If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Section 3: Composition/information on ingredients

Chemical nature : organic solvent

Components

Chemical name	Common Name/Synonyms	CAS-No.	Classification	Concentration (% w/w)
n-Butyl acetate	n-butyl acetate	123-86-4	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 50 -< 70
Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0)	Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0)	64742-95-6	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Respiratory system, Central nervous	>= 10 -< 20

			system), Category 3 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 2	
xylene	xylenes	1330-20-7	Flammable liquids, Category 3 Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2 Specific target organ toxicity - single exposure (Respiratory system), Category 3 Specific target organ toxicity - repeated exposure (Kidney, Liver, Central nervous system), Category 2 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 3	>= 10 -< 20
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-49-0	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Central	>= 2.5 -< 10

			nervous system), Category 3 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 3	
1-methoxy-2-propylacetate	2-methoxy-1-methylethyl acetate	108-65-6	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 1 -< 10
2-butoxyethyl acetate	2-butoxyethyl acetate	112-07-2	Flammable liquids, Category 4 Acute toxicity (Oral), Category 4 Acute toxicity (Dermal), Category 4	>= 1 -< 10
ethylbenzene	ethylbenzene	100-41-4	Flammable liquids, Category 2 Acute toxicity (Inhalation), Category 4 Specific target organ toxicity - repeated exposure (Auditory system), Category 2 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard,	>= 1 -< 2.5

			Category 3	
Hydrocarbons, by-products with terpene processing	Hydrocarbons, terpene processing by-products	68956-56-9	Flammable liquids, Category 3 Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2 Skin sensitization, Category 1 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 2	>= 1 -< 2.5
n-hexane	n-hexane	110-54-3	Flammable liquids, Category 2 Skin corrosion/irritation, Category 2 Reproductive toxicity, Category 2 Specific target organ toxicity - single exposure (Central nervous system), Category 3 Specific target organ toxicity - repeated exposure, Category 1 Aspiration hazard, Category 1 Hazardous to the	>= 0.1 -< 0.25

			aquatic environment - chronic hazard, Category 2	

Section 4: First-aid measures

General advice : In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product.
Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.
Never give anything by mouth to an unconscious person.
Move out of dangerous area.
Immediately remove contaminated clothing.
First aid personnel should pay attention to their own safety.
Keep patient warm and at rest.

If inhaled : If breathed in, move person into fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician or poison control center immediately.

In case of skin contact : Do NOT use solvents or thinners.

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

If symptoms persist, call a physician.

In case of eye contact : If easy to do, remove contact lens, if worn.

Call a physician immediately.

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye

		specialist.
If swallowed	:	Rinse mouth with water. Do not induce vomiting due to aspiration hazard. Keep at rest. If swallowed, call a poison control center or doctor immediately.
Most important symptoms and effects, both acute and delayed	:	May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia. Risk of product entering the lungs on vomiting after ingestion.
Notes to physician	:	No known specific antidote. Treat symptomatically.

Section 5: Fire-fighting measures

Suitable extinguishing media	:	Dry powder Carbon dioxide (CO2) Water spray Foam
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire fighting	:	Fire will produce dense black smoke containing hazardous combustion products (see section 10).

Advice for firefighters

Specific extinguishing methods	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cool containers/tanks with water spray.
Special protective equipment for fire-fighters	:	Appropriate breathing apparatus may be required.

Hazchem Code	:	3Y

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures	:	Avoid breathing vapours. For non-emergency personnel: Use personal protective equipment. Ensure adequate ventilation, especially in confined areas. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet.
Environmental precautions	:	If the product contaminates rivers and lakes or drains inform respective authorities. Avoid subsoil penetration. Do not allow uncontrolled discharge of product into the environment.
Methods and materials for containment and cleaning up	:	Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Ensure adequate ventilation.

Section 7: Handling and storage

Advice on protection against fire and explosion	:	Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapors are heavier than air and spread along floors. Vapor forms explosive mixtures with air.
Advice on safe handling	:	Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

		Do not breathe vapors or spray mist.
Hygiene measures	:	Remove contaminated clothing immediately and dispose of safely. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.
Further information on storage conditions	:	Keep away from heat. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Store protected against freezing. Keep in a dry, cool and well-ventilated place.
Materials to avoid	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Recommended storage temperature	:	5.00 - 35.00 °C
Packaging material	:	Suitable material: Carbon steel (Iron), tinned carbon steel (Tinplate)

Section 8: Exposure controls/personal protection

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
n-Butyl acetate	123-86-4	WES-STEL	200 ppm 950 mg/m3	NZ OEL
		WES-TWA	150 ppm 713 mg/m3	NZ OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0)	64742-95-6	WES-TWA	300 ppm 890 mg/m3	NZ OEL
		WES-STEL	500 ppm 1,480 mg/m3	NZ OEL
xylene	1330-20-7	WES-TWA	50 ppm 217 mg/m3	NZ OEL
	Further information: Ototoxin			
		TWA	20 ppm	ACGIH
2-butoxyethyl acetate	112-07-2	TWA	20 ppm	ACGIH
ethylbenzene	100-41-4	WES-TWA	20 ppm 88 mg/m3	NZ OEL
	Further information: Ototoxin, Skin absorption			
		WES-STEL	40 ppm	NZ OEL

			176 mg/m3	
	Further information: Ototoxin, Skin absorption			
		TWA	20 ppm	ACGIH
n-hexane	110-54-3	WES-TWA	20 ppm 72 mg/m3	NZ OEL
	Further information: Ototoxin, Exposure can also be estimated by biological monitoring			
		TWA	50 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
xylene	1330-20-7	Methylhippuric acid	Urine	End of shift	1.5 g/l	NZ BEI
		Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI
ethylbenzene	100-41-4	Sum of mandelic acid and phenylglyoxylic acids	Urine	End of exposure or end of shift	0.25 g/g creatinine	NZ BEI
		Sum of mandelic	Urine	End of shift (As	0.15 g/g creatinine	ACGIH BEI

		acid and phenyl glyoxylic acid		soon as possible after exposure ceases)		
n-hexane	110-54-3	2,5-hexanedione	Urine	End of shift	5 mg/l	NZ BEI
		2,5-Hexanedione	Urine	End of shift	0.5 mg/l	ACGIH BEI

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Suitable respiratory equipment:

half-mask with A2P2 class combination filter

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection

Remarks	:	Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. nitrile gloves - material thickness: 0,35 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Preventive skin protection Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least

protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Eye protection : Required when there is a risk of eye contact.

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Skin and body protection : Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

chemical-resistant disposable coveralls

Protective measures : Do not breathe vapour/spray.

Eye wash fountains and safety showers must be easily accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Section 9: Physical and chemical properties

Appearance : liquid

Color : colorless

Odor : hydrocarbon-like

pH : substance/mixture is non-polar/aprotic

Melting point/ range : not determined

Boiling point/boiling range	:	126.00 - 190.00 °C
Flash point	:	27 °C Method: ISO 3679
Evaporation rate	:	No data available
Flammability	:	Flammable liquid and vapour.
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	> 35.0 g/m3
Vapor pressure	:	5.0 hPa (20 °C) 48.0 hPa (50 °C)
Density	:	0.867 g/cm3 (20 °C)
Solubility(ies)		
Water solubility	:	not determined

Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	> 200 °C
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity		
Viscosity, kinematic	:	6.0 mm2/s (23 °C) not determined (40 °C)
Flow time	:	< 30 s (23 °C) Cross section: 3 mm Method: ISO 2431
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Self-heating substances	:	The substance or mixture is not classified as self heating.
Metal corrosion rate	:	Not corrosive to metals.
Particle characteristics		
Particle size	:	The substance / product is marketed or used in a non solid or granular form.

Section 10: Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	No decomposition if stored and applied as directed.

Possibility of hazardous reactions	:	Vapours may form ignitable mixture with air.
Conditions to avoid	:	Avoid direct sunlight. Heat, flames and sparks. Heat. Protect from frost.
Incompatible materials	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

Section 11: Toxicological information

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method

Components:

2-butoxyethyl acetate:

Acute oral toxicity	:	LD50 (Rat): 1,880 mg/kg
Acute dermal toxicity	:	LD50 (Rabbit): 1,500 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:

n-Butyl acetate:

Assessment	:	Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Assessment	:	Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Chronic toxicity

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT-single exposure

May cause respiratory irritation.
May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs (Kidney, Liver, Central nervous system, Auditory system) through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Section 12: Ecological information

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Components:

n-Butyl acetate:

Partition coefficient: n-octanol/water	:	Pow: 200 (25 °C) log Pow: 2.3 (25 °C) pH: 7 Method: OECD Test Guideline 117 GLP: yes

Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0):

Partition coefficient: n-	:	log Pow: 3.17

octanol/water		GLP: no

xylene:

Partition coefficient: n-octanol/water	:	log Pow: 3.12 - 3.20 (25 °C) GLP: no Remarks: Information taken from reference works and the literature.

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Partition coefficient: n-octanol/water	:	log Pow: > 4 log Pow: > 4

1-methoxy-2-propylacetate:

Partition coefficient: n-octanol/water	:	log Pow: 1.2 (20 °C) pH: 6.8 Method: OECD Test Guideline 117 GLP: yes

2-butoxyethyl acetate:

Partition coefficient: n-octanol/water	:	log Pow: 1.51 (25 °C) pH: 7 Method: OECD Test Guideline 107

GLP: no

ethylbenzene:

Partition coefficient: n-octanol/water	:	Pow: 4,170 (20 °C) log Pow: 3.6 (20 °C) pH: 7.8 GLP: yes

Hydrocarbons, by-products with terpene processing:

Partition coefficient: n-octanol/water	:	Pow: 31,770 (25 °C) log Pow: 4.5 (25 °C) Method: OECD Test Guideline 107

n-hexane:

Partition coefficient: n-octanol/water	:	log Pow: 4 (20 °C) pH: 7 Remarks: Information taken from reference works and the literature.

Mobility in soil

No data available

Other adverse effects

No data available

Section 13: Disposal considerations

Disposal methods

Waste from residues	:	Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.
Contaminated packaging	:	Packaging that is not properly emptied must be disposed of as the unused product.

Section 14: Transport information

International Regulations

UNRTDG

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
Environmentally hazardous	:	no

IATA-DGR

UN/ID No.	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	Flammable Liquids
Packing instruction (cargo	:	366

aircraft)

Packing instruction (passenger aircraft)	:	355

IMDG-Code

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
EmS Code	:	F-E, S-E
Marine pollutant	:	no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
Not applicable for product as supplied.

Domestic regulation

NZS 5433

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
Hazchem Code	:	3Y
Marine pollutant	:	no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

HSNO Approval Number
HSR002662 Surface Coatings and Colourants Flammable Group Standard

Tolerable Exposure Limits (TEL)
Not applicable

Environmental Exposure Limits (EEL)
Not applicable

HSW Controls
Certified handler certificate not required.
Tracking hazardous substance not required.
Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

Section 16: Other information

Revision Date	:	14.11.2025

Further information

Other information	:	For multi-pack systems observe material safety data sheets of all components. Restricted to professional users.
Date format	:	dd.mm.yyyy

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
NZ BEI	:	New Zealand. Biological Exposure Indices
NZ OEL	:	New Zealand. Workplace Exposure Standards for Atmospheric Contaminants

ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NZ OEL / WES-TWA	:	Workplace Exposure Standard - Time Weighted average
NZ OEL / WES-STEL	:	Workplace Exposure Standard - Short-Term Exposure Limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory

of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NZ / EN

SAFETY DATA SHEET

352-216 1L REDUCER SLOW

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2025
3.2	08.06.2025	000000000054770347	Date of first issue: 08.06.2025

Section 1: Identification

Product name : 352-216 1L REDUCER SLOW

Product code : 000000000054770347

Manufacturer or supplier's details

BASF Coatings and Chemetall New Zealand Limited
Level 1, 527A Rosebank Road, Avondale
Auckland 1026
New Zealand
Telephone: 008 837 464, +64 9 820 3888
Telefax number: +64 9 820 3979
E-mail address: nzadmin@basf.com

Emergency contact

Telephone: +64 9 255-4300
E-mail address: ProductSafety_EC_APAC@basf.com, nzadmin@basf.com

Emergency telephone : National Poisons Centre: 0800 764 766
BASF Emergency Advice Number: 0800 944 955 (24 hour advice in an emergency only)
BASF Emergency Advice Number: +61 3 8855 6666 (If calling from outside New Zealand)

Recommended use of the chemical and restrictions on use

Recommended use : Spraying
Thinner

Section 2: Hazard identification

GHS Classification

Flammable liquids : Category 3

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation	:	Category 2
Reproductive toxicity	:	Category 1
Specific target organ toxicity - single exposure	:	Category 3 (Central nervous system)
Specific target organ toxicity - repeated exposure	:	Category 2 (Kidney, Liver, Central nervous system, Auditory system)
Aspiration hazard	:	Category 1

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H360 May damage fertility or the unborn child.
H373 May cause damage to organs (Kidney, Liver, Central nervous system, Auditory system) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification
If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Section 3: Composition/information on ingredients

Chemical nature : organic solvent

Components

Chemical name	Common Name/Synonyms	CAS-No.	Classification	Concentration (% w/w)
1-methoxy-2-propylacetate	2-methoxy-1-methylethyl acetate	108-65-6	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 30 -< 50
n-Butyl acetate	n-butyl acetate	123-86-4	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 30 -< 50
xylene	xylenes	1330-20-7	Flammable liquids, Category 3	>= 10 -< 20

			Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2 Specific target organ toxicity - single exposure (Respiratory system), Category 3 Specific target organ toxicity - repeated exposure (Kidney, Liver, Central nervous system), Category 2 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 3	
ethylbenzene	ethylbenzene	100-41-4	Flammable liquids, Category 2 Acute toxicity (Inhalation), Category 4 Specific target organ toxicity - repeated exposure (Auditory system), Category 2 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard,	>= 2.5 -< 10

			Category 3	
2-butoxyethyl acetate	2-butoxyethyl acetate	112-07-2	Flammable liquids, Category 4 Acute toxicity (Oral), Category 4 Acute toxicity (Dermal), Category 4	>= 1 -< 10
2-methoxypropyl acetate	2-methoxypropyl acetate	70657-70-4	Flammable liquids, Category 3 Reproductive toxicity, Category 1 Specific target organ toxicity - single exposure (Respiratory system), Category 3	>= 0.1 -< 1

Section 4: First-aid measures

General advice : In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product.
Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.
Keep patient warm and at rest.
Never give anything by mouth to an unconscious person.
Move out of dangerous area.
Immediately remove contaminated clothing.
First aid personnel should pay attention to their own safety.

If inhaled	:	If breathed in, move person into fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician or poison control center immediately.
In case of skin contact	:	Do NOT use solvents or thinners. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
In case of eye contact	:	Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Call a physician immediately. If easy to do, remove contact lens, if worn.
If swallowed	:	Rinse mouth with water. Do not induce vomiting due to aspiration hazard. Keep at rest. If swallowed, call a poison control center or doctor immediately.
Most important symptoms and effects, both acute and delayed	:	May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated

exposure.

Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.

Risk of product entering the lungs on vomiting after ingestion.

Notes to physician : Treat symptomatically.
No known specific antidote.

Section 5: Fire-fighting measures

Suitable extinguishing media : Water spray jet

Dry powder

Alcohol-resistant foam

Carbon dioxide (CO_2)

Unsuitable extinguishing : High volume water jet

media

Specific hazards during fire fighting	:	Fire will produce dense black smoke containing hazardous combustion products (see section 10).

Advice for firefighters

Specific extinguishing methods	:	Cool containers/tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Special protective equipment for fire-fighters	:	Appropriate breathing apparatus may be required.
Hazchem Code	:	3Y

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures	:	Avoid breathing vapours. For non-emergency personnel: Use personal protective equipment. Ensure adequate ventilation, especially in confined areas. Keep away from sources of ignition.

For emergency responders:

Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.

Avoid subsoil penetration.

Do not allow uncontrolled discharge of product into the environment.

Methods and materials for containment and cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

Ensure adequate ventilation.

Section 7: Handling and storage

Advice on protection against fire and explosion : Avoid all sources of ignition: heat, sparks, open flame.

Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear.

The relevant fire protection measures should be noted.

Use explosion-proof equipment.

Vapors are heavier than air and may spread along floors.

Vapors may form explosive mixtures with air.

Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).

Do not return residues to the storage containers.

Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

The workplace should be equipped with an emergency shower and eye-rinsing facility.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Do not breathe vapors or spray mist.

Hygiene measures : Remove contaminated clothing immediately and dispose of safely.

Wash hands before breaks and at the end of workday.

Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions	:	Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Keep in a dry, cool and well-ventilated place.
Materials to avoid	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Packaging material	:	Suitable material: Carbon steel (Iron), tinned carbon steel (Tinplate)

Section 8: Exposure controls/personal protection

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
n-Butyl acetate	123-86-4	WES-STEL	200 ppm 950 mg/m3	NZ OEL
		WES-TWA	150 ppm 713 mg/m3	NZ OEL
		TWA	50 ppm	ACGIH

		STEL	150 ppm	ACGIH
xylene	1330-20-7	WES-TWA	50 ppm 217 mg/m3	NZ OEL
	Further information: Ototoxin			
		TWA	20 ppm	ACGIH
ethylbenzene	100-41-4	WES-TWA	20 ppm 88 mg/m3	NZ OEL
	Further information: Ototoxin, Skin absorption			
		WES-STEL	40 ppm 176 mg/m3	NZ OEL
	Further information: Ototoxin, Skin absorption			
		TWA	20 ppm	ACGIH
2-butoxyethyl acetate	112-07-2	TWA	20 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
xylene	1330-20-7	Methylhippuric acid	Urine	End of shift	1.5 g/l	NZ BEI
		Methylhippuric acids	Urine	End of shift (As soon as possible after exposure	1.5 g/g creatinine	ACGIH BEI

				ceases)		
ethylbenzene	100-41-4	Sum of mandelic acid and phenylglyoxylic acids	Urine	End of exposure or end of shift	0.25 g/g creatinine	NZ BEI
		Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Suitable respiratory equipment:

half-mask with A1P2 class combination filter

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection

Remarks	:	Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. butyl rubber gloves - material thickness: 0.5 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Preventive skin protection Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Eye protection : Required when there is a risk of eye contact.

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Skin and body protection : Anti-static protective clothing

Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

Protective measures : Do not breathe vapour/spray.

Eye wash fountains and safety showers must be easily accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Section 9: Physical and chemical properties

Appearance : liquid

Color : colorless

Odor	:	of acetate
pH	:	substance/mixture is non-polar/aprotic
Melting point/ range	:	not determined
Boiling point/boiling range	:	124 - 195 °C Method: calculated
Flash point	:	31 °C Method: ISO 3679
Flammability	:	Flammable liquid and vapour.
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	> 35 g/m3
Vapor pressure	:	not determined (20 °C)

		not determined (50 °C)
Density	:	0.914 g/cm3 (20 °C)
Solubility(ies)		
Water solubility	:	not determined
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	> 200 °C
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity		
Viscosity, kinematic	:	6.0 mm2/s (23 °C)
		not determined (40 °C)
Flow time	:	< 30 s (23 °C) Cross section: 3 mm Method: ISO 2431
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Self-heating substances	:	The substance or mixture is not classified as self heating.

Metal corrosion rate	:	Not corrosive to metals.
Particle characteristics		
Particle size	:	The substance / product is marketed or used in a non solid or granular form.

Section 10: Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	Vapours may form ignitable mixture with air.
Conditions to avoid	:	Avoid direct sunlight. Heat, flames and sparks.
Incompatible materials	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

Section 11: Toxicological information

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h

Test atmosphere: vapor

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Components:

2-butoxyethyl acetate:

Acute oral toxicity : LD50 (Rat): 1,880 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 1,500 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:

n-Butyl acetate:

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

Based on available data, the classification criteria are not met.

Respiratory sensitization
Based on available data, the classification criteria are not met.

Chronic toxicity

Germ cell mutagenicity
Based on available data, the classification criteria are not met.

Carcinogenicity
Based on available data, the classification criteria are not met.

Reproductive toxicity
May damage fertility or the unborn child.

STOT-single exposure
May cause drowsiness or dizziness.

STOT-repeated exposure
May cause damage to organs (Kidney, Liver, Central nervous system, Auditory system) through prolonged or repeated exposure.

Aspiration toxicity
May be fatal if swallowed and enters airways.

Section 12: Ecological information

Ecotoxicity
No data available

Persistence and degradability
No data available

Bioaccumulative potential

Components:

1-methoxy-2-propylacetate:

Partition coefficient: n-octanol/water	:	log Pow: 1.2 (20 °C) pH: 6.8 Method: OECD Test Guideline 117

GLP: yes

n-Butyl acetate:

Partition coefficient: n-octanol/water : Pow: 200 (25 °C)

log Pow: 2.3 (25 °C)

pH: 7

Method: OECD Test Guideline 117

GLP: yes

xylene:

Partition coefficient: n-octanol/water : log Pow: 3.12 - 3.20 (25 °C)

GLP: no

Remarks: Information taken from reference works and the literature.

ethylbenzene:

Partition coefficient: n-octanol/water : Pow: 4,170 (20 °C)

log Pow: 3.6 (20 °C)

pH: 7.8

GLP: yes

2-butoxyethyl acetate:

Partition coefficient: n-octanol/water	:	log Pow: 1.51 (25 °C) pH: 7 Method: OECD Test Guideline 107 GLP: no

Mobility in soil
No data available

Other adverse effects
No data available

Section 13: Disposal considerations

Disposal methods

Waste from residues	:	Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.
Contaminated packaging	:	Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC Packaging that is not properly emptied must be disposed of as the unused product.

Section 14: Transport information

International Regulations

UNRTDG

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3

Packing group	:	III
Labels	:	3
Environmentally hazardous	:	no

IATA-DGR

UN/ID No.	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	Flammable Liquids
Packing instruction (cargo aircraft)	:	366
Packing instruction (passenger aircraft)	:	355

IMDG-Code

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
EmS Code	:	F-E, S-E
Marine pollutant	:	no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
Not applicable for product as supplied.

Domestic regulation

NZS 5433

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
Hazchem Code	:	3Y
Marine pollutant	:	no

Special precautions for user
The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

ERG Code : 128

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

HSNO Approval Number
HSR002662 Surface Coatings and Colourants Flammable Group Standard

Tolerable Exposure Limits (TEL)
Not applicable

Environmental Exposure Limits (EEL)
Not applicable

HSW Controls
Certified handler certificate not required.
Tracking hazardous substance not required.
Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

Section 16: Other information

Revision Date	:	08.06.2025

Further information

Other information	:	For multi-pack systems observe material safety data sheets of all components. Restricted to professional users.
Date format	:	dd.mm.yyyy

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
NZ BEI	:	New Zealand. Biological Exposure Indices
NZ OEL	:	New Zealand. Workplace Exposure Standards for Atmospheric Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit

NZ OEL / WES-TWA	:	Workplace Exposure Standard - Time Weighted average
NZ OEL / WES-STEL	:	Workplace Exposure Standard - Short-Term Exposure Limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NZ / EN

352-216 5L BLEND-IN SLOW THINNER G2

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2025
3.2	08.06.2025	000000000050411534	Date of first issue: 08.06.2025

Section 1: Identification

Product name : 352-216 5L BLEND-IN SLOW THINNER G2

Product code : 000000000050411534

Manufacturer or supplier's details

BASF Coatings and Chemetall New Zealand Limited
Level 1, 527A Rosebank Road, Avondale
Auckland 1026
New Zealand
Telephone: 008 837 464, +64 9 820 3888
Telefax number: +64 9 820 3979
E-mail address: nzadmin@basf.com

Emergency contact

Telephone: +64 9 255-4300
E-mail address: ProductSafety_EC_APAC@basf.com, nzadmin@basf.com

Emergency telephone : National Poisons Centre: 0800 764 766
BASF Emergency Advice Number: 0800 944 955 (24 hour advice in an emergency only)
BASF Emergency Advice Number: +61 3 8855 6666 (If calling from outside New Zealand)

Recommended use of the chemical and restrictions on use

Recommended use : Spraying
Thinner

Section 2: Hazard identification

GHS Classification

Flammable liquids : Category 3

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation	:	Category 2
Reproductive toxicity	:	Category 1
Specific target organ toxicity - single exposure	:	Category 3 (Central nervous system)
Specific target organ toxicity - repeated exposure	:	Category 2 (Kidney, Liver, Central nervous system, Auditory system)
Aspiration hazard	:	Category 1

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H360 May damage fertility or the unborn child.
H373 May cause damage to organs (Kidney, Liver, Central nervous system, Auditory system) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification
If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Section 3: Composition/information on ingredients

Chemical nature : organic solvent

Components

Chemical name	Common Name/Synonyms	CAS-No.	Classification	Concentration (% w/w)
1-methoxy-2-propylacetate	2-methoxy-1-methylethyl acetate	108-65-6	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 30 -< 50
n-Butyl acetate	n-butyl acetate	123-86-4	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 30 -< 50
xylene	xylenes	1330-20-7	Flammable liquids, Category 3	>= 10 -< 20

			Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2 Specific target organ toxicity - single exposure (Respiratory system), Category 3 Specific target organ toxicity - repeated exposure (Kidney, Liver, Central nervous system), Category 2 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 3	
ethylbenzene	ethylbenzene	100-41-4	Flammable liquids, Category 2 Acute toxicity (Inhalation), Category 4 Specific target organ toxicity - repeated exposure (Auditory system), Category 2 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard,	>= 2.5 -< 10

			Category 3	
2-butoxyethyl acetate	2-butoxyethyl acetate	112-07-2	Flammable liquids, Category 4 Acute toxicity (Oral), Category 4 Acute toxicity (Dermal), Category 4	>= 1 -< 10
2-methoxypropyl acetate	2-methoxypropyl acetate	70657-70-4	Flammable liquids, Category 3 Reproductive toxicity, Category 1 Specific target organ toxicity - single exposure (Respiratory system), Category 3	>= 0.1 -< 1

Section 4: First-aid measures

General advice : In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product.
Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.
Keep patient warm and at rest.
Never give anything by mouth to an unconscious person.
Move out of dangerous area.
Immediately remove contaminated clothing.
First aid personnel should pay attention to their own safety.

If inhaled	:	If breathed in, move person into fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician or poison control center immediately.
In case of skin contact	:	Do NOT use solvents or thinners. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
In case of eye contact	:	Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Call a physician immediately. If easy to do, remove contact lens, if worn.
If swallowed	:	Rinse mouth with water. Do not induce vomiting due to aspiration hazard. Keep at rest. If swallowed, call a poison control center or doctor immediately.
Most important symptoms and effects, both acute and delayed	:	May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated

exposure.

Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.

Risk of product entering the lungs on vomiting after ingestion.

Notes to physician : Treat symptomatically.
No known specific antidote.

Section 5: Fire-fighting measures

Suitable extinguishing media : Water spray jet

Dry powder

Alcohol-resistant foam

Carbon dioxide (CO_2)

Unsuitable extinguishing : High volume water jet

media

Specific hazards during fire fighting	:	Fire will produce dense black smoke containing hazardous combustion products (see section 10).

Advice for firefighters

Specific extinguishing methods	:	Cool containers/tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Special protective equipment for fire-fighters	:	Appropriate breathing apparatus may be required.
Hazchem Code	:	3Y

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures	:	Avoid breathing vapours. For non-emergency personnel: Use personal protective equipment. Ensure adequate ventilation, especially in confined areas. Keep away from sources of ignition.

For emergency responders:

Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.

Avoid subsoil penetration.

Do not allow uncontrolled discharge of product into the environment.

Methods and materials for containment and cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

Ensure adequate ventilation.

Section 7: Handling and storage

Advice on protection against fire and explosion : Avoid all sources of ignition: heat, sparks, open flame.

Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear.

The relevant fire protection measures should be noted.

Use explosion-proof equipment.

Vapors are heavier than air and may spread along floors.

Vapors may form explosive mixtures with air.

Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).

Do not return residues to the storage containers.

Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

The workplace should be equipped with an emergency shower and eye-rinsing facility.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Do not breathe vapors or spray mist.

Hygiene measures : Remove contaminated clothing immediately and dispose of safely.

Wash hands before breaks and at the end of workday.

Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions	:	Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Keep in a dry, cool and well-ventilated place.
Materials to avoid	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Packaging material	:	Suitable material: Carbon steel (Iron), tinned carbon steel (Tinplate)

Section 8: Exposure controls/personal protection

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
n-Butyl acetate	123-86-4	WES-STEL	200 ppm 950 mg/m3	NZ OEL
		WES-TWA	150 ppm 713 mg/m3	NZ OEL
		TWA	50 ppm	ACGIH

		STEL	150 ppm	ACGIH
xylene	1330-20-7	WES-TWA	50 ppm 217 mg/m3	NZ OEL
	Further information: Ototoxin			
		TWA	20 ppm	ACGIH
ethylbenzene	100-41-4	WES-TWA	20 ppm 88 mg/m3	NZ OEL
	Further information: Ototoxin, Skin absorption			
		WES-STEL	40 ppm 176 mg/m3	NZ OEL
	Further information: Ototoxin, Skin absorption			
		TWA	20 ppm	ACGIH
2-butoxyethyl acetate	112-07-2	TWA	20 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
xylene	1330-20-7	Methylhippuric acid	Urine	End of shift	1.5 g/l	NZ BEI
		Methylhippuric acids	Urine	End of shift (As soon as possible after exposure	1.5 g/g creatinine	ACGIH BEI

				ceases)		
ethylbenzene	100-41-4	Sum of mandelic acid and phenylglyoxylic acids	Urine	End of exposure or end of shift	0.25 g/g creatinine	NZ BEI
		Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Suitable respiratory equipment:

half-mask with A1P2 class combination filter

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection

Remarks	:	Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. butyl rubber gloves - material thickness: 0.5 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Preventive skin protection Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Eye protection : Required when there is a risk of eye contact.

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Skin and body protection : Anti-static protective clothing

Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

Protective measures : Do not breathe vapour/spray.

Eye wash fountains and safety showers must be easily accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Section 9: Physical and chemical properties

Appearance : liquid

Color : colorless

Odor	:	of acetate
pH	:	substance/mixture is non-polar/aprotic
Melting point/ range	:	not determined
Boiling point/boiling range	:	124 - 195 °C Method: calculated
Flash point	:	31 °C Method: ISO 3679
Flammability	:	Flammable liquid and vapour.
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	> 35 g/m3
Vapor pressure	:	not determined (20 °C)

		not determined (50 °C)
Density	:	0.914 g/cm3 (20 °C)
Solubility(ies)		
Water solubility	:	not determined
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	> 200 °C
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity		
Viscosity, kinematic	:	6.0 mm2/s (23 °C)
		not determined (40 °C)
Flow time	:	< 30 s (23 °C) Cross section: 3 mm Method: ISO 2431
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Self-heating substances	:	The substance or mixture is not classified as self heating.

Metal corrosion rate	:	Not corrosive to metals.
Particle characteristics		
Particle size	:	The substance / product is marketed or used in a non solid or granular form.

Section 10: Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	Vapours may form ignitable mixture with air.
Conditions to avoid	:	Avoid direct sunlight. Heat, flames and sparks.
Incompatible materials	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

Section 11: Toxicological information

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h

Test atmosphere: vapor

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Components:

2-butoxyethyl acetate:

Acute oral toxicity : LD50 (Rat): 1,880 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 1,500 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:

n-Butyl acetate:

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

Based on available data, the classification criteria are not met.

Respiratory sensitization
Based on available data, the classification criteria are not met.

Chronic toxicity

Germ cell mutagenicity
Based on available data, the classification criteria are not met.

Carcinogenicity
Based on available data, the classification criteria are not met.

Reproductive toxicity
May damage fertility or the unborn child.

STOT-single exposure
May cause drowsiness or dizziness.

STOT-repeated exposure
May cause damage to organs (Kidney, Liver, Central nervous system, Auditory system) through prolonged or repeated exposure.

Aspiration toxicity
May be fatal if swallowed and enters airways.

Section 12: Ecological information

Ecotoxicity
No data available

Persistence and degradability
No data available

Bioaccumulative potential

Components:

1-methoxy-2-propylacetate:

Partition coefficient: n-octanol/water	:	log Pow: 1.2 (20 °C) pH: 6.8 Method: OECD Test Guideline 117

GLP: yes

n-Butyl acetate:

Partition coefficient: n-octanol/water : Pow: 200 (25 °C)

log Pow: 2.3 (25 °C)

pH: 7

Method: OECD Test Guideline 117

GLP: yes

xylene:

Partition coefficient: n-octanol/water : log Pow: 3.12 - 3.20 (25 °C)

GLP: no

Remarks: Information taken from reference works and the literature.

ethylbenzene:

Partition coefficient: n-octanol/water : Pow: 4,170 (20 °C)

log Pow: 3.6 (20 °C)

pH: 7.8

GLP: yes

2-butoxyethyl acetate:

Partition coefficient: n-octanol/water	:	log Pow: 1.51 (25 °C) pH: 7 Method: OECD Test Guideline 107 GLP: no

Mobility in soil
No data available

Other adverse effects
No data available

Section 13: Disposal considerations

Disposal methods

Waste from residues	:	Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.
Contaminated packaging	:	Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC Packaging that is not properly emptied must be disposed of as the unused product.

Section 14: Transport information

International Regulations

UNRTDG

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3

Packing group	:	III
Labels	:	3
Environmentally hazardous	:	no

IATA-DGR

UN/ID No.	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	Flammable Liquids
Packing instruction (cargo aircraft)	:	366
Packing instruction (passenger aircraft)	:	355

IMDG-Code

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
EmS Code	:	F-E, S-E
Marine pollutant	:	no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
Not applicable for product as supplied.

Domestic regulation

NZS 5433

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
Hazchem Code	:	3Y
Marine pollutant	:	no

Special precautions for user
The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

ERG Code : 128

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

HSNO Approval Number
HSR002662 Surface Coatings and Colourants Flammable Group Standard

Tolerable Exposure Limits (TEL)
Not applicable

Environmental Exposure Limits (EEL)
Not applicable

HSW Controls
Certified handler certificate not required.
Tracking hazardous substance not required.
Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

Section 16: Other information

Revision Date	:	08.06.2025

Further information

Other information	:	For multi-pack systems observe material safety data sheets of all components. Restricted to professional users.
Date format	:	dd.mm.yyyy

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
NZ BEI	:	New Zealand. Biological Exposure Indices
NZ OEL	:	New Zealand. Workplace Exposure Standards for Atmospheric Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit

NZ OEL / WES-TWA	:	Workplace Exposure Standard - Time Weighted average
NZ OEL / WES-STEL	:	Workplace Exposure Standard - Short-Term Exposure Limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NZ / EN

352-216 REDUCER SLOW

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2025
3.2	08.06.2025	000000000050273452	Date of first issue: 08.06.2025

Section 1: Identification

Product name : 352-216 REDUCER SLOW

Product code : 000000000050273452

Manufacturer or supplier's details

BASF Coatings and Chemetall New Zealand Limited
Level 1, 527A Rosebank Road, Avondale
Auckland 1026
New Zealand
Telephone: 008 837 464, +64 9 820 3888
Telefax number: +64 9 820 3979
E-mail address: nzadmin@basf.com

Emergency contact

Telephone: +64 9 255-4300
E-mail address: ProductSafety_EC_APAC@basf.com, nzadmin@basf.com

Emergency telephone : National Poisons Centre: 0800 764 766
BASF Emergency Advice Number: 0800 944 955 (24 hour advice in an emergency only)
BASF Emergency Advice Number: +61 3 8855 6666 (If calling from outside New Zealand)

Recommended use of the chemical and restrictions on use

Recommended use : Spraying
Thinner

Section 2: Hazard identification

GHS Classification

Flammable liquids : Category 3

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation	:	Category 2
Reproductive toxicity	:	Category 1
Specific target organ toxicity - single exposure	:	Category 3 (Central nervous system)
Specific target organ toxicity - repeated exposure	:	Category 2 (Kidney, Liver, Central nervous system, Auditory system)
Aspiration hazard	:	Category 1

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements :
H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H360 May damage fertility or the unborn child.
H373 May cause damage to organs (Kidney, Liver, Central nervous system, Auditory system) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification
If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Section 3: Composition/information on ingredients

Chemical nature : organic solvent

Components

Chemical name	Common Name/Synonyms	CAS-No.	Classification	Concentration (% w/w)
1-methoxy-2-propylacetate	2-methoxy-1-methylethyl acetate	108-65-6	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 30 -< 50
n-Butyl acetate	n-butyl acetate	123-86-4	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 30 -< 50
xylene	xylenes	1330-20-7	Flammable liquids, Category 3 Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2	>= 10 -< 20

			Specific target organ toxicity - single exposure (Respiratory system), Category 3 Specific target organ toxicity - repeated exposure (Kidney, Liver, Central nervous system), Category 2 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 3	
ethylbenzene	ethylbenzene	100-41-4	Flammable liquids, Category 2 Acute toxicity (Inhalation), Category 4 Specific target organ toxicity - repeated exposure (Auditory system), Category 2 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 3	>= 2.5 -< 10
2-butoxyethyl acetate	2-butoxyethyl acetate	112-07-2	Flammable liquids, Category 4 Acute toxicity (Oral), Category 4 Acute toxicity	>= 1 -< 10

			(Dermal), Category 4	
2-methoxypropyl acetate	2-methoxypropyl acetate	70657-70-4	Flammable liquids, Category 3 Reproductive toxicity, Category 1 Specific target organ toxicity - single exposure (Respiratory system), Category 3	>= 0.1 -< 1

Section 4: First-aid measures

General advice : In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product.
Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.
Keep patient warm and at rest.
Never give anything by mouth to an unconscious person.
Move out of dangerous area.
Immediately remove contaminated clothing.
First aid personnel should pay attention to their own safety.

If inhaled : If breathed in, move person into fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician or poison control center immediately.

In case of skin contact : Do NOT use solvents or thinners.

		Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
In case of eye contact	:	Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Call a physician immediately. If easy to do, remove contact lens, if worn.
If swallowed	:	Rinse mouth with water. Do not induce vomiting due to aspiration hazard. Keep at rest. If swallowed, call a poison control center or doctor immediately.
Most important symptoms and effects, both acute and delayed	:	May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.

Risk of product entering the lungs on vomiting after ingestion.

Notes to physician : Treat symptomatically.
No known specific antidote.

Section 5: Fire-fighting measures

Suitable extinguishing media : Water spray jet

Dry powder

Alcohol-resistant foam

Carbon dioxide (CO_2)

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire fighting : Fire will produce dense black smoke containing hazardous combustion products (see section 10).

Advice for firefighters

Specific extinguishing : Cool containers/tanks with water spray.

methods		Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Special protective equipment for fire-fighters	:	Appropriate breathing apparatus may be required.
Hazchem Code	:	3Y

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures	:	Avoid breathing vapours. For non-emergency personnel: Use personal protective equipment. Ensure adequate ventilation, especially in confined areas. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet.
Environmental precautions	:	If the product contaminates rivers and lakes or drains inform respective authorities. Avoid subsoil penetration. Do not allow uncontrolled discharge of product into the

environment.

Methods and materials for containment and cleaning up	:	Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Ensure adequate ventilation.

Section 7: Handling and storage

Advice on protection against fire and explosion	:	Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. The relevant fire protection measures should be noted. Use explosion-proof equipment. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.
Advice on safe handling	:	Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

The workplace should be equipped with an emergency shower and eye-rinsing facility.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Do not breathe vapors or spray mist.

Hygiene measures : Remove contaminated clothing immediately and dispose of safely.

Wash hands before breaks and at the end of workday.

Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions : Avoid direct sunlight.

Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel.

Always keep in containers of same material as the original one.

Observe label precautions.

Keep in a dry, cool and well-ventilated place.

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and

strongly acid materials in order to avoid exothermic reactions.

Packaging material : Suitable material: Carbon steel (Iron), tinned carbon steel (Tinplate)

Section 8: Exposure controls/personal protection

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
n-Butyl acetate	123-86-4	WES-STEL	200 ppm 950 mg/m3	NZ OEL
		WES-TWA	150 ppm 713 mg/m3	NZ OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
xylene	1330-20-7	WES-TWA	50 ppm 217 mg/m3	NZ OEL
	Further information: Ototoxin			
		TWA	20 ppm	ACGIH
ethylbenzene	100-41-4	WES-TWA	20 ppm 88 mg/m3	NZ OEL
	Further information: Ototoxin, Skin absorption			
		WES-STEL	40 ppm	NZ OEL

			176 mg/m3	
	Further information: Ototoxin, Skin absorption			
		TWA	20 ppm	ACGIH
2-butoxyethyl acetate	112-07-2	TWA	20 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
xylene	1330-20-7	Methylhippuric acid	Urine	End of shift	1.5 g/l	NZ BEI
		Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI
ethylbenzene	100-41-4	Sum of mandelic acid and phenylglyoxylic acids	Urine	End of exposure or end of shift	0.25 g/g creatinine	NZ BEI
		Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Suitable respiratory equipment:

half-mask with A1P2 class combination filter

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection

Remarks : Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g.

butyl rubber gloves - material thickness: 0.5 mm

Further information on penetration time is available from the

manufacturer of the glove.

Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.

The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Request information on glove permeation properties from the glove supplier.

Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Preventive skin protection

Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Eye protection : Required when there is a risk of eye contact.

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Skin and body protection : Anti-static protective clothing

Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

Protective measures : Do not breathe vapour/spray.

Eye wash fountains and safety showers must be easily

accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Section 9: Physical and chemical properties

Appearance	:	liquid
Color	:	colorless
Odor	:	of acetate
pH	:	substance/mixture is non-polar/aprotic
Melting point/ range	:	not determined
Boiling point/boiling range	:	124 - 195 °C Method: calculated
Flash point	:	31 °C Method: ISO 3679

Flammability	:	Flammable liquid and vapour.
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	> 35 g/m3
Vapor pressure	:	not determined (20 °C) not determined (50 °C)
Density	:	0.914 g/cm3 (20 °C)
Solubility(ies) Water solubility	:	not determined
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	> 200 °C
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity		

Viscosity, kinematic	:	6.0 mm2/s (23 °C)
		not determined (40 °C)
Flow time	:	< 30 s (23 °C) Cross section: 3 mm Method: ISO 2431
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Self-heating substances	:	The substance or mixture is not classified as self heating.
Metal corrosion rate	:	Not corrosive to metals.
Particle characteristics		
Particle size	:	The substance / product is marketed or used in a non solid or granular form.

Section 10: Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	Vapours may form ignitable mixture with air.
Conditions to avoid	:	Avoid direct sunlight.
		Heat, flames and sparks.
Incompatible materials	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Hazardous decomposition	:	No decomposition if stored and applied as directed.

products

Section 11: Toxicological information

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method

Components:

2-butoxyethyl acetate:

Acute oral toxicity	:	LD50 (Rat): 1,880 mg/kg
Acute dermal toxicity	:	LD50 (Rabbit): 1,500 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:

n-Butyl acetate:

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

Based on available data, the classification criteria are not met.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Chronic toxicity

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

May damage fertility or the unborn child.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs (Kidney, Liver, Central nervous system, Auditory system) through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Section 12: Ecological information

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Components:

1-methoxy-2-propylacetate:

Partition coefficient: n-octanol/water	:	log Pow: 1.2 (20 °C) pH: 6.8 Method: OECD Test Guideline 117 GLP: yes

n-Butyl acetate:

Partition coefficient: n-octanol/water	:	Pow: 200 (25 °C) log Pow: 2.3 (25 °C) pH: 7 Method: OECD Test Guideline 117 GLP: yes

xylene:

Partition coefficient: n-octanol/water	:	log Pow: 3.12 - 3.20 (25 °C) GLP: no Remarks: Information taken from reference works and the literature.

ethylbenzene:

Partition coefficient: n-octanol/water	:	Pow: 4,170 (20 °C) log Pow: 3.6 (20 °C) pH: 7.8 GLP: yes

2-butoxyethyl acetate:

Partition coefficient: n-octanol/water	:	log Pow: 1.51 (25 °C) pH: 7 Method: OECD Test Guideline 107 GLP: no

Mobility in soil

No data available

Other adverse effects

No data available

Section 13: Disposal considerations

Disposal methods

Waste from residues	:	Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.
Contaminated packaging	:	Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC Packaging that is not properly emptied must be disposed of as the unused product.

Section 14: Transport information

International Regulations

UNRTDG

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
Environmentally hazardous	:	no

IATA-DGR

UN/ID No.	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	Flammable Liquids
Packing instruction (cargo aircraft)	:	366
Packing instruction (passenger aircraft)	:	355

IMDG-Code

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3

Packing group	:	III
Labels	:	3
EmS Code	:	F-E, S-E
Marine pollutant	:	no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

NZS 5433

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
Hazchem Code	:	3Y
Marine pollutant	:	no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

ERG Code	:	128

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

HSNO Approval Number
HSR002662 Surface Coatings and Colourants Flammable Group Standard

Tolerable Exposure Limits (TEL)
Not applicable

Environmental Exposure Limits (EEL)
Not applicable

HSW Controls
Certified handler certificate not required.
Tracking hazardous substance not required.
Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

Section 16: Other information

Revision Date	:	08.06.2025

Further information

Other information	:	For multi-pack systems observe material safety data sheets of all components. Restricted to professional users.
Date format	:	dd.mm.yyyy

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
NZ BEI	:	New Zealand. Biological Exposure Indices
NZ OEL	:	New Zealand. Workplace Exposure Standards for Atmospheric Contaminants

ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NZ OEL / WES-TWA	:	Workplace Exposure Standard - Time Weighted average
NZ OEL / WES-STEL	:	Workplace Exposure Standard - Short-Term Exposure Limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a

guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NZ / EN

352-230 Activator 1L G2

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2025
3.1	08.06.2025	000000000050411423	Date of first issue: 08.06.2025

Section 1: Identification

Product name : 352-230 Activator 1L G2

Product code : 000000000050411423

Manufacturer or supplier's details

BASF Coatings and Chemetall New Zealand Limited
Level 1, 527A Rosebank Road, Avondale
Auckland 1026
New Zealand
Telephone: 008 837 464, +64 9 820 3888
Telefax number: +64 9 820 3979
E-mail address: nzadmin@basf.com

Emergency contact

Telephone: +64 9 255-4300
E-mail address: ProductSafety_EC_APAC@basf.com, nzadmin@basf.com

Emergency telephone : National Poisons Centre: 0800 764 766
BASF Emergency Advice Number: 0800 944 955 (24 hour advice in an emergency only)
BASF Emergency Advice Number: +61 3 8855 6666 (If calling from outside New Zealand)

Recommended use of the chemical and restrictions on use

Recommended use : Spraying
hardener

Section 2: Hazard identification

GHS Classification

Flammable liquids : Category 3

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation	:	Category 1
Reproductive toxicity	:	Category 2
Specific target organ toxicity - single exposure	:	Category 3 (Central nervous system)

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements :
H226 Flammable liquid and vapor.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.

Precautionary Statements :
Prevention:
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection/ hearing protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Section 3: Composition/information on ingredients

Chemical nature : organic solvent
inorganic acids

Components

Chemical name	Common Name/Synonyms	CAS-No.	Classification	Concentration (% w/w)
propylene glycol monoethyl ether	1-ethoxypropan-2-ol	1569-02-4	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 25 -< 50
propan-2-ol	propan-2-ol	67-63-0	Flammable liquids, Category 2 Serious eye damage/eye irritation, Category 2 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 20 -< 25
5-methylhexan-2-one	5-methylhexan-2-one	110-12-3	Flammable liquids, Category 3 Acute toxicity (Inhalation), Category 4 Reproductive toxicity, Category 2	>= 15 -< 20
isobutyl alcohol	2-methylpropan-1-ol	78-83-1	Flammable liquids, Category 3 Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 1 Specific target organ	>= 15 -< 20

			toxicity - single exposure (Respiratory system, Central nervous system), Category 3	
phosphoric acid	orthophosphoric acid (Solution)	7664-38-2	Corrosive to Metals, Category 1 Acute toxicity (Oral), Category 4 Skin corrosion/irritation, Category 1B Serious eye damage/eye irritation, Category 1	>= 1 -< 2

Section 4: First-aid measures

General advice : Never give anything by mouth to an unconscious person.
Move out of dangerous area.
In all cases of doubt, or when symptoms persist, seek medical attention.
Immediately remove contaminated clothing.
If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).
First aid personnel should pay attention to their own safety.

If inhaled : If breathed in, move person into fresh air.

If breathing is irregular or stopped, administer artificial respiration.

If symptoms persist, call a physician.

In case of skin contact : Do NOT use solvents or thinners.

		Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
In case of eye contact	:	If easy to do, remove contact lens, if worn. Call a physician immediately. Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
If swallowed	:	Rinse mouth with water. Do not induce vomiting due to aspiration hazard. Keep at rest. If swallowed, call a poison control center or doctor immediately.
Most important symptoms and effects, both acute and delayed	:	Causes skin irritation. Causes serious eye damage. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.
Notes to physician	:	Treat symptomatically. No known specific antidote.

Section 5: Fire-fighting measures

Suitable extinguishing media	:	Water spray jet

Dry powder

Alcohol-resistant foam

Carbon dioxide (CO2)

Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire fighting	:	Fire will produce dense black smoke containing hazardous combustion products (see section 10).

Advice for firefighters

Specific extinguishing methods	:	Cool containers/tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Special protective equipment	:	Appropriate breathing apparatus may be required.

for fire-fighters

Hazchem Code : 3Y

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures : Avoid breathing vapours.

For non-emergency personnel:

Use personal protective equipment.

Ensure adequate ventilation, especially in confined areas.

Keep away from sources of ignition.

For emergency responders:

Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.

Avoid subsoil penetration.

Do not allow uncontrolled discharge of product into the environment.

Methods and materials for containment and cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local /

national regulations (see section 13).

Ensure adequate ventilation.

Section 7: Handling and storage

Advice on protection against fire and explosion : Avoid all sources of ignition: heat, sparks, open flame.

Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear.

The relevant fire protection measures should be noted.

Use explosion-proof equipment.

Vapors are heavier than air and may spread along floors.

Vapors may form explosive mixtures with air.

Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).

Do not return residues to the storage containers.

Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

		The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Do not breathe vapors or spray mist.
Hygiene measures	:	Remove contaminated clothing immediately and dispose of safely. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.
Further information on storage conditions	:	Keep away from heat. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Store protected against freezing. Keep in a dry, cool and well-ventilated place.
Materials to avoid	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Recommended storage	:	5.00 - 35.00 °C

temperature

Packaging material : Suitable material: High density polyethylene (HDPE), Low density polyethylene (LDPE), Polyethylenetherephtalate (PET), Polypropylene

Section 8: Exposure controls/personal protection

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
propylene glycol monoethyl ether	1569-02-4	TWA	50 ppm	ACGIH
		STEL	200 ppm	ACGIH
propan-2-ol	67-63-0	WES-TWA	400 ppm 983 mg/m3	NZ OEL
		WES-STEL	500 ppm 1,230 mg/m3	NZ OEL
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
5-methylhexan-2-one	110-12-3	WES-TWA	50 ppm 234 mg/m3	NZ OEL
		TWA	20 ppm	ACGIH
		STEL	50 ppm	ACGIH
isobutyl alcohol	78-83-1	WES-TWA	50 ppm	NZ OEL

			152 mg/m3	
		TWA	50 ppm	ACGIH
phosphoric acid	7664-38-2	WES-TWA	1 mg/m3	NZ OEL
		TWA	1 mg/m3	ACGIH
		STEL	3 mg/m3	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of workweek	40 mg/l	ACGIH BEI

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Suitable respiratory equipment:

half-mask with A1P2 class combination filter

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection

Remarks	:	Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. nitrile gloves - material thickness: 0,35 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Preventive skin protection Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of

permeation time according to EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Eye protection : Required when there is a risk of eye contact.

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Skin and body protection : Anti-static protective clothing

Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

Protective measures : Do not breathe vapour/spray.

Eye wash fountains and safety showers must be easily accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Section 9: Physical and chemical properties

Appearance : liquid

Color : colorless

Odor	:	alcohol-like
pH	:	substance/mixture is non-polar/aprotic
Melting point/ range	:	not determined
Boiling point/boiling range	:	82.00 - 158.00 °C
Flash point	:	23 °C Method: ISO 3679
Flammability	:	Flammable liquid and vapour.
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	> 35.0 g/m3
Vapor pressure	:	not determined (20 °C) not determined (50 °C)

Relative vapor density	:	Heavier than air.
Density	:	0.837 g/cm3 (20 °C)
Solubility(ies)		
Water solubility	:	not determined
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	> 200 °C
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity		
Viscosity, kinematic	:	6.0 mm2/s (23 °C) not determined (40 °C)
Flow time	:	< 30 s Cross section: 3 mm
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Self-heating substances	:	The substance or mixture is not classified as self heating.
Metal corrosion rate	:	Not corrosive to metals.

Particle characteristics

Particle size : The substance / product is marketed or used in a non solid or granular form.

Section 10: Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : Vapours may form ignitable mixture with air.

Conditions to avoid : Avoid direct sunlight.

Protect from frost.

Heat.

Heat, flames and sparks.

Incompatible materials : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Hazardous decomposition products : No decomposition if stored and applied as directed.

Section 11: Toxicological information

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h

Test atmosphere: vapor

Method: Calculation method

Components:

phosphoric acid:

Acute oral toxicity : LD50 (Rat, female): 2,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization

Not classified due to lack of data.

Respiratory sensitization

Not classified due to lack of data.

Chronic toxicity

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

Section 12: Ecological information

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Components:

propylene glycol monoethyl ether:

Partition coefficient: n-octanol/water	:	log Pow: 0 (20 °C) pH: 7

propan-2-ol:

Partition coefficient: n-octanol/water	:	log Pow: 0.05 (25 °C) Remarks: Information taken from reference works and the literature.

5-methylhexan-2-one:

Partition coefficient: n-octanol/water	:	log Pow: 1.88 (25 °C)

isobutyl alcohol:

Partition coefficient: n-octanol/water	:	Pow: 10 (25 °C) log Pow: 1 (25 °C) Method: OECD Test Guideline 117

GLP: yes

Mobility in soil

No data available

Other adverse effects

No data available

Section 13: Disposal considerations

Disposal methods

Waste from residues	:	Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.
Contaminated packaging	:	Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC Packaging that is not properly emptied must be disposed of as the unused product.

Section 14: Transport information

International Regulations

UNRTDG

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
Environmentally hazardous	:	no

IATA-DGR

UN/ID No.	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	Flammable Liquids
Packing instruction (cargo aircraft)	:	366
Packing instruction (passenger aircraft)	:	355

IMDG-Code

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
EmS Code	:	F-E, S-E
Marine pollutant	:	no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

NZS 5433

UN number	:	UN 1263

Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
Hazchem Code	:	3Y
Marine pollutant	:	no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

ERG Code : 128

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

HSNO Approval Number

HSR002662 Surface Coatings and Colourants Flammable Group Standard

Tolerable Exposure Limits (TEL)

Not applicable

Environmental Exposure Limits (EEL)

Not applicable

HSW Controls

Certified handler certificate not required.
Tracking hazardous substance not required.
Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

Section 16: Other information

Revision Date	:	08.06.2025

Further information

Other information	:	For multi-pack systems observe material safety data sheets of all components. Restricted to professional users.
Date format	:	dd.mm.yyyy

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
NZ OEL	:	New Zealand. Workplace Exposure Standards for Atmospheric Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NZ OEL / WES-TWA	:	Workplace Exposure Standard - Time Weighted average
NZ OEL / WES-STEL	:	Workplace Exposure Standard - Short-Term Exposure Limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NZ / EN

352-235 2,5L Activator slow

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2025
4.0	22.08.2025	000000000054626293	Date of first issue: 22.08.2025

Section 1: Identification

Product name : 352-235 2,5L Activator slow

Product code : 000000000054626293

Manufacturer or supplier's details

BASF Coatings and Chemetall New Zealand Limited
Level 1, 527A Rosebank Road, Avondale
Auckland 1026
New Zealand
Telephone: 008 837 464, +64 9 820 3888
Telefax number: +64 9 820 3979
E-mail address: nzadmin@basf.com

Emergency contact

Telephone: +64 9 255-4300
E-mail address: ProductSafety_EC_APAC@basf.com, nzadmin@basf.com

Emergency telephone : National Poisons Centre: 0800 764 766
BASF Emergency Advice Number: 0800 944 955 (24 hour advice in an emergency only)
BASF Emergency Advice Number: +61 3 8855 6666 (If calling from outside New Zealand)

Recommended use of the chemical and restrictions on use

Recommended use : Spraying
Thinner

Section 2: Hazard identification

GHS Classification

Flammable liquids : Category 3

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation : Category 1

Specific target organ toxicity - single exposure	:	Category 3 (Respiratory system, Central nervous system)

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements :
H226 Flammable liquid and vapor.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

Precautionary Statements :

Prevention:
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification
If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Section 3: Composition/information on ingredients

Chemical nature : organic solvent
inorganic acids

Components

Chemical name	Common Name/Synonyms	CAS-No.	Classification	Concentration (% w/w)
isobutyl alcohol	2-methylpropan-1-ol	78-83-1	Flammable liquids, Category 3 Skin corrosion/irritation, Category 2 Serious eye damage/eye	>= 50 -< 70

			irritation, Category 1 Specific target organ toxicity - single exposure (Respiratory system, Central nervous system), Category 3	
n-butanol	butan-1-ol	71-36-3	Flammable liquids, Category 3 Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 1 Specific target organ toxicity - single exposure (Respiratory system, Central nervous system), Category 3	>= 30 -< 50
propylene glycol monoethyl ether	1-ethoxypropan-2-ol	1569-02-4	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 10 -< 20
phosphoric acid	orthophosphoric acid (Solution)	7664-38-2	Corrosive to Metals, Category 1 Acute toxicity (Oral), Category 4 Skin corrosion/irritation, Category 1B Serious eye	>= 3 -< 5

			damage/eye irritation, Category 1	

Section 4: First-aid measures

General advice	:	Never give anything by mouth to an unconscious person. Move out of dangerous area. In all cases of doubt, or when symptoms persist, seek medical attention. Immediately remove contaminated clothing. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). First aid personnel should pay attention to their own safety.
If inhaled	:	If breathed in, move person into fresh air. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.
In case of skin contact	:	Do NOT use solvents or thinners. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
In case of eye contact	:	Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Call a physician immediately. If easy to do, remove contact lens, if worn.
If swallowed	:	Rinse mouth with water.

Do not induce vomiting due to aspiration hazard.

Keep at rest.

If swallowed, call a poison control center or doctor immediately.

Most important symptoms and effects, both acute and delayed : Causes skin irritation.

Causes serious eye damage.

May cause respiratory irritation.

May cause drowsiness or dizziness.

Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Notes to physician : Treat symptomatically.
No known specific antidote.

Section 5: Fire-fighting measures

Suitable extinguishing media : Water spray jet

Dry powder

Alcohol-resistant foam

Carbon dioxide (CO2)

Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire fighting	:	Fire will produce dense black smoke containing hazardous combustion products (see section 10).
Hazardous combustion products	:	Oxides of phosphorus

Advice for firefighters

Specific extinguishing methods	:	Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Cool containers/tanks with water spray.
Special protective equipment for fire-fighters	:	Appropriate breathing apparatus may be required.
Hazchem Code	:	3Y

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures	:	Avoid breathing vapours. For non-emergency personnel: Use personal protective equipment. Ensure adequate ventilation, especially in confined areas. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet.
Environmental precautions	:	Do not allow uncontrolled discharge of product into the environment. Avoid subsoil penetration. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Ensure adequate ventilation. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

Section 7: Handling and storage

Advice on protection against fire and explosion	:	Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing

leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear.

The relevant fire protection measures should be noted.

Use explosion-proof equipment.

Vapors are heavier than air and may spread along floors.

Vapors may form explosive mixtures with air.

Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).

Do not return residues to the storage containers.

Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

The workplace should be equipped with an emergency shower and eye-rinsing facility.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

		Do not breathe vapors or spray mist.
Hygiene measures	:	Remove contaminated clothing immediately and dispose of safely. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.
Further information on storage conditions	:	Keep away from heat. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Store protected against freezing. Keep in a dry, cool and well-ventilated place.
Materials to avoid	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Recommended storage temperature	:	5 - 40 °C
Packaging material	:	Suitable material: High density polyethylene (HDPE), Low density polyethylene (LDPE), Polyethylenetherephtalate (PET), Polypropylene

Section 8: Exposure controls/personal protection

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
isobutyl alcohol	78-83-1	WES-TWA	50 ppm 152 mg/m3	NZ OEL
		TWA	50 ppm	ACGIH
n-butanol	71-36-3	WES-Ceiling	50 ppm 150 mg/m3	NZ OEL
	Further information: Skin absorption			
		TWA	20 ppm	ACGIH
propylene glycol monoethyl ether	1569-02-4	TWA	50 ppm	ACGIH
		STEL	200 ppm	ACGIH
phosphoric acid	7664-38-2	WES-TWA	1 mg/m3	NZ OEL
		TWA	1 mg/m3	ACGIH
		STEL	3 mg/m3	ACGIH

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Suitable respiratory equipment:

half-mask with A1P2 class combination filter

In case of mist, spray or aerosol exposure wear suitable

personal respiratory protection and protective suit.

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection

Remarks	:	Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. nitrile gloves - material thickness: 0,35 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Request information on glove permeation properties from the glove supplier.

Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Preventive skin protection

Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Eye protection : Required when there is a risk of eye contact.

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Skin and body protection : Anti-static protective clothing

Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

Protective measures : Do not breathe vapour/spray.

Eye wash fountains and safety showers must be easily accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety

practice.

Section 9: Physical and chemical properties

Appearance	:	liquid
Color	:	colorless
Odor	:	alcohol-like
pH	:	substance/mixture is non-polar/aprotic
Melting point/ range	:	not determined
Boiling point/boiling range	:	not determined
Flash point	:	> 32 °C Method: ISO 3679
Flammability	:	Flammable liquid and vapour.
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	> 35 g/m3

Vapor pressure	:	not determined (20 °C) not determined (50 °C)
Relative vapor density	:	Heavier than air.
Density	:	0.833 g/cm3 (20 °C)
Solubility(ies) Water solubility	: :	 not determined
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	> 200 °C
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity Viscosity, kinematic	: :	 6.0 mm2/s (23 °C) not determined (40 °C)
Flow time	:	< 30 s (23 °C) Cross section: 3 mm Method: ISO 2431
Explosive properties	:	Not explosive

Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Self-heating substances	:	The substance or mixture is not classified as self heating.
Metal corrosion rate	:	Not corrosive to metals.
Particle characteristics Particle size	:	The substance / product is marketed or used in a non solid or granular form.

Section 10: Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	Vapours may form ignitable mixture with air.
Conditions to avoid	:	Heat. Heat, flames and sparks. Protect from frost. Avoid direct sunlight.
Incompatible materials	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

Section 11: Toxicological information

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Components:

phosphoric acid:

Acute oral toxicity : LD50 (Rat, female): 2,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization

Based on available data, the classification criteria are not met.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Chronic toxicity

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.
May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration toxicity

Based on available data, the classification criteria are not met.

Section 12: Ecological information

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Components:

isobutyl alcohol:

Partition coefficient: n-octanol/water	:	Pow: 10 (25 °C) log Pow: 1 (25 °C) Method: OECD Test Guideline 117 GLP: yes

n-butanol:

Partition coefficient: n-octanol/water	:	log Pow: 1 (25 °C) Method: OECD Test Guideline 117 GLP: yes

propylene glycol monoethyl ether:

Partition coefficient: n-octanol/water	:	log Pow: 0 (20 °C) pH: 7

Mobility in soil

No data available

Other adverse effects

No data available

Section 13: Disposal considerations

Disposal methods

Waste from residues	:	Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.
Contaminated packaging	:	Packaging that is not properly emptied must be disposed of as the unused product.

Section 14: Transport information

International Regulations

UNRTDG

UN number	:	UN 1263
Proper shipping name	:	PAINT
Class	:	3
Packing group	:	III
Labels	:	3
Environmentally hazardous	:	no

IATA-DGR

UN/ID No.	:	UN 1263
Proper shipping name	:	PAINT

Class	:	3
Packing group	:	III
Labels	:	Flammable Liquids
Packing instruction (cargo aircraft)	:	366
Packing instruction (passenger aircraft)	:	355

IMDG-Code

UN number	:	UN 1263
Proper shipping name	:	PAINT
Class	:	3
Packing group	:	III
Labels	:	3
EmS Code	:	F-E, S-E
Marine pollutant	:	no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
Not applicable for product as supplied.

Domestic regulation

NZS 5433

UN number	:	UN 1263
Proper shipping name	:	PAINT
Class	:	3
Packing group	:	III

Labels	:	3
Hazchem Code	:	3Y
Marine pollutant	:	no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

HSNO Approval Number
HSR002662 Surface Coatings and Colourants Flammable Group Standard

Tolerable Exposure Limits (TEL)
Not applicable

Environmental Exposure Limits (EEL)
Not applicable

HSW Controls
Certified handler certificate not required.
Tracking hazardous substance not required.
Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

Section 16: Other information

Revision Date	:	22.08.2025

Further information

Other information	:	For multi-pack systems observe material safety data sheets of all components. Restricted to professional users.
Date format	:	dd.mm.yyyy

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NZ OEL	:	New Zealand. Workplace Exposure Standards for Atmospheric Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NZ OEL / WES-TWA	:	Workplace Exposure Standard - Time Weighted average
NZ OEL / WES-Ceiling	:	Workplace Exposure Standard - Ceiling

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level;

NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NZ / EN

SAFETY DATA SHEET

352-345 5L CV Reducer very slow

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2025
5.0	15.08.2025	000000000054771142	Date of first issue: 15.08.2025

Section 1: Identification

Product name : 352-345 5L CV Reducer very slow

Product code : 000000000054771142

Manufacturer or supplier's details

BASF Coatings and Chemetall New Zealand Limited
Level 1, 527A Rosebank Road, Avondale
Auckland 1026
New Zealand
Telephone: 008 837 464, +64 9 820 3888
Telefax number: +64 9 820 3979
E-mail address: nzadmin@basf.com

Emergency contact

Telephone: +64 9 255-4300
E-mail address: ProductSafety_EC_APAC@basf.com, nzadmin@basf.com

Emergency telephone : National Poisons Centre: 0800 764 766
BASF Emergency Advice Number: 0800 944 955 (24 hour advice in an emergency only)
BASF Emergency Advice Number: +61 3 8855 6666 (If calling from outside New Zealand)

Recommended use of the chemical and restrictions on use

Recommended use : Spraying
Thinner

Section 2: Hazard identification

GHS Classification

Flammable liquids : Category 3

Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)

Aspiration hazard	:	Category 1
Hazardous to the aquatic environment - chronic hazard	:	Category 2

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements :
H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements :

Prevention:
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing mist or vapors.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P331 Do NOT induce vomiting.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391 Collect spillage.
Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification
If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Section 3: Composition/information on ingredients

Chemical nature : organic solvent

Components

Chemical name	Common Name/Synonyms	CAS-No.	Classification	Concentration (% w/w)
1-methoxy-2-propylacetate	2-methoxy-1-methylethyl acetate	108-65-6	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 20 -< 30

Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0)	Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0)	64742-95-6	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Respiratory system, Central nervous system), Category 3 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 2	>= 25 -< 30
2-butoxyethyl acetate	2-butoxyethyl acetate	112-07-2	Flammable liquids, Category 4 Acute toxicity (Oral), Category 4 Acute toxicity (Dermal), Category 4	>= 10 -< 20
n-Butyl acetate	n-butyl acetate	123-86-4	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 10 -< 20

Section 4: First-aid measures

General advice : In case of intoxication, call a poison control center or

physician for treatment advice, taking the packaging or the label of the product.
Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.
Keep patient warm and at rest.
Never give anything by mouth to an unconscious person.
Move out of dangerous area.
Immediately remove contaminated clothing.
First aid personnel should pay attention to their own safety.

If inhaled : If breathed in, move person into fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician or poison control center immediately.

In case of skin contact : Do NOT use solvents or thinners.

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

If symptoms persist, call a physician.

In case of eye contact : In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

If symptoms persist, call a physician.

If swallowed : Rinse mouth with water.

Do not induce vomiting due to aspiration hazard.

Keep at rest.

If swallowed, call a poison control center or doctor immediately.

Most important symptoms and effects, both acute and delayed	:	May be fatal if swallowed and enters airways. May cause respiratory irritation. May cause drowsiness or dizziness. Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia. Risk of product entering the lungs on vomiting after ingestion.
Notes to physician	:	Treat symptomatically. No known specific antidote.

Section 5: Fire-fighting measures

Suitable extinguishing media	:	Water spray jet Dry powder Alcohol-resistant foam Carbon dioxide (CO2)

Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire fighting	:	Fire will produce dense black smoke containing hazardous combustion products (see section 10).

Advice for firefighters

Specific extinguishing methods	:	Cool containers/tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Special protective equipment for fire-fighters	:	Appropriate breathing apparatus may be required.
Hazchem Code	:	3Y

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures	:	Avoid breathing vapours. For non-emergency personnel: Use personal protective equipment.

Ensure adequate ventilation, especially in confined areas.

Keep away from sources of ignition.

For emergency responders:

Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.

Avoid subsoil penetration.

Do not allow uncontrolled discharge of product into the environment.

Methods and materials for containment and cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

Ensure adequate ventilation.

Section 7: Handling and storage

Advice on protection against fire and explosion : Avoid all sources of ignition: heat, sparks, open flame.

Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear.

The relevant fire protection measures should be noted.

Use explosion-proof equipment.

Vapors are heavier than air and may spread along floors.

Vapors may form explosive mixtures with air.

Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).

Do not return residues to the storage containers.

Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

The workplace should be equipped with an emergency shower and eye-rinsing facility.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Do not breathe vapors or spray mist.

Hygiene measures : Remove contaminated clothing immediately and dispose of

safely.

Wash hands before breaks and at the end of workday.

Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions	:	Keep away from heat. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Store protected against freezing. Keep in a dry, cool and well-ventilated place.
Materials to avoid	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Recommended storage temperature	:	5.00 - 40.00 °C
Packaging material	:	Suitable material: Carbon steel (Iron), tinned carbon steel (Tinplate)

Section 8: Exposure controls/personal protection

Ingredients with workplace control parameters

Components	CAS-No.	Value type	Control	Basis

		(Form of exposure)	parameters / Permissible concentration	
Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0)	64742-95-6	WES-TWA	300 ppm 890 mg/m3	NZ OEL
		WES-STEL	500 ppm 1,480 mg/m3	NZ OEL
2-butoxyethyl acetate	112-07-2	TWA	20 ppm	ACGIH
n-Butyl acetate	123-86-4	WES-STEL	200 ppm 950 mg/m3	NZ OEL
		WES-TWA	150 ppm 713 mg/m3	NZ OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Suitable respiratory equipment:

half-mask with A1P2 class combination filter

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection

Remarks	:	Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. butyl rubber gloves - material thickness: 0.5 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier.

Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Preventive skin protection

Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Eye protection : Required when there is a risk of eye contact.

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Skin and body protection : Anti-static protective clothing

Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

Protective measures : Do not breathe vapour/spray.

Eye wash fountains and safety showers must be easily accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Section 9: Physical and chemical properties

Appearance	:	liquid
Color	:	colorless
Odor	:	of acetate
pH	:	substance/mixture is non-polar/aprotic
Melting point/ range	:	not determined
	:	124.00 - 195.00 °C
Flash point	:	41 °C Method: ISO 3679
Flammability	:	Flammable liquid and vapour.
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	> 35.0 g/m3

Vapor pressure	:	not determined (20 °C) not determined (50 °C)
Density	:	0.921 g/cm3 (20 °C)
Solubility(ies) Water solubility	: :	 not determined
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	> 200 °C
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity Viscosity, kinematic	: :	 6.0 mm2/s (23 °C) not determined (40 °C)
Flow time	:	< 30 s Cross section: 3 mm
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

Self-heating substances	:	The substance or mixture is not classified as self heating.
Metal corrosion rate	:	Not corrosive to metals.
Particle characteristics		
Particle size	:	The substance / product is marketed or used in a non solid or granular form.

Section 10: Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	Vapours may form ignitable mixture with air.
Conditions to avoid	:	Avoid direct sunlight. Heat. Heat, flames and sparks. Protect from frost.
Incompatible materials	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

Section 11: Toxicological information

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method

Components:

2-butoxyethyl acetate:

Acute oral toxicity	:	LD50 (Rat): 1,880 mg/kg
Acute dermal toxicity	:	LD50 (Rabbit): 1,500 mg/kg

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Components:

n-Butyl acetate:

Assessment	:	Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Skin sensitization

Based on available data, the classification criteria are not met.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Chronic toxicity

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.
May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Section 12: Ecological information

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Components:

1-methoxy-2-propylacetate:

Partition coefficient: n-octanol/water	:	log Pow: 1.2 (20 °C) pH: 6.8 Method: OECD Test Guideline 117 GLP: yes

Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0):

Partition coefficient: n-octanol/water	:	log Pow: 3.17 GLP: no

2-butoxyethyl acetate:

Partition coefficient: n-octanol/water	:	log Pow: 1.51 (25 °C) pH: 7 Method: OECD Test Guideline 107 GLP: no

n-Butyl acetate:

Partition coefficient: n-octanol/water	:	Pow: 200 (25 °C) log Pow: 2.3 (25 °C) pH: 7 Method: OECD Test Guideline 117 GLP: yes

Mobility in soil

No data available

Other adverse effects

No data available

Section 13: Disposal considerations

Disposal methods

Waste from residues	:	Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.
Contaminated packaging	:	Packaging that is not properly emptied must be disposed of as the unused product.

Section 14: Transport information

International Regulations

UNRTDG

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
Environmentally hazardous	:	yes

IATA-DGR

UN/ID No.	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	Flammable Liquids

Packing instruction (cargo aircraft)	:	366
Packing instruction (passenger aircraft)	:	355

IMDG-Code

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL (SOLVENT NAPHTHA)
Class	:	3
Packing group	:	III
Labels	:	3
EmS Code	:	F-E, S-E
Marine pollutant	:	yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
Not applicable for product as supplied.

Domestic regulation

NZS 5433

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3

Hazchem Code	:	3Y
Marine pollutant	:	yes

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

HSNO Approval Number

HSR002662 Surface Coatings and Colourants Flammable Group Standard

Tolerable Exposure Limits (TEL)

Not applicable

Environmental Exposure Limits (EEL)

Not applicable

HSW Controls

Certified handler certificate not required.
Tracking hazardous substance not required.
Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

Section 16: Other information

Revision Date	:	15.08.2025

Further information

Other information	:	For multi-pack systems observe material safety data sheets of

all components.
Restricted to professional users.

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

NZ OEL : New Zealand. Workplace Exposure Standards for Atmospheric Contaminants

ACGIH / TWA : 8-hour, time-weighted average

ACGIH / STEL : Short-term exposure limit

NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average

NZ OEL / WES-STEL : Workplace Exposure Standard - Short-Term Exposure Limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level;

NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NZ / EN

352-370 5L CV Reducer extra slow

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2025
4.0	22.08.2025	000000000050660900	Date of first issue: 22.08.2025

Section 1: Identification

Product name : 352-370 5L CV Reducer extra slow

Product code : 000000000050660900

Manufacturer or supplier's details

BASF Coatings and Chemetall New Zealand Limited
Level 1, 527A Rosebank Road, Avondale
Auckland 1026
New Zealand
Telephone: 008 837 464, +64 9 820 3888
Telefax number: +64 9 820 3979
E-mail address: nzadmin@basf.com

Emergency contact

Telephone: +64 9 255-4300
E-mail address: ProductSafety_EC_APAC@basf.com, nzadmin@basf.com

Emergency telephone : National Poisons Centre: 0800 764 766
BASF Emergency Advice Number: 0800 944 955 (24 hour advice in an emergency only)
BASF Emergency Advice Number: +61 3 8855 6666 (If calling from outside New Zealand)

Recommended use of the chemical and restrictions on use

Recommended use : Spraying
Thinner

Section 2: Hazard identification

GHS Classification

Flammable liquids : Category 3

Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)

Aspiration hazard	:	Category 1
Hazardous to the aquatic environment - chronic hazard	:	Category 3

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements :
H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements :

Prevention:
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing mist or vapors.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P331 Do NOT induce vomiting.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification
If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Section 3: Composition/information on ingredients

Chemical nature : organic solvent

Components

Chemical name	Common Name/Synonyms	CAS-No.	Classification	Concentration (% w/w)
Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0)	Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0)	64742-95-6	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Respiratory system, Central nervous system), Category 3 Aspiration hazard,	>= 20 -< 25

			Category 1 Hazardous to the aquatic environment - chronic hazard, Category 2	
1-methoxy-2-propylacetate	2-methoxy-1-methylethyl acetate	108-65-6	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 10 -< 20
2-butoxyethyl acetate	2-butoxyethyl acetate	112-07-2	Flammable liquids, Category 4 Acute toxicity (Oral), Category 4 Acute toxicity (Dermal), Category 4	>= 10 -< 20
n-Butyl acetate	n-butyl acetate	123-86-4	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 1 -< 10

Section 4: First-aid measures

General advice : Move out of dangerous area.

In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product.
Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.
Keep patient warm and at rest.
Never give anything by mouth to an unconscious person.
Immediately remove contaminated clothing.
First aid personnel should pay attention to their own safety.

If inhaled : If breathed in, move person into fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician or poison control center immediately.

In case of skin contact : Do NOT use solvents or thinners.

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

If symptoms persist, call a physician.

In case of eye contact : In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

If symptoms persist, call a physician.

If swallowed : If swallowed, call a poison control center or doctor immediately.

Rinse mouth with water.

Do not induce vomiting due to aspiration hazard.

Keep at rest.

Most important symptoms and effects, both acute and delayed	:	Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia. Risk of product entering the lungs on vomiting after ingestion. May be fatal if swallowed and enters airways. May cause respiratory irritation. May cause drowsiness or dizziness.
Notes to physician	:	Treat symptomatically. No known specific antidote.

Section 5: Fire-fighting measures

Suitable extinguishing media	:	Water spray jet Dry powder Alcohol-resistant foam Carbon dioxide (CO2)

Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire fighting	:	Fire will produce dense black smoke containing hazardous combustion products (see section 10).

Advice for firefighters

Specific extinguishing methods	:	Cool containers/tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Special protective equipment for fire-fighters	:	Appropriate breathing apparatus may be required.
Hazchem Code	:	3Y

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures	:	Avoid breathing vapours. For non-emergency personnel: Use personal protective equipment.

Ensure adequate ventilation, especially in confined areas.

Keep away from sources of ignition.

For emergency responders:

Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.

Avoid subsoil penetration.

Do not allow uncontrolled discharge of product into the environment.

Methods and materials for containment and cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

Ensure adequate ventilation.

Section 7: Handling and storage

Advice on protection against fire and explosion : Avoid all sources of ignition: heat, sparks, open flame.

Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear.

The relevant fire protection measures should be noted.

Use explosion-proof equipment.

Vapors are heavier than air and may spread along floors.

Vapors may form explosive mixtures with air.

Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).

Do not return residues to the storage containers.

Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

The workplace should be equipped with an emergency shower and eye-rinsing facility.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Do not breathe vapors or spray mist.

Hygiene measures : Remove contaminated clothing immediately and dispose of

		safely. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.
Further information on storage conditions	:	Keep away from heat. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Store protected against freezing. Keep in a dry, cool and well-ventilated place.
Materials to avoid	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Recommended storage temperature	:	5 - 35 °C
Packaging material	:	Suitable material: Carbon steel (Iron), tinned carbon steel (Tinplate)

Section 8: Exposure controls/personal protection

Ingredients with workplace control parameters

Components	CAS-No.	Value type	Control	Basis

		(Form of exposure)	parameters / Permissible concentration	
Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0)	64742-95-6	WES-TWA	300 ppm 890 mg/m3	NZ OEL
		WES-STEL	500 ppm 1,480 mg/m3	NZ OEL
2-butoxyethyl acetate	112-07-2	TWA	20 ppm	ACGIH
n-Butyl acetate	123-86-4	WES-STEL	200 ppm 950 mg/m3	NZ OEL
		WES-TWA	150 ppm 713 mg/m3	NZ OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Suitable respiratory equipment:

half-mask with A1P2 class combination filter

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection

Remarks	:	Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. butyl rubber gloves - material thickness: 0.5 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier.

Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Preventive skin protection

Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Eye protection : Required when there is a risk of eye contact.

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Skin and body protection : Anti-static protective clothing

Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

Protective measures : Do not breathe vapour/spray.

Eye wash fountains and safety showers must be easily accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Section 9: Physical and chemical properties

Appearance	:	liquid
Color	:	colorless
Odor	:	ester-like
pH	:	substance/mixture is non-polar/aprotic
Melting point/ range	:	not determined
Boiling point/boiling range	:	124 - 195 °C Method: calculated
Flash point	:	44 °C Method: ISO 3679
Flammability	:	Flammable liquid and vapour.
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	> 35 g/m3

Vapor pressure	:	13.0000 hPa (20 °C) Method: calculated not determined (50 °C)
Density	:	0.924 g/cm3 (20 °C)
Solubility(ies) Water solubility	: :	 not determined
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	> 200 °C
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity Viscosity, kinematic	: :	 6.0 mm2/s (23 °C) not determined (40 °C)
Flow time	:	< 30 s (23 °C) Cross section: 3 mm Method: ISO 2431
Explosive properties	:	Not explosive

Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Self-heating substances	:	The substance or mixture is not classified as self heating.
Metal corrosion rate	:	Not corrosive to metals.
Particle characteristics Particle size	:	The substance / product is marketed or used in a non solid or granular form.

Section 10: Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	Vapours may form ignitable mixture with air.
Conditions to avoid	:	Avoid direct sunlight. Heat. Heat, flames and sparks. Protect from frost.
Incompatible materials	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

Section 11: Toxicological information

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Components:

2-butoxyethyl acetate:

Acute oral toxicity : LD50 (Rat): 1,880 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 1,500 mg/kg

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Components:

n-Butyl acetate:

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Skin sensitization

Based on available data, the classification criteria are not met.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Chronic toxicity

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.
May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Section 12: Ecological information

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Components:

Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0):

Partition coefficient: n-octanol/water	:	log Pow: 3.17 GLP: no

1-methoxy-2-propylacetate:

Partition coefficient: n-octanol/water	:	log Pow: 1.2 (20 °C) pH: 6.8 Method: OECD Test Guideline 117 GLP: yes

2-butoxyethyl acetate:

Partition coefficient: n-octanol/water	:	log Pow: 1.51 (25 °C) pH: 7 Method: OECD Test Guideline 107 GLP: no

n-Butyl acetate:

Partition coefficient: n-octanol/water	:	Pow: 200 (25 °C) log Pow: 2.3 (25 °C) pH: 7 Method: OECD Test Guideline 117 GLP: yes

Mobility in soil

No data available

Other adverse effects

No data available

Section 13: Disposal considerations

Disposal methods

Waste from residues	:	Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.
Contaminated packaging	:	Packaging that is not properly emptied must be disposed of as the unused product.

Section 14: Transport information

International Regulations

UNRTDG

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
Environmentally hazardous	:	no

IATA-DGR

UN/ID No.	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	Flammable Liquids

Packing instruction (cargo aircraft)	:	366
Packing instruction (passenger aircraft)	:	355

IMDG-Code

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
EmS Code	:	F-E, S-E
Marine pollutant	:	no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
Not applicable for product as supplied.

Domestic regulation

NZS 5433

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
Hazchem Code	:	3Y

Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

HSNO Approval Number
not allocated

Tolerable Exposure Limits (TEL)
Not applicable

Environmental Exposure Limits (EEL)
Not applicable

Section 16: Other information

Revision Date : 22.08.2025

Further information

Other information : For multi-pack systems observe material safety data sheets of all components.
Restricted to professional users.

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NZ OEL	:	New Zealand. Workplace Exposure Standards for Atmospheric Contaminants

ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NZ OEL / WES-TWA	:	Workplace Exposure Standard - Time Weighted average
NZ OEL / WES-STEL	:	Workplace Exposure Standard - Short-Term Exposure Limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; SADT - Self-Accelerating

Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NZ / EN

We create chemistry

Safety data sheet

1. Substance/preparation and manufacturer/supplier identification

Product name:
352-450 1L BLEND REDUCER G2

Use: Thinner

Manufacturer/supplier:
BASF New Zealand Ltd.
5E City Works Depot
77 Cook Street
Auckland Central, Auckland 1010
NEW ZEALAND
Telephone: +64 9 255-4300
Telefax number: +64 9 255-4307

Emergency information:
National Poisons Centre: 0800 764 766
BASF Emergency Advice Number: 0800 944 955 (24 hour advice in an emergency only)
BASF Emergency Advice Number: +61 3 8855 6666 (If calling from outside New Zealand)

2. Hazard identification

Classification of the substance and mixture:
Skin corrosion/irritation: Cat.3
Serious eye damage/eye irritation: Cat.2A
Aspiration hazard: Cat.1
Specific target organ toxicity — single exposure: Cat.3 (May cause drowsiness and dizziness.)
Specific target organ toxicity — single exposure: Cat.3 (irritating to respiratory system)
Hazardous to the aquatic environment - acute: Cat.3
Hazardous to the aquatic environment - chronic: Cat.3
Flammable liquids: Cat.3
Carcinogenicity: Cat.2

Label elements and precautionary statement:

Pictogram:



Signal Word:
Danger

Hazard Statement:

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H316	Causes mild skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P201	Obtain special instructions before use.
P280	Wear protective gloves, protective clothing and eye protection or face protection.
P264	Wash contaminated body parts thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P242	Use non-sparking tools.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P243	Take action to prevent static discharges.
P233	Keep container tightly closed.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground and bond container and receiving equipment.
P202	Do not handle until all safety precautions have been read and understood.
P273	Avoid release to the environment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or physician if you feel unwell.
P370 + P378	In case of fire: Use water spray for extinction.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or physician.
P332 + P313	If skin irritation occurs: Get medical attention.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P337 + P313	If eye irritation persists: Get medical attention.
P308 + P313	IF exposed or concerned: Get medical attention.
P331	Do NOT induce vomiting.

Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.

Other hazards which do not result in classification:
If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

3. Composition/information on ingredients

Chemical nature

Substance nature: mixture

acrylic resin, organic solvent

Hazardous ingredients

n-Butyl acetate

Content (W/W): >= 30 % - < 50 %	Flam. Liq.: Cat. 3
CAS Number: 123-86-4	STOT SE: Cat. 3 (drowsiness and dizziness)
	Aquatic Acute: Cat. 3

Solventnaphtha (petroleum), light aromatic

Content (W/W): >= 15 % - < 20 %	Asp. Tox.: Cat. 1
CAS Number: 64742-95-6	Flam. Liq.: Cat. 3
	STOT SE: Cat. 3 (drowsiness and dizziness)
	STOT SE: Cat. 3 (irr. to respiratory syst.)
	Aquatic Chronic: Cat. 2

Propanoic acid, 3-ethoxy-, ethyl ester

Content (W/W): >= 12.5 % - < 15 %	Flam. Liq.: Cat. 3
CAS Number: 763-69-9	Acute Tox.: Cat. 5 (oral)
	Aquatic Acute: Cat. 3
	Acute Tox.: Cat. 5 (dermal)

4-methylpentan-2-one

Content (W/W): >= 10 % - < 12.5 % CAS Number: 108-10-1	Asp. Tox.: Cat. 2 Flam. Liq.: Cat. 2 Acute Tox.: Cat. 4 (Inhalation - vapour) Acute Tox.: Cat. 5 (oral) Eye Dam./Irrit.: Cat. 2A Carc.: Cat. 2 STOT SE: Cat. 3 (drowsiness and dizziness) STOT SE: Cat. 3 (irr. to respiratory syst.)

xylene

Content (W/W): >= 7 % - < 10 % CAS Number: 1330-20-7	Asp. Tox.: Cat. 1 Flam. Liq.: Cat. 3 Acute Tox.: Cat. 5 (Inhalation - vapour) Acute Tox.: Cat. 5 (oral) Skin Corr./Irrit.: Cat. 2 Eye Dam./Irrit.: Cat. 2B STOT SE: Cat. 3 (irr. to respiratory syst.) STOT RE (Central nervous system, Liver, Kidney): Cat. 2 Aquatic Acute: Cat. 2 Aquatic Chronic: Cat. 3

2-butoxyethyl acetate

Content (W/W): >= 2 % - < 2.5 % CAS Number: 112-07-2	Flam. Liq.: Cat. 4 Acute Tox.: Cat. 4 (oral) Acute Tox.: Cat. 4 (dermal) Aquatic Acute: Cat. 3

ethylbenzene

Content (W/W): >= 1 % - < 2 % CAS Number: 100-41-4	Asp. Tox.: Cat. 1 Flam. Liq.: Cat. 2 Acute Tox.: Cat. 4 (Inhalation - vapour) Acute Tox.: Cat. 5 (oral) STOT RE (Auditory organ): Cat. 2 Aquatic Acute: Cat. 2 Aquatic Chronic: Cat. 3

4. First-Aid Measures

General advice:
First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove affected person from danger area. Keep warm, calm and covered up. Immediately remove contaminated clothing. Never give anything by mouth to an unconscious person. In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product. Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.

If inhaled:
Immediate medical attention required. Remove the affected individual into fresh air and keep the person calm. If breathing is irregular or stopped, administer artificial respiration.

On skin contact:
If symptoms persist, seek medical advice. Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

On contact with eyes:
Remove contact lenses, if present. Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Immediate medical attention required.

On ingestion:
Summon medical aid without delay. Do not induce vomiting due to aspiration hazard. Rinse mouth immediately with water. Keep at rest.

Note to physician:
Symptoms: Eye irritation, aspiration pneumonia, allergic symptoms, dazed state, irritation of respiratory tract, skin irritation, dizziness, Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.
Hazards: If swallowed, in the event of vomiting, risk of product entering the lungs. When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.
Treatment: Symptomatic treatment (decontamination, vital functions).
Antidote: No known specific antidote.

5. Fire-Fighting Measures

Suitable extinguishing media:
carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:
water jet

Specific hazards:
Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

Special protective equipment:
Appropriate breathing apparatus may be required.

Further information:
Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

6. Accidental Release Measures

Personal precautions:
Avoid breathing vapours.For non-emergency personnel:Use personal protective clothing.Ensure adequate ventilation.Keep away from sources of ignition.For emergency responders:Advice on

product handling can be found in sections 7 and 8 of this safety data sheet.Information regarding personal protective measures, see section 8.

Environmental precautions:
Do not allow to enter drains or waterways.If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency.Do not discharge into the subsoil/soil.

Methods for cleaning up or taking up:
Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents. Ensure adequate ventilation.

7. Handling and Storage

Handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:
Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapours are heavier than air and spread along floors. Vapour forms explosive mixtures with air. The relevant fire protection measures should be noted. Use explosion-proof equipment.

Storage

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

Suitable materials for containers: tinned carbon steel (Tinplate), Carbon steel (Iron)
Further information on storage conditions: Keep container dry. Keep away from heat. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Store protected against freezing.

Storage stability:
Storage temperature: 5 - 35 °C

8. Exposure controls and personal protection

Components with occupational exposure limits

ethylbenzene, 100-41-4;
TWA value 20 ppm (ACGIHTLV)
TWA value 88 mg/m3 ; 20 ppm (OEL (NZ))
STEL value 176 mg/m3 ; 40 ppm (OEL (NZ))
Skin Designation (OEL (NZ))
Skin absorption can be significant.

4-methylpentan-2-one, 108-10-1;
STEL value 75 ppm (ACGIHTLV)
TWA value 20 ppm (ACGIHTLV)
TWA value 205 mg/m3 ; 50 ppm (OEL (NZ))
STEL value 307 mg/m3 ; 75 ppm (OEL (NZ))

n-Butyl acetate, 123-86-4;
STEL value 150 ppm (ACGIHTLV)
TWA value 50 ppm (ACGIHTLV)
TWA value 713 mg/m3 ; 150 ppm (OEL (NZ))
STEL value 950 mg/m3 ; 200 ppm (OEL (NZ))

xylene, 1330-20-7;
TWA value 20 ppm (ACGIHTLV)
TWA value 217 mg/m3 ; 50 ppm (OEL (NZ))

Solventnaphtha (petroleum), light aromatic, 64742-95-6;

Personal protective equipment

Respiratory protection:
Suitable respiratory protection: e.g. half-mask with A2P2 class combination filter When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators. Use A1P2 breathing-protection half mask in case of contact with aerosols.

Hand protection:
Further information on penetration time is available from the manufacturer of the glove.
Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.
The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).
Follow manufacturer's advice on use, storage, maintenance and replacement of gloves.
The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).
Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g.
nitrile gloves - material thickness: 0,7 mm
Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):
Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)

Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Eye protection:
Tightly fitting safety goggles (splash goggles) (e.g. EN 166), Required when there is a risk of eye contact.

Body protection:
Anti-static protective clothing, Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

General safety and hygiene measures:
Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Ensure adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

9. Physical and Chemical Properties

Form:	liquid	
Colour:	colourless	
Odour:	of hydrocarbons	
pH value:		
	substance/mixture is non-polar/aprotic	
Melting point:		
	not determined	
onset of boiling:		
	not determined	
Flash point:	26 °C	(ISO 3679)
Flammability (solid/gas):	Flammable liquid and vapour.	
Lower explosion limit:	36 g/m3	
Ignition temperature:	> 200 °C	
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
Self heating ability:	It is not a material capable of spontaneous heating	
Explosion hazard:	not explosive	
Fire promoting properties:	not fire-propagating	
Vapour pressure:		
	(20 °C)	
	not determined	

(50 °C)
not determined

Density: 0.883 g/cm3
(20 °C)

Relative vapour density (air):
Heavier than air.

Miscibility with water:
immiscible

Partitioning coefficient n-octanol/water (log Pow):
not applicable for mixtures

Viscosity, kinematic:
(40 °C)
No data available.
6.0 mm2/s
(23 °C)

Flow time: < 30 s (DIN EN ISO 2431; 3 mm)
(23 °C)

10. Stability and Reactivity

Conditions to avoid:
Avoid heat. Avoid direct sunlight. Avoid all sources of ignition: heat, sparks, open flame. Avoid freezing.

Thermal decomposition: No decomposition if stored and handled as prescribed/indicated.

Substances to avoid:
Keep away from highly acidic or alkaline substances as well as oxidants in order to prevent exothermal reactions.

Hazardous reactions:
Vapours may form ignitable mixture with air.

When exposed to high temperatures hazardous decomposition products such as carbon monoxide, carbon dioxide, smoke, oxides of nitrogen may be produced., No hazardous decomposition products if stored and handled as prescribed/indicated.

Chemical stability:
The product is stable if stored and handled as prescribed/indicated.

Reactivity:
No hazardous reactions if stored and handled as prescribed/indicated.

11. Toxicological Information

Routes of exposure

Assessment of acute toxicity

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated and prolonged exposure to solvents at levels significantly above OELs may lead to the development of long-lasting central nervous system disorders such as chronic toxic encephalopathy, signs of toxicity include changes in behaviour and memory. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Based on available data, the classification criteria are not met.

Symptoms

Eye irritation aspiration pneumonia allergic symptoms dazed state irritation of respiratory tract skin irritation dizziness Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Irritation

Assessment of irritating effects:
The liquid splashed in the eyes may cause irritation and reversible damage. Eye contact causes irritation. Skin contact causes slight irritation.

Respiratory/Skin sensitization

Assessment of sensitization:
Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Assessment of mutagenicity:
Based on available data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity:
Indication of possible carcinogenic effect in animal tests.

Reproductive toxicity

Assessment of reproduction toxicity:
Based on available data, the classification criteria are not met.

Developmental toxicity

Assessment of teratogenicity:
Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Causes temporary irritation of the respiratory tract. Possible narcotic effects (drowsiness or dizziness).

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:
Based on available data, the classification criteria are not met.

Aspiration hazard

May also damage the lung at swallowing (aspiration hazard).

12. Ecological Information

Ecotoxicity

Assessment of aquatic toxicity:
Harmful to aquatic life. Harmful to aquatic life with long lasting effects. There are no test results available for this product. Do not allow to enter drains or waterways.

Mobility

Assessment transport between environmental compartments:
No data available.

Persistence and degradability

Assessment biodegradation and elimination (H2O):
Biological degradability of hazardous substances mentioned in section 3:

Information on: ethylbenzene
Elimination information:
70 - 80 % TIC of the ThIC (28 d) (ISO 14593) (aerobic, activated sludge) Readily biodegradable (according to OECD criteria).

Information on: 2-butoxyethyl acetate
Elimination information:
88 % BOD of the ThOD (28 d) (OECD 301F; ISO 9408; 92/69/EWG, C.4-D) (aerobic, activated sludge, domestic)

Information on: n-Butyl acetate
Elimination information:
80 % BOD of the ThOD (5 d) (OECD 301D; 92/69/EWG, C.4-E) (aerobic, municipal sewage treatment plant effluent)

Information on: Ethyl 3-ethoxypropionate
Elimination information:
100 % CO2 formation relative to the theoretical value (28 d) (Directive 84/449/EEC, C.5) (aerobic, activated sludge, domestic, non-adapted) Readily biodegradable.

100 % CO2 formation relative to the theoretical value (18 d) (OECD 301B; ISO 9439; 92/69/EWG, C.4-C) (aerobic)

Information on: xylene
Elimination information:
87.8 % BOD of the ThOD (28 d) (OECD Guideline 301 F) (aerobic, activated sludge, domestic, non-adapted)
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Bioaccumulation potential

Bioaccumulation potential:
No data available.

13. Disposal Considerations

Do not discharge into drains/surface waters/groundwater.
Observe national and local legal requirements.

Contaminated packaging:
Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

14. Transport Information

Domestic transport:

UN number or ID number:	UN 1263
UN proper shipping name:	PAINT
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	no
Special precautions for user:	None known

Further information
Hazchem Code:3Y
IERG Number:14

Sea transport
IMDG

UN number or ID number:	UN 1263
UN proper shipping name:	PAINT
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	no Marine pollutant: NO
Special precautions for user:	EmS: F-E; S-E

Air transport
IATA/ICAO

UN number or ID number:	UN 1263
UN proper shipping name:	PAINT
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	No Mark as dangerous for the environment is needed
Special precautions for user:	None known

15. Regulatory Information

Other regulations

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.
Tracking requirements do not apply to this substance.
A certified handler is not required for the handling of this substance.

HSNO Approval Number HSR002669
Surface Coatings and Colourants (Flammable, Toxic [6.7]) Group Standard 2017

16. Other Information

For multi-pack systems observe material safety data sheets of all components.Restricted to professional users.

Vertical lines in the left hand margin indicate an amendment from the previous version.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

352-500 0,5L SPOT BLENDER G2

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2025
4.2	08.06.2025	000000000050411592	Date of first issue: 08.06.2025

Section 1: Identification

Product name : 352-500 0,5L SPOT BLENDER G2

Product code : 000000000050411592

Manufacturer or supplier's details

BASF Coatings and Chemetall New Zealand Limited
Level 1, 527A Rosebank Road, Avondale
Auckland 1026
New Zealand
Telephone: 008 837 464, +64 9 820 3888
Telefax number: +64 9 820 3979
E-mail address: nzadmin@basf.com

Emergency contact

Telephone: +64 9 255-4300
E-mail address: ProductSafety_EC_APAC@basf.com, nzadmin@basf.com

Emergency telephone : National Poisons Centre: 0800 764 766
BASF Emergency Advice Number: 0800 944 955 (24 hour advice in an emergency only)
BASF Emergency Advice Number: +61 3 8855 6666 (If calling from outside New Zealand)

Recommended use of the chemical and restrictions on use

Recommended use : Spraying
Thinner

Section 2: Hazard identification

GHS Classification

Flammable liquids : Category 3

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation	:	Category 2
Specific target organ toxicity - single exposure	:	Category 3 (Central nervous system)
Specific target organ toxicity - repeated exposure	:	Category 2 (Kidney, Liver, Central nervous system, Auditory system)
Aspiration hazard	:	Category 1

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements :
H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs (Kidney, Liver, Central nervous system, Auditory system) through prolonged or repeated exposure.

Precautionary Statements :
Prevention:
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 Get medical advice/ attention if you feel unwell.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards which do not result in classification
If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Section 3: Composition/information on ingredients

Chemical nature : acrylic resin
organic solvent

Components

Chemical name	Common Name/Synonyms	CAS-No.	Classification	Concentration (% w/w)
n-Butyl acetate	n-butyl acetate	123-86-4	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 30 -< 50
1-methoxy-2-propylacetate	2-methoxy-1-methylethyl acetate	108-65-6	Flammable liquids, Category 3 Specific target organ toxicity - single exposure (Central nervous system), Category 3	>= 20 -< 30
xylene	xylenes	1330-20-7	Flammable liquids, Category 3 Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2	>= 10 -< 20

			Specific target organ toxicity - single exposure (Respiratory system), Category 3 Specific target organ toxicity - repeated exposure (Kidney, Liver, Central nervous system), Category 2 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 3	
ethylbenzene	ethylbenzene	100-41-4	Flammable liquids, Category 2 Acute toxicity (Inhalation), Category 4 Specific target organ toxicity - repeated exposure (Auditory system), Category 2 Aspiration hazard, Category 1 Hazardous to the aquatic environment - chronic hazard, Category 3	>= 2.5 -< 10

Section 4: First-aid measures

General advice	:	In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product. Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident. Keep patient warm and at rest. Never give anything by mouth to an unconscious person. Move out of dangerous area. Immediately remove contaminated clothing. First aid personnel should pay attention to their own safety.
If inhaled	:	If breathed in, move person into fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician or poison control center immediately.
In case of skin contact	:	Do NOT use solvents or thinners. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
In case of eye contact	:	Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Call a physician immediately. If easy to do, remove contact lens, if worn.
If swallowed	:	Rinse mouth with water. Do not induce vomiting due to aspiration hazard.

Keep at rest.

If swallowed, call a poison control center or doctor immediately.

Most important symptoms and effects, both acute and delayed : Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.

Risk of product entering the lungs on vomiting after ingestion.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Notes to physician : Treat symptomatically.
No known specific antidote.

Section 5: Fire-fighting measures

Suitable extinguishing media : Water spray jet

Dry powder

Alcohol-resistant foam

Carbon dioxide (CO2)

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire fighting : Fire will produce dense black smoke containing hazardous combustion products (see section 10).

Advice for firefighters

Specific extinguishing methods : Cool containers/tanks with water spray.

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

Hazchem Code : 3Y

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures	:	Avoid breathing vapours. For non-emergency personnel: Use personal protective equipment. Ensure adequate ventilation, especially in confined areas. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet.
Environmental precautions	:	If the product contaminates rivers and lakes or drains inform respective authorities. Avoid subsoil penetration. Do not allow uncontrolled discharge of product into the environment.
Methods and materials for containment and cleaning up	:	Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Ensure adequate ventilation.

Section 7: Handling and storage

Advice on protection against fire and explosion :

Avoid all sources of ignition: heat, sparks, open flame.

Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear.

The relevant fire protection measures should be noted.

Use explosion-proof equipment.

Vapors are heavier than air and may spread along floors.

Vapors may form explosive mixtures with air.

Advice on safe handling :

Provide good ventilation of working area (local exhaust ventilation if necessary).

Do not return residues to the storage containers.

Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

The workplace should be equipped with an emergency shower and eye-rinsing facility.

Avoid contact with the skin, eyes and clothing.

		Handle in accordance with good industrial hygiene and safety practice. Do not breathe vapors or spray mist.
Hygiene measures	:	Remove contaminated clothing immediately and dispose of safely. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.
Further information on storage conditions	:	Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Keep in a dry, cool and well-ventilated place.
Materials to avoid	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Packaging material	:	Suitable material: Carbon steel (Iron), tinned carbon steel (Tinplate)

Section 8: Exposure controls/personal protection

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of	Control parameters /	Basis

		exposure)	Permissible concentration	
n-Butyl acetate	123-86-4	WES-STEL	200 ppm 950 mg/m3	NZ OEL
		WES-TWA	150 ppm 713 mg/m3	NZ OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
xylene	1330-20-7	WES-TWA	50 ppm 217 mg/m3	NZ OEL
	Further information: Ototoxin			
		TWA	20 ppm	ACGIH
ethylbenzene	100-41-4	WES-TWA	20 ppm 88 mg/m3	NZ OEL
	Further information: Ototoxin, Skin absorption			
		WES-STEL	40 ppm 176 mg/m3	NZ OEL
	Further information: Ototoxin, Skin absorption			
		TWA	20 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
xylene	1330-20-7	Methylhippuric acid	Urine	End of shift	1.5 g/l	NZ BEI
		Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI
ethylbenzene	100-41-4	Sum of mandelic acid and phenylglyoxylic acids	Urine	End of exposure or end of shift	0.25 g/g creatinine	NZ BEI
		Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Suitable respiratory equipment:

half-mask with A1P2 class combination filter

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection

Remarks : Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g.

nitrile gloves - material thickness: 0,35 mm

Further information on penetration time is available from the manufacturer of the glove.

Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.

The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Request information on glove permeation properties from the glove supplier.

Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Preventive skin protection

Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Eye protection : Required when there is a risk of eye contact.

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Skin and body protection : Anti-static protective clothing

Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

Protective measures : Do not breathe vapour/spray.

Eye wash fountains and safety showers must be easily accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Section 9: Physical and chemical properties

Appearance	:	liquid
Color	:	colorless
Odor	:	hydrocarbon-like
pH	:	substance/mixture is non-polar/aprotic
Melting point/ range	:	not determined
Boiling point/boiling range	:	124 - 167 °C Method: calculated
Flash point	:	24 °C Method: ISO 3679

Flammability	:	Flammable liquid and vapour.
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	> 35 g/m3
Vapor pressure	:	8.4000 hPa (20 °C) Method: calculated not determined (50 °C)
Density	:	0.911 g/cm3 (20 °C)
Solubility(ies)		
Water solubility	:	not determined
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	> 200 °C
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity		
Viscosity, kinematic	:	6.0 mm2/s (23 °C)

		5.10 mm2/s (40 °C)
Flow time	:	< 30 s (23 °C) Cross section: 3 mm Method: ISO 2431
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Self-heating substances	:	The substance or mixture is not classified as self heating.
Metal corrosion rate	:	Not corrosive to metals.
Particle characteristics Particle size	:	The substance / product is marketed or used in a non solid or granular form.

Section 10: Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	Vapours may form ignitable mixture with air.
Conditions to avoid	:	Avoid direct sunlight. Heat, flames and sparks.
Incompatible materials	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Hazardous decomposition	:	No decomposition if stored and applied as directed.

products

Section 11: Toxicological information

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method

Skin corrosion/irritation

Causes skin irritation.

Components:

n-Butyl acetate:

Assessment	:	Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

Based on available data, the classification criteria are not met.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Chronic toxicity

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs (Kidney, Liver, Central nervous system, Auditory system) through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Section 12: Ecological information

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Components:

n-Butyl acetate:

Partition coefficient: n-octanol/water	:	Pow: 200 (25 °C) log Pow: 2.3 (25 °C) pH: 7 Method: OECD Test Guideline 117 GLP: yes

1-methoxy-2-propylacetate:

Partition coefficient: n-octanol/water	:	log Pow: 1.2 (20 °C) pH: 6.8 Method: OECD Test Guideline 117 GLP: yes

xylene:

Partition coefficient: n-octanol/water	:	log Pow: 3.12 - 3.20 (25 °C) GLP: no Remarks: Information taken from reference works and the literature.

ethylbenzene:

Partition coefficient: n-octanol/water	:	Pow: 4,170 (20 °C) log Pow: 3.6 (20 °C) pH: 7.8 GLP: yes

Mobility in soil

No data available

Other adverse effects

No data available

Section 13: Disposal considerations

Disposal methods

Waste from residues	:	Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.
Contaminated packaging	:	Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC Packaging that is not properly emptied must be disposed of as the unused product.

Section 14: Transport information

International Regulations

UNRTDG

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
Environmentally hazardous	:	no

IATA-DGR

UN/ID No.	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III

Labels	:	Flammable Liquids
Packing instruction (cargo aircraft)	:	366
Packing instruction (passenger aircraft)	:	355

IMDG-Code

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
EmS Code	:	F-E, S-E
Marine pollutant	:	no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
Not applicable for product as supplied.

Domestic regulation

NZS 5433

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3

Hazchem Code : 3Y

Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

ERG Code : 128

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

HSNO Approval Number
not allocated

Tolerable Exposure Limits (TEL)

Chemical name	Environmental compartment	Reference concentration
xylene	Air	0.87 mg/m3
	Water	0.6 mg/l

Environmental Exposure Limits (EEL)
Not applicable

Section 16: Other information

Revision Date : 08.06.2025

Further information

Other information	:	For multi-pack systems observe material safety data sheets of all components. Restricted to professional users.
Date format	:	dd.mm.yyyy

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
NZ BEI	:	New Zealand. Biological Exposure Indices
NZ OEL	:	New Zealand. Workplace Exposure Standards for Atmospheric Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NZ OEL / WES-TWA	:	Workplace Exposure Standard - Time Weighted average
NZ OEL / WES-STEL	:	Workplace Exposure Standard - Short-Term Exposure Limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea

Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NZ / EN